

Carlyle / Carrier 5H60 - C109

Specifications

Brand	Carlyle / Carrier
Type	5H60 - C109
Refrigerant	Freon
kW at 0°C/+40°C	131,1
kW at -5°C/+40°C	106,2
kW at -10°C/+40°C	100,0 (at -7°C/+40°C)
kW at -20°C/+40°C	52,3
kW at -30°C/+40°C	33,6 (at -28°C/+40°C)
Electromotor Specs	50/60 Hz - 45/52 kW - 1475/1775 RPM
On steel base frame	✓
Pressure safety switches	✓
Hp/Lp/Op	
Pressure gauges	✓
Hp/Lp/Op	
Liquid line filter drier	✓
m3 / h	195,9
Remarks	Y.o.b. 2002
Sizes	2230x950x1500 mm (LxWxH)
Stock	2



Description

Used Carlyle / Carrier 5H60 - C109

Used Carlyle / Carrier 5H60 - C109 condensing unit. Complete with a Carlyle 5H60 - C109 open-drive reciprocating compressor, Lönne MBC 223-4AA96-Z 225M elektromotor: 50/60 Hz - 45/52 kW - 1475/1775 RPM, liquid receiver, shell and tube as condenser and pressure and safety switches/gauges.

*Why choose for HOSBV? Were not only the largest used refrigeration specialist in Europe, but also, we deliver all equipment including an extensive test, warranty and industrial cleaning. Optional we can arrange shipment and export documents





