

Carrier 30 RQS 160

Specifications

Brand	Carrier
Type	30 RQS 160
Product type	Heat pump
Capacity kW	149,0*
Capacity Tons	*42,4
Refrigerant	Freon
Refrigerant Type	R410A
Pump	✓
Hydronic Module	✓
Weight in kg.	1074
Sizes	2270x2060x1330 mm (LxWxH)
Compressor(s) type & model	4x Copeland ZP182KQE- TFD-604
Display	Carrier Touch pilot junior
Number of fans	2
Fan specifications	50 Hz - 1,4/0,19 kW - 970/480 RPM
Remarks	Y.o.b. 2017
Remarks	*Cooling capacity
Stock	1



Description

Used Carrier 30 RQS 160

Used Carrier 30 RQS 160 reversible chiller / heat pump on R410A build in 2017. Complete with 4x Copeland ZP182KQE-TFD-604 hermetic scroll compressors, condenser with grooved copper tubes and aluminium fins with 2 fans: 50 Hz - 1,4/0,19 kW - 970/480 RPM, plate heat exchanger functioning as evaporator with a volume of 35 liters, 2x Mecasem SAS NGA liquid receivers, Grundfos AC 25-125 water pump and a Carrier Touch pilot junior. *All components of this used chiller will be tested on adequate performance, leak free condition (condensing blocks), compressors, fans, control panel, and so forth). Choosing HOSBV means buying with warranty. We perform an industrial cleaning. *If requested we are happy to arrange your shipment.



1- SERIAL NUMBER NUMERO DI SERIE	M2017006573		
2- MODEL MODELLO	30RQS-160A0277-PE- CE 0062		
17- DESCRIPTION DESCRIZIONE			
3- VARIANT VERSIONE	NGAH		
4- YEAR OF MANUFACTURE AND TEST DATE ANNO E DATA DI COSTRUZIONE	07/06/2017		
18- HERMETICALLY SEALED EQUIPMENT APPARECCHIATURE SIGILLATE ERMETICAMENTE	N		
19- CONTAINS FLUORINATED GREENHOUSE GASES CONTIENE GAS FLUORURATI EFFETTO SERRA	Y		
25- FLUID DURING TRANSPORT LIQUIDI DURANTE IL TRASPORTO	R-410A	37.00	kg
5- REFRIGERANT REFRIGERANTE	R-410A	6- PED GROUP ? GRUPPO PED	GMP 2088
50- CIRCUIT CIRCUITO	A / B / C		
7- FACTORY CHARGE CARICO FABBRICA	18.50 / 18.50 / *	kg	
51- CHARGE ADDED ON SITE CARICO AGGIUNTO IN SEDE	/ / /	kg	
52- TOTAL CHARGE CARICO TOTALE	18.50 / 18.50 / *	kg	
	38.63 / 38.63 / *	t. eq. CO2	
9- INERTING MEDIUM CARICA DI TENUTA	23- NITROGEN		
10- ALLOWABLE PRESSURE MIN/MAX MIN/MAX PRESSIONE AMMISSIBILE	(PS) (-1.0 / 44.2 bar -99.0 / 4420.0 kPa)	21- HIGH PRESSURE ALTA PRESSIONE	22- LOW PRESSURE BASSA PRESSIONE
11- ALLOWABLE TEMPERATURE MIN/MAX MIN/MAX TEMPERATURA AMMISSIBILE	(TS) -20.0 / 68.0 °C	-20.0 / 48.0 °C	
12- PRESSURE SAFETY SWITCH SETTING 1/2 TARATURA PRESSOSTATI DI SICUREZZA 1/2	44.2 / * bar	* / * bar	
13- RELIEF VALVE SETTING PRESSIONE DI INTERVENTO VALVOLA DI SICUREZZA	* bar	* bar	
24- RUPTURE DISKS SETTING PRESSIONE DI INTERVENTO DEI DISCHI DI ROTTURA	* bar	* bar	
14- UNIT LEAK TEST PRESSURE PRESSIONE DI PROVA	17.0 bar		
15- VOLTAGE TENSIONE	400 V	+10 % -10 %	16- PHASES 3 FASE
18- MAXIMUM AMPS MAX CORRENTE	146.10 / *	A	
19- MAX POWER INPUT POTENZA ASSORBITA	71.70 / *	kW	
20- NET WEIGHT PESO NETTO	1074	+5 % -5 %	
		17- FREQUENCY ~ 50 Hz FREQUENZA	44- IP 44

MANUFACTURED IN FRANCE BY
 CARRIER SCS - 01120 MONTLUEL - FRANCE
 AN AFFILIATED COMPANY OF CARRIER CORPORATION
 FARMINGTON CT, USA

PLS TRUCK V41







