

Bitzer 4FE-28Y-40P

Specifications

Brand	Bitzer
Type	4FE-28Y-40P
Refrigerant	Freon
kW at 0°C/+40°C	84,4
kW at -5°C/+40°C	70,5
kW at -10°C/+40°C	58,4
kW at -20°C/+40°C	38,7
kW at -30°C/+40°C	24,2
kW at -40°C/+40°C	13,6
kW at -45°C/+40°C	9,6
On steel base frame	✓
Pressure safety switches	✓
Hp/Lp/Op	
Liquid receiver	✓
Liquid receiver ltr.	25
m ³ / h	101,8
Remarks	Y.o.b. 2016
Condensing Unit	✓
Sizes	2100x1100x1950 mm (LxWxH)
Stock	1



Description

Used Bitzer 4FE-28Y-40P

Used Bitzer 4FE-28Y-40P condensing unit on Freon. Complete with 1 Bitzer 4FE-28Y-40P semi-hermetic reciprocating compressor, condensor with 2 EBM-Papst A6E630-AN01-01 fans - 50 Hz - 0,60 kW - 860 RPM - diameter 630 mm, OCSCOLD RLV 25L liquid receiver with a volume of 25 liter and pressure and safety switches. The compressor has a displacement of 101,8 m³/h.

*Why choose for HOSBV? We are not only the largest used refrigeration specialist in Europe, but also, we deliver all equipment including an extensive test, warranty and an industrial cleaning. *Optionally we can also perform a new paint job and arrange the logistics.



PS
KOELTECHNIEK & KLIMAATBEHEERSING

PS Koeltechniek Deventer B.V.
Maagdenburgstraat 40
7421 ZE Deventer
Tel. 0570 624784
info@ps-koeltechniek.nl
www.ps-koeltechniek.nl

Installatienummer	P0187.2855.16.7-3		
Type / naam koelinstallatie	Vriescel Telson		
Type koudemiddel	R 449A	GWP Koudemiddel	1397
Nom. vulling in kg	30	Nom. vulling in ton CO2-eq.	41,91
PED categorie	II		
Max. PS / TS HD	28 bar	60°C	CE 1117
Max. PS / TS LD	16 bar	36°C	
Bouwjaar	2016		
Logboek aanwezig	Ja		





