

# Bitzer 6FE-50Y-40P

## Specifications

|                              |   |
|------------------------------|---|
| Brand                        | Bitzer  |
| Type                         | 6FE-50Y-40P   |
| Refrigerant                  | Freon   |
| kW at 0°C/+40°C              | 124,6   |
| kW at -5°C/+40°C             | 103,8   |
| kW at -10°C/+40°C            | 85,6  |
| kW at -20°C/+40°C            | 56,3  |
| kW at -30°C/+40°C            | 34,5  |
| kW at -40°C/+40°C            | 18,8  |
| kW at -45°C/+40°C            | 12,8  |
| Condensing pressure switches | ✓   |
| Oil level system AC&R        | ✓   |
| Sight Glass                  | ✓   |
| m <sup>3</sup> / h           | 50 Hz - 151,6 m <sup>3</sup> /h / 60 Hz - 183,1 m <sup>3</sup> /h |
| Remarks                      | Y.o.b. 2013   |
| Sizes                        | 800x600x440 mm (LxWxH)  |
| Stock                        | 1   |



## Description

### Used Bitzer 6FE-50Y-40P

Used Bitzer 6FE-50Y-40P semi-hermetic reciprocating compressor on Freon with a Henry Technologies S-9530 oil level system AC&R, condensing pressure switch and sight glass. The compressor has a displacement of 151,6 m<sup>3</sup>/h at 50 Hz and 183,1 m<sup>3</sup>/h at 60 Hz.

\*Why choose for HOSBV? Were not only the largest used refrigeration specialist in Europe, but also, we deliver all equipment including an extensive test, warranty and industrial cleaning.

\*Optional we can also perform a new paint job and arrange the logistics.



