

# Bitzer 4G.2

## Specifications

|                          |                                      |
|--------------------------|--------------------------------------|
| Brand                    | Bitzer                               |
| Type                     | 4G.2                                 |
| Refrigerant              | Freon                                |
| kW at 0°C/+40°C          | 70,8                                 |
| kW at -5°C/+40°C         | 58,7                                 |
| kW at -10°C/+40°C        | 48,1                                 |
| kW at -20°C/+40°C        | 31,2                                 |
| kW at -30°C/+40°C        | 18,8                                 |
| kW at -40°C/+40°C        | 10,1                                 |
| Electromotor Specs       | 22                                   |
| Unloaded Start           | ✓                                    |
| Pressure safety switches | ✓                                    |
| Hp/Lp/Op                 |                                      |
| Remarks                  | # // Electromotor: 22 kW at 1465 RPM |
| Remarks                  | R404a - R22 or other freon types     |
| Sizes                    | 1300x400x500 mm (LxWxH)              |
| Stock                    | 1                                    |



## Description

### Used Bitzer 4G.2

Used Bitzer 4G.2 freon compressor, complete with unloaded start and safety pressure switches. This unit has a cooling capacity of 70,8 kW at 0°C/+40°C.

Why choose for HOSBV? Were not only the largest used refrigeration specialist in Europe, but also, we deliver all equipment including an extensive test, warranty and deliver after an industrial cleaning. \*If requested we are happy to arrange your logistics.

