

Helpman LEX 24-H

Specifications

Brand	Helpman
Type	LEX 24-H
kW	17,8
Refrigerant	Freon
Number of Fans	2
Fin Space in mm	7
Defrosting	Electric
m ³ /h	11600
Sizes	1880x770x810 mm (LxWxH)
Remarks	Surface 69,8 m ²
Remarks	Diameter fan 50 cm
Weight	128 kg
Stock	1



Description

Used Helpman LEX 24-H

Used blow-through unit cooler Helpman LEX-24-E with electric defrosting. diameter 50 cm.

*All components of this used evaporator will be tested on good working, leak free condition (electro engines, coils, bearings). Choosing HOSBV means buying with warranty. We perform a industrial cleaning and rust spots will be covered. Also, we can arrange your shipment.



Blow Through Unit Coolers 1.5 - 40 kW HELPMAN LEX



Nominal Capacities (kW)

Cooler type	R 22	R 134a	R 404A	For reference only		
	frosted DT ₁	frosted DT ₁	frosted DT ₁	dry conditions DT ₁ R 22 R 134a R 404A		
Fin spacing 4 mm						
LEX 2-4	1.5	1.3	1.5	1.3	1.1	1.3
LEX 4-4	1.9	1.5	1.8	1.7	1.3	1.6
LEX 6-4	2.8	2.4	2.8	2.4	2.1	2.5
LEX 8-4	4.7	4.1	4.7	4.1	3.5	4.1
LEX 10-4	4.7	4.4	4.8	4.1	3.8	4.2
LEX 12-4	5.9	5.6	6.2	5.1	4.9	5.4
LEX 14-4	6.5	6.4	7.1	5.7	5.6	6.2
LEX 16-4	8.7	8.4	9.3	7.5	7.3	8.1
LEX 18-4	9.7	8.7	9.8	8.5	7.8	8.6
LEX 20-4	12.9	10.8	12.7	11.2	9.4	11.0
LEX 22-4	16.1	13.0	15.4	14.0	11.3	13.4
LEX 24-4	20.0	16.1	19.2	17.4	14.0	16.7
LEX 26-4	26.0	23.0	26.0	22.6	20.0	22.6
LEX 28-4	28.8	29.9	33.2	28.5	25.2	28.9
LEX 30-4	40.3	39.3	38.5	35.0	29.3	33.4
Fin spacing 7 mm						
LEX 2-7	1.3	1.2	1.3	1.1	1.0	1.2
LEX 4-7	1.7	1.4	1.7	1.5	1.2	1.4
LEX 6-7	2.5	2.2	2.5	2.2	1.9	2.2
LEX 8-7	4.1	3.7	4.3	3.6	3.3	3.7
LEX 10-7	3.7	3.6	4.0	3.2	3.2	3.5
LEX 12-7	5.0	4.9	5.3	4.4	4.3	4.6
LEX 14-7	5.5	5.5	6.0	4.8	4.8	5.2
LEX 16-7	7.4	7.3	8.0	6.4	6.3	7.0
LEX 18-7	8.5	7.8	8.9	7.4	6.8	7.6
LEX 20-7	11.4	10.0	11.4	9.9	8.7	9.9
LEX 22-7	14.5	12.4	14.5	12.6	10.7	12.4
LEX 24-7	18.1	15.8	17.8	15.7	13.5	15.5
LEX 26-7	22.8	21.2	23.4	19.8	18.4	20.4
LEX 28-7	28.5	28.5	29.3	24.8	23.0	25.5
LEX 30-7	36.5	31.0	35.9	31.7	27.0	31.2

Capacities

Frosted Conditions
 -Lightly frosted coil.
 -Relative humidity 95 %
 -Suction gas superheating 62 % of the temperature difference (DT₁), with a minimum of 3.5 K