

DWM DLJP-30X-EWL

Specifications

| | |
|-------------------|----------------------------------|
| Brand | DWM |
| Type | DLJP-30X-EWL |
| Refrigerant | Freon |
| kW at 0°C/+40°C | 11.81 |
| kW at -5°C/+40°C | 9.76 |
| kW at -10°C/+40°C | 7.96 |
| kW at -20°C/+40°C | 5.06 |
| kW at -30°C/+40°C | 2.93 |
| kW at -40°C/+40°C | 1.41 |
| kW at -45°C/+40°C | 0.82 |
| m3 / h | 14.5 |
| Remarks | 1450 RPM |
| Remarks | R404a - R22 or other freon types |
| Remarks | y.o.b. 2003 |
| Weight in kg. | 89 |
| Stock | 1 |



Description

Used DWM DLJP-30X-EWL

Used semi-hermetic reciprocating compressor DWM - Copeland DLJP-30X-EWL. Our capacity table is based on the used type of Freon. You can also use this compressor(s) on alternative types of Freon. For all the other specs (if available), see the picture of the manufacturer model plate or the attached pdf file. *Why choose for HOSBV? We're not only the largest used refrigeration specialist in Europe, but also, we deliver all equipment including an extensive test, warranty and industrial cleaning. *Optional we can also perform a new paint job and arrange the logistics.



Model: DLJ-30 X
Capacity

R404A/R507

Cooling capacity [kW]

| $t_c \setminus t_a$ | -45 | -40 | -35 | -30 | -25 | -20 | -15 | -10 | -5 | 0 | 5 |
|---------------------|------|------|------|------|------|------|------|-------|-------|-------|-------|
| 20 | 1.83 | 2.57 | 3.48 | 4.58 | 5.89 | 7.43 | 9.23 | 11.31 | 13.68 | 16.37 | 19.40 |
| 25 | 1.57 | 2.27 | 3.12 | 4.16 | 5.38 | 6.83 | 8.51 | 10.46 | 12.68 | 15.21 | 18.07 |
| 30 | 1.31 | 1.98 | 2.78 | 3.74 | 4.89 | 6.23 | 7.80 | 9.62 | 11.70 | 14.07 | 16.75 |
| 35 | 1.06 | 1.69 | 2.44 | 3.33 | 4.40 | 5.64 | 7.10 | 8.79 | 10.72 | 12.93 | 15.44 |
| 40 | 0.82 | 1.41 | 2.11 | 2.93 | 3.91 | 5.06 | 6.41 | 7.96 | 9.76 | 11.81 | 14.14 |
| 45 | 0.57 | 1.13 | 1.78 | 2.54 | 3.44 | 4.49 | 5.72 | 7.15 | 8.80 | 10.70 | 12.85 |
| 50 | - | 0.85 | 1.45 | 2.15 | 2.96 | 3.92 | 5.04 | 6.35 | 7.85 | 9.59 | 11.57 |
| 55 | - | 0.58 | 1.13 | 1.76 | 2.49 | 3.36 | 4.37 | 5.55 | 6.91 | - | - |

Power input [kW]

| $t_c \setminus t_a$ | -45 | -40 | -35 | -30 | -25 | -20 | -15 | -10 | -5 | 0 | 5 |
|---------------------|------|------|------|------|------|------|------|------|------|------|------|
| 20 | 1.35 | 1.59 | 1.83 | 2.04 | 2.22 | 2.36 | 2.46 | 2.51 | 2.49 | 2.40 | 2.24 |
| 25 | 1.30 | 1.58 | 1.84 | 2.09 | 2.32 | 2.51 | 2.67 | 2.77 | 2.82 | 2.80 | 2.71 |
| 30 | 1.24 | 1.54 | 1.84 | 2.12 | 2.39 | 2.63 | 2.83 | 3.00 | 3.11 | 3.16 | 3.14 |
| 35 | 1.16 | 1.48 | 1.81 | 2.13 | 2.43 | 2.71 | 2.97 | 3.18 | 3.35 | 3.47 | 3.52 |
| 40 | 1.08 | 1.42 | 1.77 | 2.12 | 2.46 | 2.78 | 3.08 | 3.34 | 3.57 | 3.74 | 3.86 |
| 45 | 1.00 | 1.35 | 1.72 | 2.10 | 2.47 | 2.83 | 3.17 | 3.48 | 3.75 | 3.99 | 4.17 |
| 50 | - | 1.29 | 1.68 | 2.08 | 2.47 | 2.87 | 3.24 | 3.60 | 3.93 | 4.21 | 4.45 |
| 55 | - | 1.24 | 1.64 | 2.06 | 2.48 | 2.90 | 3.32 | 3.71 | 4.08 | - | - |