


Qty. Description

1 LP 65-125/117 A-F-A-AUUE



Note! Product picture may differ from actual product

Product No.: [48000031](#)

Single-stage centrifugal in-line single-head pump.

The in-line design with opposite suction and discharge ports enables mounting in pipework or on a concrete foundation.

The shaft seal is a corrosion resistant maintenance-free mechanical seal.

Liquid:

Pumped liquid: Water
 Liquid temperature range: 0 .. 90 °C
 Selected liquid temperature: 20 °C
 Density: 998.2 kg/m³

Technical:

Pump speed on which pump data are based: 2900 rpm
 Rated flow: 34 m³/h
 Rated head: 15 m
 Actual impeller diameter: 117 mm
 Impeller nom: 125 mm
 Primary shaft seal: AUUE

Materials:

Pump housing: Cast iron
 EN-JL1040
 ASTM 35-40
 Impeller: Stainless steel
 DIN W.-Nr. 1.4301
 AISI 304

Installation:

Max pressure at stated temp: 16 bar / 90 °C
 Flange standard: DIN
 Pipe connection: DN 65
 Pressure rating: PN 16
 Port-to-port length: 475 mm
 Flange size for motor: F115

Electrical data:

Power (P2) required by pump: 2.2 kW

Others:

Net weight: 32.2 kg

Description	Value
General information:	
Product name:	LP 65-125/117 A-F-A-AUUE
Product No:	48000031
EAN number:	5700390472900
Price:	
Technical:	
Pump speed on which pump data are based:	2900 rpm
Rated flow:	34 m ³ /h
Rated head:	15 m
Actual impeller diameter:	117 mm
Impeller nom:	125 mm
Primary shaft seal:	AUUE
Pump version:	A
Model:	C
Materials:	
Pump housing:	Cast iron
Pump housing:	EN-JL1040
Pump housing:	ASTM 35-40
Impeller:	Stainless steel
Impeller:	DIN W.-Nr. 1.4301
Impeller:	AISI 304
Material code:	A
Installation:	
Max pressure at stated temp:	16 bar / 90 °C
Flange standard:	DIN
Pipe connection:	DN 65
Pressure rating:	PN 16
Port-to-port length:	475 mm
Flange size for motor:	F115
Connect code:	F
Liquid:	
Pumped liquid:	Water
Liquid temperature range:	0 .. 90 °C
Selected liquid temperature:	20 °C
Density:	998.2 kg/m ³
Electrical data:	
Power (P2) required by pump:	2.2 kW
Others:	
Net weight:	32.2 kg

