



---

## Dry cooler

### Goedhart KOAD 50N/3-6P

---

Capacity:	<b>49,8 kW</b>	Medium:	<b>Propylene glycol 55 %</b>
Air flow:	<b>13.610,0 m<sup>3</sup>/h</b>	Inlet:	<b>50,0 °C</b>
Air inlet:	<b>30,0 °C</b>	Outlet:	<b>40,2 °C</b>
Air outlet:	<b>41,3 °C</b>	Pressure drop:	<b>0,30 bar</b>
		Volume flow:	<b>4,35 m<sup>3</sup>/h</b>

---

Capacity:	<b>88,7 kW</b>	Medium:	<b>Ethylene glycol 34 %</b>
Air flow:	<b>13.610,0 m<sup>3</sup>/h</b>	Inlet:	<b>60,0 °C</b>
Air inlet:	<b>25,0 °C</b>	Outlet:	<b>40,0 °C</b>
Air outlet:	<b>44,6 °C</b>	Pressure drop:	<b>0,22 bar</b>
		Volume flow:	<b>4,2 m<sup>3</sup>/h</b>

---

Fans:	<b>3 Pieces 1~220V 50Hz</b>
Speed:	<b>880 min<sup>-1</sup></b>
Capacity:	<b>0,4 kW</b>

---

Surface:	<b>146,0 m<sup>2</sup></b>	Tubes:	<b>Copper</b>
Tube volume:	<b>18,0 dm<sup>3</sup></b>	Fins:	<b>Aluminium</b>
Fin spacing:	<b>2,4 mm</b>	Passes:	<b>4</b>
		Distributions:	<b>12</b>