

Model	Nominal capacities R404A		AC fans 400/50/3									Connections	
			fan		Sound		air		coil	Int.	OD		
	Capacity SC 15		nr.	power		pressure		flow		surface	volume	in	out
AGQ	D kW	Y kW		D W	Y W	D dB(A)	Y dB(A)	D m <sup>3</sup> /h	Y m <sup>3</sup> /h	m <sup>2</sup>	dm <sup>3</sup>	mm	mm
Noise level Q													
AGQ501 A	13.1	10.6	1	150	80	29	23	3763	2771	29.3	3.3	16	16
AGQ501 B	15.7	12.3	1	150	80	29	23	3530	2589	43.9	4.9	16	16
AGQ501 C	16.4	12.6	1	150	80	29	23	3327	2433	58.6	6.5	18	18
AGQ502 A	26.2	21.2	2	300	160	32	26	7527	5542	58.6	6.2	22	22
AGQ502 B	31.3	24.7	2	300	160	32	26	7060	5178	87.8	9.3	28	28
AGQ502 C	32.8	25.1	2	300	160	32	26	6654	4866	117.1	12.2	28	28
AGQ503 A	40.2	32.5	3	450	240	34	28	11290	8313	87.8	9.1	28	28
AGQ503 B	47.1	37.1	3	450	240	34	28	10590	7767	131.8	13.9	35	35
AGQ503 C	50.2	38.5	3	450	240	34	28	9981	7299	175.7	18.1	35	35
AGQ504 A	52.5	42.4	4	600	320	35	29	15050	11080	117.1	12.3	35	35
AGQ504 B	61.5	48.4	4	600	320	35	29	14120	10360	175.7	17.9	35	35
AGQ504 C	67.6	51.7	4	600	320	35	29	13310	9732	234.2	23.4	35	35
AGQ631 A	19.0	-	1	235	-	31	-	5537	-	40.7	4.6	18	18
AGQ631 B	22.8	-	1	235	-	31	-	5248	-	61.0	6.9	22	22
AGQ631 C	24.7	-	1	235	-	31	-	4993	-	81.3	9.0	22	22
AGQ632 A	38.2	-	2	470	-	34	-	11070	-	81.3	8.8	28	28
AGQ632 B	45.3	-	2	470	-	34	-	10500	-	122.0	13.5	35	35
AGQ632 C	48.8	-	2	470	-	34	-	9986	-	162.7	17.4	35	35
AGQ633 A	55.9	-	3	705	-	36	-	16610	-	122.0	13.2	35	35
AGQ633 B	69.1	-	3	705	-	36	-	15740	-	183.0	19	35	35
AGQ633 C	74.6	-	3	705	-	36	-	14980	-	244.0	25.6	42	42
AGQ634 A	76.4	-	4	940	-	37	-	22150	-	162.7	16.9	35	35
AGQ634 B	90.6	-	4	940	-	37	-	20990	-	244.0	25.3	42	42
AGQ634 C	97.7	-	4	940	-	37	-	19970	-	325.3	32.9	42	42
AGQ635 A	96.7	-	5	1175	-	38	-	27690	-	203.3	21.4	42	42
AGQ635 B	114.7	-	5	1175	-	38	-	26240	-	305.0	32.4	54	54
AGQ635 C	123.6	-	5	1175	-	38	-	24970	-	406.6	41.9	54	54
AGQ636 A	116.6	-	6	1410	-	38	-	33220	-	244.0	26.7	54	54
AGQ636 B	138.3	-	6	1410	-	38	-	31490	-	366.0	38.0	54	54
AGQ636 C	149.4	-	6	1410	-	38	-	29960	-	488.0	49.3	54	54