



Selection: Semi-hermetic Reciprocating Compressors

Input Values

Compressor model	(4FC-5.F1Y)	Suction gas temperature	20,00 °C
Mode	Refrigeration and Air conditioning	Operating mode	Auto
Refrigerant	R404A	Power supply	400V-3-50Hz
Reference temperature	Dew point temp.	Frequency compressor	80,0 Hz
Liq. subc. (in condenser)	0 K	Useful superheat	100%


Result

Q [W]	Cooling capacity	COP [-]	COP/EER
Qu* [W]	Evaporator capacity	m [kg/h]	Mass flow
P [kW]	Power input	Op.	Operating mode
I [A]	Current	th [°C]	Discharge gas temp. w/o cooling
Qc [W]	Condenser capacity		





tc	to	5°C	0°C	-5°C	-10°C	-15°C	-20°C	-25°C	-30°C
30°C	Q [W]	30974	25969	21622	17850	14583	11765	9345	7277
	Qu* [W]	30974	25969	21622	17850	14583	11765	9345	7277
	P [kW]	6,87	6,80	6,60	6,30	5,91	5,43	4,89	4,30
	I [A]	10,71	10,60	10,33	9,90	9,34	8,66	7,88	7,02
	Qc [W]	37842	32765	28225	24151	20489	17195	14233	11572
	COP [-]	4,51	3,82	3,27	2,83	2,47	2,17	1,91	1,69
	m [kg/h]	798	660	543	444	360	288	228	176,3
	Op.	Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard
	th [°C]	60,7	68,0	75,7	83,7	92,2	101,2	110,8	120,9
	40°C	Q [W]	26200	21943	18231	14998	12192	9766	7678
Qu* [W]		26200	21943	18231	14998	12192	9766	7678	5891
P [kW]		8,30	8,00	7,59	7,09	6,50	5,85	5,14	4,39
I [A]		12,74	12,32	11,73	11,02	10,19	9,26	8,24	7,16
Qc [W]		34499	29944	25824	22088	18695	15613	12815	10280
COP [-]		3,16	2,74	2,40	2,12	1,88	1,67	1,49	1,34
m [kg/h]		764	629	516	420	338	269	210	160,1
Op.		Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard
th [°C]		73,0	80,4	88,2	96,4	105,0	114,0	123,5	133,6
50°C		Q [W]	21488	17961	14872	12172	9824	7790	6039
	Qu* [W]	21488	17961	14872	12172	9824	7790	6039	4542
	P [kW]	9,55	9,03	8,41	7,71	6,94	6,11	5,24	4,35
	I [A]	14,57	13,81	12,91	11,90	10,80	9,63	8,39	7,09
	Qc [W]	31038	26992	23284	19882	16760	13897	11277	8888
	COP [-]	2,25	1,99	1,77	1,58	1,42	1,28	1,15	1,04
	m [kg/h]	729	598	488	394	315	247	190,2	142,1
	Op.	Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard
	th [°C]	85,2	92,8	100,7	109,0	117,8	126,9	136,5	0

-- No calculation possible (see message in single point selection)

Application Limits 4FC-5.F1




Legend

-  additional cooling & suction gas superheat $\leq 20\text{K}$
-  additional cooling or suction gas superheat $\leq 20\text{K}$
-  application limits of individual compressors depend on max. power consumption of frequency inverter
-  A



Technical Data: (4FC-5.F1Y)

Dimensions and Connections



Technical Data

Technical Data

Displacement (1450 RPM 50Hz)	18,05 m ³ /h
Displacement (1750 RPM 60Hz)	21,78 m ³ /h
Displacement at 87 Hz	32,0 m ³ /h
Frequency range	25..87 Hz
No. of cylinder x bore x stroke	4 x 41 mm x 39,3 mm
Weight	105 kg
Max. pressure (LP/HP)	19 / 28 bar
Connection suction line	28 mm - 1 1/8"
Connection discharge line	16 mm - 5/8"
Oil type R134a/R407C/R404A/R507A/R407A/R407F	tc<55°C: BSE32 tc>55°C: BSE55 (Option)
Oil type R22 (R12/R502)	B5.2 (Standard)

Motor data

Electrical data frequency inverter

Voltage	380..480V/3/50_60Hz
Max operating current	20.0 A
Max. Power input	11,0 kW

Extent of delivery (Standard)

Motor protection	SE-B1
Enclosure class	IP65
Vibration dampers	Standard
Oil charge	2,00 dm ³

Available Options

Discharge gas temperature sensor	Option
Additional fan	Option
Crankcase heater	0..120 W PTC (Option)
Oil level monitoring	OLC-K1 (Option)

Sound measurement

Sound power level (-10°C / 45°C)	68,8 dB(A) @ 50Hz
with sound jacket	60,8 dB(A) @ 50Hz
Sound pressure level @ 1m (-10°C / 45°C)	60,8 dB(A) @ 50Hz
with sound jacket	52,8 dB(A) @ 50Hz



Semi-hermetic Reciprocating Compressors

Motor 1 = e.g. 4TES-12 with 12"HP", primary for air-conditioning (e.g. R22,R407C) and air-conditioning with R134a at high ambient temperatures.

Motor 2 = e.g. 4TES-9 with 8"HP", universal Motor for medium and low temperature application (e.g. R404A, R507A, R407A, R407F) and air-conditioning with R134a

Motor 3 = e.g. 4TES-8, for medium temperature applications and R134a

For more information concerning the application range use the "Limits" button.

Operation modes 4VES-7 to 6FE-44 and 44JE-30 to 66FE-88 with R407F/R407A/R22

CIC = liquid injection with low temperature application, suction gas cooled motor.

ASERCOM certified performance data

The Association of European Refrigeration Component Manufacturers has implemented a procedure of certifying performance data. The high standard of these certifications is assured by:

- * plausibility tests of the data performed by experts.
- * regular measurements at independent institutes.

These high efforts result in the fact that only a limited number of compressors can be submitted. Due to this not all BITZER compressors are certified until now. Performance data of compressors which fulfil the strict requirements may carry the label "ASERCOM certified". In this software you will find the label at the respective compressors on the right side below the field "result" or in the print out of the performance data. All certified compressors and further information are listed on the homepage of ASERCOM.

Condensing capacity

The condensing capacity can be calculated with or without heat rejection. This option can be set in the menu Program Options. The heat rejection is constantly 5% of the power consumption. The condensing capacity is to be found in the line Condensing cap. (with HR) resp. Condensing capacity.

Data for sound emission

Data based on 50HZ application (IP-units 60Hz) and R404A if not declared.

Sound pressure level: values based on free field area conditions with hemispherical sound emission in 1 meter distance.

General remarks regarding sound data

Listed sound data were measured under testing conditions in our laboratory. For this purpose the free-standing test sample is mounted on a solid foundation plate and the pipework is connected vibration-free to the largest extend possible. Suction and discharge lines are fixed in a flexible configuration, such that a transmission of vibrations to the environment can be largely excluded. In real installations considerable differences might be observed, compared to the measurements in the laboratory. The airborne sound emitted by the compressor can be reflected from surfaces of the system and this may increase the airborne sound level measured close to the compressor. Vibrations caused by the compressor are also transferred to the system by the compressor feet and piping depending on the damping ratio of the fixings. Thus, the vibrations can induce other components to such an extent that these components contribute to an increase in airborne sound emission. If required, the transfer of vibrations to the system can be minimized by suitable fixing and damping elements.

Legend of connection positions according to "Dimensions":

- 1 High pressure connection (HP)
- 2 Connection for discharge gas temperature sensor (HP) (for 4VE(S)-6Y .. 4NE(S)-20(Y) connection for CIC sensor as alternative)
- 3 Low pressure connection (LP)
- 4 CIC system: injection nozzle (LP)
- 4b Connection for CIC sensor
- 4c Connection for CIC sensor (MP / operation with liquid subcooler)
- 5 Oil fill plug
- 6 Oil drain
- 7 Oil filter (magnetic screw)
- 8 Oil return (oil separator)
- 8* Oil return with NH3 and insoluble oil
- 9 Connection for oil and gas equalization (parallel operation)
- 9a Connection for gas equalization (parallel operation)



- 9b Connection for oil equalization (parallel operation)
 - 10 Oil heater connection
 - 11 Oil pressure connection +
 - 12 Oil pressure connection –
 - 13 Cooling water connection
 - 14 Intermediate pressure connection (MP)
 - 15 Liquid injection (operation without liquid subcooler and with thermostatic expansion valve)
 - 16 Connection for oil monitoring (opto-electrical oil monitoring "OLC-K1" or differential oil pressure switch "Delta-PII")
 - 17 Refrigerant inlet at liquid subcooler
 - 18 Refrigerant outlet at liquid subcooler
 - 19 Clamp space
 - 20 Terminal plate
 - 21 Maintenance connection for oil valve
 - 22 Pressure relief valve to the atmosphere (discharge side)
 - 23 Pressure relief valve to the atmosphere (suction side)
 - 24 IQ MODULE
 - SL Suction gas line
 - DL Discharge gas line
- Dimensions can show tolerances according to EN ISO 13920-B.