



---

## Dry cooler

### Guntner S-GVH 066A/2x6L

---

Capacity:	<b>158,4 kW</b>	Medium:	<b>Ethylene glycol 34 Vol. %</b>
Air flow:	<b>107.500,0 m<sup>3</sup>/h</b>	Inlet:	<b>40,0 °C</b>
Air inlet:	<b>25,0 °C</b>	Outlet:	<b>35,0 °C</b>
Air outlet:	<b>29,4 °C</b>	Pressure drop:	<b>0,90 bar</b>
		Volume flow:	<b>29,8 m<sup>3</sup>/h</b>

---

Capacity:	<b>612,8 kW</b>	Medium:	<b>Ethylene glycol 34 Vol. %</b>
Air flow:	<b>107.500,0 m<sup>3</sup>/h</b>	Inlet:	<b>60,0 °C</b>
Air inlet:	<b>25,0 °C</b>	Outlet:	<b>40,0 °C</b>
Air outlet:	<b>42,2 °C</b>	Pressure drop:	<b>0,81 bar</b>
		Volume flow:	<b>28,8 m<sup>3</sup>/h</b>

---

Fans:	<b>12 Pieces 3~400V 50Hz</b>
Speed:	<b>880 min<sup>-1</sup></b>
Capacity:	<b>0,50 kW</b>

---

Surface:	<b>935,9 m<sup>2</sup></b>	Tubes:	<b>Copper</b>
		Fins:	<b>Aluminium</b>