

WRVi 321mm range



Oil injected screw compressors Product specifications





Howden's WRV range of screw compressors are well proven, offer high reliability and versatility, and are designed for a wide range of applications. Our double-walled casing design, robust and highly reliable oil injected range, which includes the world's largest capacity oil injected screw compressors.



Max pressure	24.1 bar g	350 psi g			
Min flow	1919 sm³/hr	1129 CFM			
Max flow	7675 sm³/hr	4517CFM			
Min speed	1500 rpm				
Max speed	3600 rpm				
Max power	2044 kW	2741 hp			



Features and benefits

Thrust bearings: Angular contact or tilted pad.

Sleeve type journal bearings: Long operational life span.

Double wall construction: Low operating noise and suitable for high pressure application.

Optional casing and rotor material of construction: Flexibility to match project specification (eg. API 619).

Shaft seal options: Variety of standard and zero emission arrangements.

Range of capability: Probably the most comprehensive range of capacities available in the marketplace.

Variable Vi: Available with variable Vi.

Installed compressors: More than 25,000 WRV compressors installed worldwide.

WRV 321 illustrative performance

WRV 321 variants	Speed rpm	Swept volume m³/hr	Nominal capacities in kW for R717			Dimensions	Weight	Sound
			High stage -10/+35°C	Booster -40/-10°C	With economiser -40/+35°C	in mm basic unit L x W x H	(basic direct drive unit) kg / Ibs	pressure level dBa
WRV321/132	3000	3830	2457	772	747	2005x940x971	2925 / 6447	90
WRV321/165	3000	4790	3071	967	934	2110x940x971	3150 / 6943	90
WRV321/193	3000	5260	3456	1086	1090	2200x940x971	3260 / 7186	90
WRV321/220	3000	6385	4095	1290	1245	2345x940x971	3500 / 2715	90

For more information on Howden screw compressors, contact:

Howden Compressors Ltd. 133 Barfillan Drive, Glasgow G52 1BE, Scotland, United Kingdom

Tel: + 44 (0) 141 885 7500

Fax: + 44 (0) 141 882 8648

Email: hcl.sales@howden.com

Revolving Around You™