



---

## Dry cooler

### Lu-Ve

---

Capacity:	<b>58,6 kW</b>	Medium:	<b>Ethylene glycol 34 Vol. %</b>
Air flow:	<b>46.800,0 m<sup>3</sup>/h</b>	Inlet:	<b>40,0 °C</b>
Air inlet:	<b>25,0 °C</b>	Outlet:	<b>35,0 °C</b>
Air outlet:	<b>28,8 °C</b>	Pressure drop:	<b>0,90 bar</b>
		Volume flow:	<b>11,0 m<sup>3</sup>/h</b>

---

Capacity:	<b>210,7 kW</b>	Medium:	<b>Ethylene glycol 34 Vol. %</b>
Air flow:	<b>46.800,0 m<sup>3</sup>/h</b>	Inlet:	<b>60,0 °C</b>
Air inlet:	<b>25,0 °C</b>	Outlet:	<b>40,0 °C</b>
Air outlet:	<b>38,6 °C</b>	Pressure drop:	<b>0,70 bar</b>
		Volume flow:	<b>9,9 m<sup>3</sup>/h</b>

---

Fans:	<b>3 Pieces 3~400V 50Hz</b>
Speed:	<b>880 min<sup>-1</sup></b>
Capacity:	<b>1,45 kW</b>

---

Surface:	<b>285,2 m<sup>2</sup></b>	Tubes:	<b>Copper</b>
Fin spacing:	<b>2,4 mm</b>	Fins:	<b>Aluminium</b>
		Passes:	<b>4</b>
		Distributions:	<b>33</b>