



---

## Dry cooler

---

Capacity:	<b>8,2 kW</b>	Medium:	<b>Ethylene glycol 34 Vol. %</b>
Air flow:	<b>2.000,0 m<sup>3</sup>/h</b>	Inlet:	<b>40,0 °C</b>
Air inlet:	<b>25,0 °C</b>	Outlet:	<b>35,0 °C</b>
Air outlet:	<b>37,4 °C</b>	Pressure drop:	<b>0,14 bar</b>
		Volume flow:	<b>1,5 m<sup>3</sup>/h</b>

---

Capacity:	<b>15,2 kW</b>	Medium:	<b>Ethylene glycol 34 Vol. %</b>
Air flow:	<b>2.000,0 m<sup>3</sup>/h</b>	Inlet:	<b>60,0 °C</b>
Air inlet:	<b>25,0 °C</b>	Outlet:	<b>40,0 °C</b>
Air outlet:	<b>47,9 °C</b>	Pressure drop:	<b>0,03 bar</b>
		Volume flow:	<b>0,7 m<sup>3</sup>/h</b>

---

Surface:	<b>35,2 m<sup>2</sup></b>	Tubes:	<b>Stainless steel</b>
		Passes:	<b>20</b>
		Distributions:	<b>3</b>