

COMPACT AIR COOLERS



WELCOME TO GÜNTNER

With nearly a century of technological and engineering excellence, our air coolers are second to none. High quality, robust and reliable products give your business the very best.

Güntner standardised COMPACT Air Coolers come in a smart design and impress with their quality and performance.

Our COMPACT Air Cooler range is created with hygiene in mind, assuring that the units are perfectly suited for use in areas with stringent hygiene requirements. All components are food-safe, easy to clean and easy to inspect, minimizing risk of bacteria growth.

In addition, these units have a 3-year warranty as standard, and are kept in stock to ensure quick delivery.





1.5

BAKERY

BUTCHER

1

HOSPITALITY

CONVENIENCE

SMALL BUSINESS

SLIM COMPACT

Güntner

3

A great choice for saving space, the Slim COMPACT Air Cooler is the ideal solution for small and low cold stores - the flat design of the unit occupying very little space allowing optimal use of the cold room, such as in hospitality or convenience stores.

KEY FEATURES

HIGH QUALITY CASING

The unit is constructed from high quality aluminium casing with a powder coating, which is anti-corrosive.

EASY CLEANING & INSPECTION

The entire drip tray unit and inner tray can be hinged down, ensuring easy access for cleaning and inspection.

COIL DEFENDER

For slightly more corrosive atmospheres, there's a Coil Defender option available. This anti-corrosion coating protects the heat exchanger with its standard material combination of copper tubes and aluminium fins, ensuring a long life-time of the unit.

EFFICIENT FANS

Maintenance-free, durable fans. Available in AC and EC technology, ErP-compliant, in various sizes, optimal air and sound level properties.

FLUIDS

This unit works with all common refrigeration fluids.

HACCP CERTIFICATION

Certified by the German TÜV SÜD, models carrying this certification are perfectly suited for use in areas with stringent hygiene requirements.

3-YEAR WARRANTY

The Slim COMPACT Air Cooler comes with a 3-year warranty as standard, giving you more peace of mind.

TECHNICAL DETAILS


GASC SERIES				
Refrigerant	t _o	Air inlet	Fin spacing 4 mm	Fin spacing 7mm
CO ₂	-8 ℃ -25 ℃	0 °C -18 °C	0,8 - 14 kW	0,6 - 12 kW 0,6 - 9 kW
Fluid	-8 °C	0°C	0,8 - 16,5 kW	0,6 - 14 kW
A2L / HFC	-8 ℃ -25 ℃	0 °C -18 °C	0,8 - 13 kW	0,6 - 10 kW 0,6 - 9 kW

MATERIALS				
	Casing	Fin	Тгау	Tube
AIMg	\checkmark		\checkmark	
Aluminium		~		
Aluminium - epoxy resin coating		(~)		
Coil Defender		(~)		(~)
Copper				~

✓ Standard (✓) Optional

FANS				
	1 fan	2 fans	3 fans	4 fans
Ø 200 mm	\checkmark	\checkmark	\checkmark	
Ø 300 mm	\checkmark	\checkmark	\checkmark	~
<mark>Ø 315 mm</mark>	\checkmark	\checkmark	\checkmark	\checkmark

AIRFLOW DIRECTION



DEFROSTING TYPES

DEFRUSTING TYPES			
	Coil	Тгау	
Circulating Air	\checkmark	\checkmark	
Electric	(~)	(~)	

✓ Standard (✓) Optional

ACCESSORIES				
	GASC CX	GASC FP	GASC PX	GASC RX
Coil Defender	(~)	(~)	(~)	(~)
Condensate pump				
Epoxy coated fins	(~)	(~)	(~)	(~)
Streamer				
Thread / Flange connections		(~)		
Wiring to terminal box	~	\checkmark	~	\checkmark

 $\mathsf{CX} = \mathsf{CO}_2; \ \mathsf{FP} = \mathsf{Fluid}; \ \mathsf{PX} = \mathsf{A2L}; \ \mathsf{RX} = \mathsf{HFC}$

✓ Standard (✓) Optional

CONFIGURE YOUR SYSTEMS & SOLUTIONS AT DIGITAL SPEED



וויוי**myGPC** from Güntner

