



Application expertise



Wide & versatile ranges



Configurator & support

Alfa Laval is in the air.

Commercial air heat exchangers from Alfa Laval



Model	Nominal capacities R404A Capacity SC 15 kW	AC fans 230/50/1						Connections	
		nr.	fan power W	sound pressure dB(A)	air flow m <sup>3</sup> /h	coil surface m <sup>2</sup>	Int. volume dm <sup>3</sup>	in mm	out mm
Noise level L									
AGL351 A	5.6	1	65	27	1663	12.2	1.5	16	16
AGL351 B	6.7	1	65	27	1539	18.3	2.2	16	16
AGL351 C	7.1	1	65	27	1434	24.4	2.9	16	16
AGL352 A	11.5	2	130	30	3326	24.4	2.6	16	16
AGL352 B	13.2	2	130	30	3078	36.6	3.9	16	16
AGL352 C	14.3	2	130	30	2868	48.8	5.1	16	16
AGL353 A	17.1	3	195	32	4989	36.6	3.7	16	16
AGL353 B	20.3	3	195	32	4618	54.9	5.6	18	18
AGL353 C	21.6	3	195	32	4302	73.2	7.5	22	22
AGL501 A	15.1	1	220	37	4671	29.3	3.3	16	16
AGL501 B	18.4	1	220	37	4402	43.9	4.9	16	16
AGL501 C	19.6	1	220	37	4165	58.6	6.5	18	18
AGL502 A	30.3	2	440	40	9341	58.6	6.2	22	22
AGL502 B	37.0	2	440	40	8804	87.8	9.3	28	28
AGL502 C	39.3	2	440	40	8330	117.1	12.2	28	28
AGL503 A	46.3	3	660	42	14010	87.8	9.1	28	28
AGL503 B	55.6	3	660	42	13210	131.8	13.9	35	35
AGL503 C	60.3	3	660	42	12490	175.7	18.1	35	35
AGL504 A	60.6	4	880	43	18680	117.1	12.3	35	35
AGL504 B	72.6	4	880	43	17610	175.7	17.9	35	35
AGL504 C	80.8	4	880	43	16660	234.2	23.4	35	35
AGL631 A	25.4	1	600	45	8746	40.7	4.6	18	18
AGL631 B	31.3	1	600	45	8197	61.0	6.9	22	22
AGL631 C	34.5	1	600	45	7726	81.3	9.0	22	22
AGL632 A	51.1	2	1200	48	17490	81.3	8.8	28	28
AGL632 B	62.5	2	1200	48	16390	122.0	13.5	35	35
AGL632 C	68.6	2	1200	48	15450	162.7	17.4	35	35
AGL633 A	75.6	3	1800	50	26240	122.0	13.2	35	35
AGL633 B	95.1	3	1800	50	24590	183.0	19	35	35
AGL633 C	104.9	3	1800	50	23180	244.0	25.6	42	42
AGL634 A	103.3	4	2400	51	34980	162.7	16.9	35	35
AGL634 B	125.2	4	2400	51	32790	244.0	25.3	42	42
AGL634 C	137.3	4	2400	51	30900	325.3	32.9	42	42
AGL635 A	129.3	5	3000	52	43730	203.3	21.4	42	42
AGL635 B	158.4	5	3000	52	40980	305.0	32.4	54	54
AGL635 C	173.7	5	3000	52	38630	406.6	41.9	54	54
AGL636 A	155.2	6	3600	52	52480	244.0	26.7	54	54
AGL636 B	190.9	6	3600	52	49180	366.0	38.0	54	54
AGL636 C	210.3	6	3600	52	46360	488.0	49.3	54	54