

Brazed heat exchangers SWEP 810TH are made of high-strength steelAISJ 316, designed to operate in refrigerationsystems with a maximum pressure of 45 bar,

Connecting pipes of standard sizes are presented in the table. It is possible to order with pipe. Saccording to customer drawings.

Additional accessories such as insulation and mounting frames are available on request.

The presented models of the BlOTH serieshave a capacity from 1.7 to 8.1 kW, adapted to work with modern refrigerants.

C.ontactingus via the feedback foml guarantees that issues will be resolved at a professional level.

## 810TH Series and evaporators/condensers

Model	Number of plates, (pcs)	Performance ( <b>kW</b> )	Connecting pipes		Oimensions	Weight	
			Water	Refrigerant	(mm)	(kg)	
BloTHxlo/lP-SC-M	10	1.7	1"	11/8"	289x119x33	2.4	Order
BloTHxl4/lP-SC-M	14	2.4	1"	11/8"	289x119x42	2.7	Order
BloTHx20/lP-SC-M	20	3.8	1"	11/8"	289x119x56	3.1	Order
BloTHx24/lP-SC-M	24	4.8	1"	11/8"	289x119x65	3.9	Order
BloTHx26/lP-SC-M	26	6.1	1"	11/8"	289x119x76	4.1	Order
BlOTHx30/lp-SC-M	thirty	8.1	1"	11/8"	289x119x80	4.7	Order

## Bloth series-capacitors

Model	Number of plates, (pcs)	Performance (kW)	Connecting pipes		Oimensions	Weight	
			Water	Refrigerant	(mm)	(kg)	
810THx40/1P-SC-M	40	8.1	1"	11/8"	289x119x35	5.2	Order
810THx50/lP-SC-M	50	11.0	1"	1 1/8"	289x119x44	6.1	Order
810THx60/1P-SC-M	60	12.3	1"	11/8"	289x119x59	7.5	Order
810THx70/lP-SC-M	70	14.S	1"	1 1/8"	289x119x72	9.2	Order