

YCWM/YCRM POLARIS

WATER COOLED AND
REMOTE AIR COOLED CHILLERS

INSTALLATION, COMMISSIONING,
OPERATION AND MAINTENANCE



REFRIGERANT TYPE: R22, R407C

 **YORK**[®]
INTERNATIONAL

CE

Effective from 04/99

GB

Table of Contents

<p>1 SUPPLIER INFORMATION</p> <p>1.1 Introduction 1.1</p> <p>1.2 Warranty 1.1</p> <p>1.3 Safety 1.1</p> <p>1.4 Emergency Stops/Shutdown 1.2</p> <p>1.5 About this Manual 1.2</p> <p>1.6 Safety Labels 1.3</p> <p>1.7 Material Safety Data 1.4</p> <p>2 PRODUCT DESCRIPTION</p> <p>2.1 Introduction 2.1</p> <p>2.2 General Specification 2.2</p> <p>2.3 Compressors 2.2</p> <p>2.4 Refrigerant Circuits 2.2</p> <p>2.5 Evaporators and Condensers (Models 60 to 150) 2.2</p> <p>2.6 Evaporator (Models 170 to 280) 2.2</p> <p>2.7 Condensers (Models 170 to 280) 2.2</p> <p>2.8 Power and Controls 2.3</p> <p>2.9 Theory of Operation 2.3</p> <p>2.10 Nomenclature 2.4</p> <p>3 TRANSPORTATION, HANDLING AND STORAGE</p> <p>3.1 Inspection 3.1</p> <p>3.2 Handling 3.1</p> <p>3.3 Anchorage 3.2</p> <p>3.4 Storage 3.2</p>	<p>4 INSTALLATION</p> <p>4.1 Location 4.1</p> <p>4.2 Evaporator External Water System 4.1</p> <p>4.3 Condenser External Water System 4.2</p> <p>4.4 Water Connections 4.3</p> <p>4.5 Refrigerant Connections 4.3</p> <p>4.6 Electrical Supplies 4.4</p> <p>4.7 Electrical Connections 4.4</p> <p>5 COMMISSIONING</p> <p>5.1 Preliminary Checks 5.1</p> <p>5.2 Refrigerant Charging YCRM Units 5.1</p> <p>5.3 Starting 5.1</p> <p>5.3 Performance Check 5.2</p> <p>5.5 Customer Handover 5.2</p> <p>6 OPERATION</p> <p>6.1 Control Panel 6.2</p> <p>6.2 Unit Starting 6.2</p> <p>6.3 Water Temperature Display 6.2</p> <p>6.4 Alarm Display and Reset 6.3</p> <p>6.5 Unit Shutdown 6.3</p>
--	--

7 MAINTENANCE

7.1	General Requirements	7.1
7.2	Daily Maintenance	7.1
7.3	Refrigerant Charge	7.2
7.4	Compressors	7.2
7.5	Filter Drier	7.2
7.6	Sight Glass	7.2
7.7	Thermostatic Expansion Valve	7.3
7.8	Evaporator(s)	7.3
7.9	Condensers	7.3

8 TROUBLE SHOOTING**9 TECHNICAL DATA**

9.1	Pressure Drop Graphs	9.1
9.2	Safety Switch Settings	9.4
9.3	Operational Limits	9.4
9.4	Physical Data	9.5
9.5	Unit Electrical Data	9.6
9.6	Compressor Electrical Data	9.6
9.7	Sound Power Levels	9.7
9.8	Space Requirements	9.7
9.9	Dimensions	9.8
9.10	Process and Instrumentation Diagrams	9.11

10 SPARE PARTS

10.1	Recommended Spares	10.1
10.2	Recommended Compressor Oils	10.1
10.3	Associated Diagrams	10.1

11 DE-COMMISSIONING, DISMANTLING AND DISPOSAL

11.1	General	11.1
------	---------	------

1 SUPPLIER INFORMATION

1.1 Introduction

York YCWM/YCRM Series chillers are manufactured to the most stringent design and construction standards to ensure high performance, reliability and adaptability to all types of air conditioning installations. The unit is intended for cooling water or glycol and is not suitable for purposes other than those specified in this manual.

If the unit is used improperly, or for different purposes without the prior agreement of York International or their agents, then such use would be outside the scope and may be unsafe.

This manual contains all the information required for correct installation and commissioning of the unit, together with operation and maintenance instructions. The manual should be read thoroughly before attempting to operate or service the unit.

With the exception of the operations detailed in this manual, all installation, commissioning and maintenance tasks must be performed by suitably trained and qualified personnel from an Authorised York Service Centre.

The manufacturer is not liable for injury or damage resulting from incorrect installation/commissioning or operation, insufficient maintenance and/or failure to follow the procedures and instructions contained in this manual.

1.2 Warranty

The unit is supplied finished, tested and ready to work. The unit warranty will be void if any modification to the unit is carried out without written agreement of York International.

For warranty purposes, the following conditions must be satisfied:

- The initial start of the unit must be carried out by trained personnel from an Authorised York Service Centre.
- Maintenance must be carried out by properly trained personnel.
- Only genuine York spare parts must be used.
- All the scheduled maintenance operations detailed in this manual must be performed at the specified times.

Failure to satisfy any of these conditions will automatically void the warranty.

1.3 Safety

The installation of the unit must be carried out according to the Machinery Safety Directive (CEE 89/392), (as modified by Directive CEE 91/368, 93/44 and 93/68) to the Low Voltage Directive CEE 73/23, to the Electromagnetic Interference Directive CEE 89/336 and according to normal rules for technical matters prescribed by the applicable country regulations. Do not operate the unit before having observed all the above.



The unit must be earthed and no installation or maintenance work should be attempted on the electrical equipment without first switching off and isolating the main power supply and any control supplies.

Failure to observance of the above safety measures may result in fire or electrocution should a short-circuit occur.



The unit contains refrigerant vapour and liquid under pressure within the heat exchangers, compressors and pipework. Release of refrigerant can be a danger and cause injury.



It is the responsibility of the user to ensure that the unit is suitable for the conditions of use and that installation and regular maintenance is carried out by personnel with the appropriate skills and in accordance with this manual.



Support of the unit must be provided as indicated in this manual, failure to provide proper support may put personnel at risk of injury.



The unit is not designed to withstand loads or stresses from adjacent equipment, pipework and structures. Any such extraneous loads or stress may cause failure or collapse which can be a danger and cause injury. In such cases the warranty will be void.



Do not discard or burn the packaging in the environment.

1.5 About this Manual

For safety reasons, the instructions contained in this manual must be followed categorically; furthermore, damage caused by misuse is not covered by the warranty.

This manual uses the following conventions:



Warning messages alert you to a specific procedure or practice which, if not followed correctly, could cause serious personal injury.



Caution messages appear before procedures which, if not observed, could result in damage to the unit.



Notes contain particularly important comments which are set off from the text.

The contents of this manual, and of any other document supplied with the unit, are the property of YORK which reserves all rights. They may not be reproduced, in whole or in part, without the written authorisation of YORK.

1.4 Emergency Stops/Shutdown

Models 60 to 150

The ganged master switch adjacent to the control panel will shutdown the unit when it is set to the 0 position.

Models 170 to 280

The isolator switch on the electrical panel will shutdown the unit when the lever is pulled downwards.

1.6 Safety Labels

The following labels are fitted to each unit.

Refrigerant Identification Label



Unit Identification Label

York
CE

MODELLO _____
MODEL

MATRICOLA _____
SERIAL NUMBER

CARICA REFR. _____
REFRIGERANT CHARGE

DATI ELETTRICI _____
ELECTRICAL DATA

ALIM. POTENZA MAIN SUPPLY	400	3	50
------------------------------	-----	---	----

CORRENTE DI SPUNTO _____ A
LRA

CORRENTE A PIENO CARICO _____ A
FLA


POTENZA ASSORBITA _____ Kw
POWER INPUT

PRESS. ESERC. ACQUA _____ bar
WATER OPERATION PRESSURE

MASSA _____ Kg
WEIGHT

MADE IN ITALY

Electrical Warning Label



Crankcase Heater Warning Label

ATTENZIONE
INSERIRE LE RESISTENZE DI RISCALDAMENTO OLIO ALMENO 12 ORE PRIMA DI OGNI AVVIAMENTO.

PRIMA DELLA MESSA IN TENSIONE ASSICURARSI CHE LE VITI DEI CIRCUITI ELETTRICI SIANO SERRATE COMPLETAMENTE.

WARNING
ENERGIZE THE CRANKCASE HEATER FOR AT LEAST 12 HOURS BEFORE EACH STARTING.

BEFORE TIGHTENING-UP, TO TIGHTEN ALL TERMINAL SCREWS ESPECIALLY THOSE IN MAIN CIRCUIT.

88100215/B

Test Certificate

CERTIFICATO DI COLLAUDO PRODUZIONE YORK
YORK PRODUCTION TEST CERTIFICATE
UNITA' ARIA-ARIA/ARIA-ACQUA - SEMICENTRALI - CHILLER AIR/AIR AIR/WATER

NO. UNITA' COLLAUDATA _____
TEST NUMBER _____
DATA COLLAUDO _____
DATE OF TEST _____
MATERIALE COLLAUDATO _____
MATERIAL TESTED _____

PROGR. COLL. CHECK	DESCRIZIONE DEI TEST DESCRIPTION OF QUALITY CHECK	TIMERO OPERAT. INSP. CODE
01	VERIFICA ASSEMBLAGGIO VERIFY ASSEMBLY COMPLETE	
02	VERIFICA VISIVA CABLAGGIO COLLEG. ELETTRICI E CONNESSIONI VERIFY WIRING CONNECTIONS	
03	VUOTO E CARICA REF. VACUUM AND CHARGE TEST	
04	VERIFICA CON CERCAFUGHE TENUTA CIRCUITO FRIGORIFERO REFRIGERANT LEAK TEST	
05	PROVE FUNZIONALI CON RILIEVI TEMPERATURE/PRESSIONI-FUMORE FUNCTION AND RUN TEST NOISE TEST	
06	VERIFICA INTERVENTI SICUREZZE PRESSIONE E TEMPERATURA CHECK OPERATION AND SAFETY DEVICES	
07	VERIFICA TENUTA CIRCUITO IDR. E FUNZIONAMENTO POMPA (SU PACCHETTO) HYDRAULIC CIRCUIT TEST (PUMP CHECK ONLY FOR PACK UNIT)	
08	VERIFICA MONTAGGIO ACCESSORI (SE PREVISTI) E DOCUMENTAZIONE CHECK ACCESSORIES/DOCUMENTATION	
09	CONTROLLO ESTETICO FINALE E PULIZIA INTERNA VISUAL CHECK FOR DIRT AND DAMAGE	

1.7 Material Safety Data

Refrigerant Data:		
Safety Data	R22, R407C	
Toxicity	Low.	
In contact with skin	Liquid splashes or spray may cause freeze burns. Unlikely to be hazardous by skin absorption. R22 may be slightly irritant and liquid has a degreasing effect. Thaw affected areas with water. Remove contaminated clothing carefully - may adhere to skin in case of freeze burns. Was affected areas with plenty of warm water. If symptoms occur (irritation or blistering) obtain medical attention.	
In contact with eyes	Vapour has no effect. Liquid splashes or spray may cause freeze burns. Immediately irrigate with eyewash solution or clean water for at least 10 minutes. Obtain immediate medical attention.	
Ingested	Highly unlikely to occur - but should this occur freeze burn will occur. Do not induce vomiting. Provided patient is conscious, wash mouth with water and give about 250 ml (0.5 pint) to drink. Obtain immediate medical attention.	
Inhalation	R22: High levels of vapour concentration initially produce stimulation and then depression of the central nervous system causing headaches and giddiness and may lead to unconsciousness. Can prove suddenly fatal if the exposure has been severe.	R407C: High atmospheric concentrations may lead anaesthetic effect, including loss of consciousness. Very high exposures may cause an abnormal heart rhythm and prove suddenly fatal.
	At higher concentration there is a danger from asphyxiation due to reduced oxygen content of atmosphere. Remove patient to fresh air, keep warm and at rest. Administer oxygen if necessary. Apply artificial respiration if breathing has ceased or shows signs of failing. In event of cardiac arrest apply external cardiac massage. Obtain immediate medical attention.	
Further Medical Advice	Symptomatic and supportive therapy is indicated. Cardiac sensitisation has been described which may, in the presence of circulating catecholamines such as adrenalin, give rise to cardiac arrhythmias and subsequent arrest following exposure to high concentrations.	
Long term exposure	R22: A lifetime inhalation study in rats and mice give a small excess in salivary gland tumours in male rats only at 50,000 ppm. 10,000 ppm showed no effect. This information suggests that R22 does not represent a carcinogenic hazard to humans.	R407C: A lifetime inhalation study in rats has shown that exposure to 50,000 ppm resulted in benign tumours of the testis. This is not considered to be of relevance to humans exposed to concentrations at or below the occupational exposure limit.
Occupational exposure limits	R22: Recommended limit : 1000 ppm v/v - 8 hr TWA 1250 ppm v/v - 12 hr TWA.	R407C: Recommended limit: 1000 ppm v/v - 8 hr TWA.
Stability	R22: Unstable.	R407C: Not specified.
Conditions to avoid	Use in presence of naked flames, red hot surfaces and high moisture levels.	

Hazardous reactions	May react violently with sodium, potassium, barium and other alkali and alkaline earth metals. Incompatible materials : Magnesium and alloys containing more than 2% magnesium.	
Hazardous decomposition products	R22: Halogen acids formed by thermal decomposition.	R407C: Halogen acids by thermal decomposition and hydrolysis.
General precautions	Avoid inhalation of high concentrations of vapours. Atmospheric concentrations should be minimised and kept as low as reasonably practicable below the Occupational exposure limit. The vapour is heavier than air and collects at low level and in confined areas. Ventilate by extraction at lowest levels.	
Respiratory protection	Where doubt exists on atmospheric concentration, HSE approved breathing apparatus should be worn. This should be self contained or of the long breather type.	
Storage	Keep containers dry and in a cool place away from fire risk, direct sunlight, and all sources of heat such as radiators. Keep at temperatures not exceeding 45 °C.	
Protective clothing	Wear overalls, impervious gloves and goggles/face protection.	
Spill / Leak procedure	Ensure suitable personal protective clothing and respiratory protection is worn. Provided it is safe to do so, isolate the source of the leak. Allow small spillages to evaporate provided there is suitable ventilation. Large spillages : Ventilate area. Contain spillages with sand, earth or any suitable absorbent material. Prevent liquid from entering drains, sewers, basements and work pits since vapour may create a suffocating atmosphere.	
Disposal	Best to recover and recycle. If this is not possible, destruction is to be in an approved facility which is equipped to absorb and neutralise acids and other toxic processing products.	
Fire extinguishing data	R22: Non-flammable	R407C: Non-flammable at atmospheric conditions.
Containers	Fire exposed containers should be kept cool with water sprays. Containers may burst if overheated.	
Fire fighting protective equipment	Self contained breathing apparatus and protective clothing must be worn in fire conditions.	

REFRIGERANT OIL DATA	
Safety Data	Oil
Classification	Non-hazardous
In contact with skin	Minimally irritating. No first aid necessary. Exercise reasonable personal cleanliness including cleansing exposed skin areas several times daily with soap and water. Launder soiled work clothes at least weekly.
In contact with eyes	As with most foreign materials flush with plenty of eyewash solution or clean water.
Ingested	Obtain immediate medical attention.
Inhalation	Obtain immediate medical attention.
Conditions to avoid	Strong oxidisers, caustic or acid solutions, excessive heat. May degrade some paints and rubber materials.
Respiratory protection	Use in well ventilated areas
Protective clothing	Goggles or face shield should be worn. Gloves not necessary, but recommended, especially for prolonged exposure.
Spill / Leak procedure	Wear suitable protective equipment, especially goggles. Stop source of spill. Use absorbent materials to soak up fluid (i.e. sand, sawdust, and commercially available materials).
Disposal	Incinerate the oil and all associated wastes in an approved facility in accordance with local laws and regulations governing oily wastes.
Fire extinguishing data	Use dry chemical, carbon dioxide or foam spraying water on hot or burning liquid, may cause frothing or splashing.
	If a leak or spill has not ignited use water spray to disperse the vapours and to provided protection for persons attempting to stop the leak.
Containers	Fire exposed containers should be kept cool with water sprays.
Fire fighting protective equipment	Self contained breathing apparatus should be worn in fire conditions.

- 1 Compressor Compartment
- 2 Power Compartment
- 3 Control Compartment
- 4 Evaporator
- 5 Condenser
- 6 Cable Entry



2 PRODUCT DESCRIPTION

2.1 Introduction

The YCWM/YCRM range of twin refrigerant circuit water chillers are designed to be located inside the plant room of a building.

YCWM chillers require a cooling tower or dry cooler for heat rejection. YCRM chillers require a remote air cooled condenser for heat rejection.

The range includes the following models:

Models	Description
YCWM 60 to 280	Water Cooled chillers charged with refrigerant R22
YCWM-B 60 to 280	Water Cooled chillers charged with refrigerant R407C
YCRM 60 to 280	Remote Air Cooled chillers charged with refrigerant R22
YCRM-B 60 to 280	Remote Air Cooled chillers charged with refrigerant R407C

The following options are available:

Option	Description
Acoustic Kit (170-280)	A factory installed kit using acoustically lined compressor enclosure and compressor acoustic covers.
Remote Control Kit	A field mounted control panel to provide remote control.
Pressure Gauge Kit (170-280)	Factory fitted mechanical gauge kit for display of unit operating parameters.
Manifold Kit	Field mounted manifolds to provide a single point of connection for leaving and return water circuits.
Flow Switch Kit	Field mounted flow switches for evaporator water circuits.

2.2 General Specification

YCWM/YCRM models are completely assembled with all interconnecting refrigerant piping and wiring ready for field installation. After assembly a full run test is performed, with water flowing through the evaporators, to verify that each refrigerant circuit operates correctly.

YCWM units are pressure tested, evacuated and fully charged with refrigerant and include an initial oil charge.

YCRM units are pressure tested, evacuated and include a nitrogen holding charge and initial oil charge.

The unit base and frame is of heavy gauge galvanised steel fastened with stainless steel screws and bolts. All panels are easily removed for access to components. Galvanised steel parts are painted with baked-on enamel coloured blue.

2.3 Compressors

The hermetic compressors have internal motor protection and an internal overflow valve from discharge to suction. Starting is direct on line. The compressors are mounted on rubber anti-vibration pads and housed in a separate acoustically lined enclosure.

Compressor lubrication is force-fed by a reversible oil pump to all crankshaft and bearing surfaces through a fine mesh stainless steel oil strainer.

The compressor motors are refrigerant gas cooled, with integral thermistor protection against overloads. The overload protection is automatically reset after approximately 8 seconds. The motor terminal boxes are to IP-54 weather protection.

The compressors are switched On and Off by the unit microprocessor to provide capacity control,

2.4 Refrigerant Circuits

Two complete refrigerant circuits are supplied on each unit. All piping is ACR copper, with brazed joints. Refrigerant circuits include: a service valve for refrigerant charging, suction discharge and liquid line isolating valves, a sight glass with moisture indicator and thermostatic expansion valve. High and low pressure switches and a filter/drier are also included.

2.5 Evaporators and Condensers (Models 60 to 150)

Each of the two evaporators and condensers is a stainless steel plate type heat exchanger thermally insulated with flexible closed cell material. Design working pressure is 10 bar g on the water side and 30 bar g on the refrigerant side. An electric heater mat and differential pressure switch is provided.

Each exchanger is provided with flow and return water connections. Water connection is via 1 inch gas threaded connections on models 60 and 75 and 1½ inch gas threaded connections on models 90 to 150.

2.6 Evaporator (Models 170 to 280)

The single dual-circuit steel shell and copper tube evaporator is a direct-expansion type. It has refrigerant in the tubes, which are formed in a hair-pin configuration, and chilled liquid flowing through the baffled shell. The evaporator is covered with flexible, closed-cell, foam insulation.

Water connection to the evaporator is via victualic type connections. The evaporator has a heating element controlled by a thermostat. Water vent and drain connections are included on the evaporator.

The evaporator design working pressure on the water side is 10 barg and 30 barg on the refrigerant side.

2.7 Condensers (Models 170 to 280)

The condensers are shell and tube type with a built-in sub-cooler and removeable water heads. The design working pressure on the water side is 10 barg and 30 barg on the refrigerant side.

2.8 Power and Controls

All controls and motor starting equipment necessary for full unit operation are factory wired and tested. The power and control components are separated within the panel, which is designed to IP-53 weather protection.

Power Compartment

The power compartment contains compressor contactors, fuses and supply protection.

Control Compartment


The control compartment contains an electronic circuit board and a soft touch key control panel with display of operating functions, alarms and stops.

2.9 Theory of Operation

YCWM Cooling Mode

Low pressure liquid refrigerant enters the cooler (Evaporator) and is evaporated and superheated by the heat energy absorbed from the chilled water passing through the cooler shell. Low pressure vapour enters the compressor where pressure and superheat are increased. Heat is rejected by the water cooled condenser. The fully condensed and subcooled liquid refrigerant then enters the expansion valve where pressure reduction and further cooling takes place before returning to the cooler.


YCWM Models 60 to 150




YCRM Cooling Mode

The operation of the YCRM is identical to the YCWM except for the water cooled condenser which is replaced by a remote air cooled condenser.

YCWM Models 170 to 280



2.10 Nomenclature



3 TRANSPORTATION, HANDLING AND STORAGE

YCWM/YCRM series chillers are supplied fully assembled.

YCWM units are pre-charged with refrigerant and oil in the correct quantity required for operation.

YCRM units include a nitrogen holding charge and are pre-charged with oil in the correct quantity required for operation.



The refrigerant circuit on YCRM units must be charged before the unit is operated.

3.1 Inspection

Immediately upon receiving the unit, it should be inspected for possible damage which may have occurred during transit as goods are shipped ex-works at purchaser's risk. In addition, ensure that all ordered components have been received.

If any damage is evident, it should be noted on the carrier's freight bill and a claim entered in accordance with the advice note instructions. If the damage is other than superficial, immediately advise your local York representative.

York accepts no responsibility for shipping damage, even in cases where the factory has arranged for shipping.


3.2 Handling

Models 60 to 150 are designed to be lifted using a fork lift truck.

Models 170 to 280 are designed to be lifted using lifting lugs and cables. A spreader bar or frame should be used with the cables, to avoid damaging the unit.

Before moving the unit ensure that the installation site is suitable to receive the unit and to support its weight and mechanical impact.

During handling the unit should not be inclined from the vertical.



Care should be taken to avoid damaging the paneling when lifting and moving the unit to the installation site. The sides of the unit should be protected with stiff cardboard or plywood.



Do not remove the protective packaging until the unit is ready for operation.

3.3 Anchorage

YCWM/YCRM series chillers are provided with 18 mm diameter holes in the base frame for retaining the unit if required.

3.4 Storage

If the unit is to be stored prior to installation, certain precautions should be taken to prevent damage, corrosion or deterioration:

- Ensure that all openings, such as water connections, are securely capped or sealed.
- Do not store where exposed to ambient air temperatures exceeding 45°C for R22 or 42°C for R407C units, preferably out of direct sunlight.
- Store the unit in a location where minimum activity is likely to take place to limit the risk of accidental damage.
- Do not steam clean the unit.
- Remove the keys necessary to gain access to the control panel and deposit them with a responsible person on site.

Periodic visual examination during storage is recommended.

4 INSTALLATION

4.1 Location



Before installing the unit, make sure that the building structure and/or mounting surface can support the unit weight. Overall weights are detailed in Section 9.

The unit has been designed for floor mounting in protected indoor locations.

The installation site should ensure adequate clearances and drainage for maintenance, refer to Section 9 for details.

4.2 Evaporator External Water System



The external water hydraulic circuit must ensure constant water flow to the evaporator(s) under all operating or adjustment conditions.

The external water system should consist of the following:

- A circulation pump providing sufficient flow and hydraulic head.
- The primary system water content should be no less than 10 litres per kW of cooling capacity. If the total volume in primary system pipework and evaporator is insufficient, an insulated reservoir tank should be installed. This tank will ensure that repetitive starts of the compressors are avoided.
- A diaphragm-type expansion tank with safety valve outlet which must be visible.



The tank should be sized to accommodate a 2% increase in total fluid volume in the system (evaporator, lines, user circuits and reservoir tank where provided). The expansion tank does not need to be insulated, as water does not normally circulate therein.

- A flow switch to deactivate the unit when water is not circulating.




The flow switch must be connected in series with other external interlocks. The flow switch should be installed on the pump delivery, upstream of the unit.

A Normally Open differential pressure switch may be installed instead of the flow switch. The pressure switch senses water pressure drop across the evaporator.

In addition:

- Install a filter/strainer on the inlet side of the evaporator(s).
- Install shutoff valves on the evaporator(s) inlet and outlet water lines.
- Install a valved by-pass around the evaporator(s).
- Install air vent valves at the highest points of the lines.
- Provide suitable drainage points (with plugs, cocks etc.) at the lowest points of the lines.
- Insulate the pipework to prevent heat loss.



Key

- | | | | |
|----|---------------|----|-------------|
| I | Pressure | R | Drain tap |
| T | Temperature | F | Strainer |
| S | Gate valves | F1 | Flow switch |
| S1 | By-pass valve | | |



Before filling the system, ensure that it is free from foreign matter, sand, stones, rust flakes, solder, slag or other materials which could damage the evaporators.

It is advisable to by-pass the unit when flushing out the lines.



Water used to fill the circuit may have to be treated to ensure that the pH value is correct.

Standard evaporators provided on YCWM/YCRM units are designed to chill mixtures of water and ethylene glycol with a corrosion-inhibiting additive down to $-10\text{ }^{\circ}\text{C}$ (R22) and $-5\text{ }^{\circ}\text{C}$ (R407C).

The amount of ethylene glycol to be added is as follows.

Amounts are shown as a percentage by weight of the circuit design water content:

operation from $+5$ to $0\text{ }^{\circ}\text{C}$: 20%

operation from 0 to $-5\text{ }^{\circ}\text{C}$: 30%

operation from -5 to $-10\text{ }^{\circ}\text{C}$: 40%

4.3 Condenser External Water System



The external water hydraulic circuit must ensure constant water flow to the condensers under all operating or adjustment conditions.

For cooling of YCWM units, condensers are usually piped in conjunction with a cooling tower, although in some cases they can be cooled by well water.

With water cooled units it is necessary to control coolant flow and/or temperature into the condenser to maintain refrigerant pressure constant to ensure satisfactory operation.

For a cooling tower system the simplest forms of control are to use fan cycling, fan speed control, or air damper control, with the tower having a thermostat in its sump.

If these methods are not available, or a cooling tower is not the source of cooling water, then a three way valve recirculation system can be used.


The external water system should consist of the following:

- A circulation pump providing sufficient flow and hydraulic head.
- The primary system water content should be no less than 5 litres per kW of cooling capacity.

The water used for the condenser external water system should have a hardness value within 10 to $15\text{ }^{\circ}\text{Fr}$.

In addition:

- Install a filter/strainer on the inlet side of the condenser(s).
- Install shutoff valves on the condenser(s) inlet and outlet water lines.
- Install a valved by-pass around the condenser(s).
- Install air vent valves at the highest points of the lines.
- Provide suitable drainage points (with plugs, cocks, etc.) at the lowest points of the lines.



Key

I	Pressure	R	Drain tap
T	Temperature	F	Strainer
S	Gate valves	F1	Flow switch
S1	By-pass valve		

4.4 Water Connections




The water inlet and outlet connections must be connected correctly as shown on the labels fitted next to the fittings.

Connect the external water supply lines to the water inlet and outlet fittings on the unit, refer to section 9 for diameters and locations.

YCWM 60-150 Heat Pump

The YCWM unit can operate as a water to water heat pump by reversing the cycle on the water circuits using three way valves. Pressostatic two way valves are available as an option for remote location in the condenser water pipework.



This type of operation is possible only if the condensers are supplied with well water or disposable water. The system cannot be used if a cooling tower is used.

The unit is supplied as standard in the cooling mode only. If necessary the change to heating mode is carried out by York Personnel during commissioning and first time start-up of the unit, when requested.

4.5 Refrigerant Connections

For cooling of YCRM units, condensers are usually of the remote air-cooled type either roof or ground level mounted. Refrigerant systems should be designed and installed by suitably qualified persons in compliance with relevant national codes and standards. The complete pipework system and condenser must have a Design Working Pressure of at least 30 barg.

When the unit has been located in its final position, the refrigerant system pipework can be connected. Pipework and fittings **MUST** be separately supported and not cause any loading on the unit. Flexible connections are recommended and will also minimise transmission of vibrations to the building.

Pipework Design

The following notes give guidance but should not be considered exhaustive.

P-traps and double risers may be required when the condenser is sighted above the unit. Horizontal runs of the liquid line should be inclined slightly towards the YCRM unit.

An in-line receiver should not be installed in the refrigerant system.

Where the condenser is above or level with the unit, the discharge line should rise to at least the top edge of the condenser at some point. This will prevent liquid draining back to the compressor during the off cycle.

Elbows, bends and valves should be minimised to reduce pressure drop and prevent loss of performance. The liquid line in particular should be designed for minimum pressure drop to avoid flashing in the liquid line which will cause loss of performance and fault conditions to occur. Particular care should be taken where the condenser is below or level with the unit.

Refrigerant Connections

Units are supplied with a nitrogen holding charge. This should be relieved carefully via the suction service connections and the liquid line service connections.

The pipework can be brazed directly onto the welding connections taking care to protect the unit from excess heat which may cause distortion.

System Testing

All newly installed pipework must be pressure / leak tested to national code requirements (normally 1.1 x Design Working Pressure) then fully evacuated before charging. Refer to the section 5 for correct charging methods.



Incorrectly or badly designed and/or installed pipework systems may invalidate unit warranty

4.6 Electrical Supplies



Ensure that the power supply is off before working on the electrical system.



The unit must be provided with an earth connection.



It is the installers responsibility to ensure that all external wiring complies with applicable safety regulations.

York is not responsible for injury or damage of any kind resulting from failure to observe these precautions.

The unit complies with CEI-IEC standards n.17/13 of 1980.

The electrical distribution system must be able to supply all the unit power and the disconnect switches and circuit breakers must be sized to handle the unit starting current, refer to Section 9.

Supply and isolating devices shall be designed so that the lines are fully independent. Magnetic thermal differential breakers are recommended, to prevent damage due to electrical phase loss.

Power supplies to the compressors are through contactors controlled by the control panel. Each motor is provided with an internal thermal overload cut-out and external fuses.

Supply cables should be routed through the cable entries on the unit and enter the electrical panel through the hole.

4.7 Electrical Connections

The installation of the unit on the final site must be carried out according to the Machinery Safety Directive (CEE 89/392), (as modified by Directive CEE 91/368, 93/44 and 93/68) to the Low Voltage Directive CEE 73/23, to the Electromagnetic Interference Directive CEE 89/336 and according to normal rules for technical matters prescribed by country regulations. Do not operate the unit before having observed all the above. Supply lines shall consist of insulated copper conductors sized for maximum current draw.

Terminal connections should be made in accordance with the connection diagram in this manual and the diagram supplied with the unit.



Before connecting the supply lines, check that the mains voltage is within the range shown in the Electrical Data in Section 9.


For the 3 -phase power supply, also check that the phase unbalance does not exceed 2%. The check is performed by measuring the difference between the voltage of each phase pair and the average mains voltage during operation. The maximum measured difference (unbalance) shall not exceed 2% of the average voltage.

If the unbalance is unacceptable, the electricity supply company must be asked to correct the fault.




Supplying the unit with a line whose unbalance exceeds the specified value will automatically void the warranty.

YCWM-B and YCWM Models 60 to 150 Electrical Connections



YCWM-B and YCWM Models 170 to 280 Electrical Connections



5 COMMISSIONING



The unit must be started by trained personnel from an Authorised York Service Centre. Failure to satisfy this requirement will void the warranty.



The operations performed by York service personnel are limited to unit starting, and do not include other work on system such as electrical connection, water connection, etc. All other preparatory work, including oil pre-heating (for at least 12 hours) must be performed by installer.

5.1 Preliminary Checks

The following operations must be performed before starting the unit and should be performed before York service personnel arrive.

- With master isolating switch off, check that the electrical terminal clamps are tight and that all contactors operate correctly.
- Check that the voltage and phase unbalance of the power supply is within limits, refer to Section 4.
- Connect (non-energised) contacts of the flow switch and the pump thermal overload cut-out or other devices (where provided) to terminals 1-2 and 3-4 respectively.
- Check that the evaporator and condenser external water circuit components (pumps, sensors, user equipment, filters, expansion tank and reservoir where provided) have been correctly installed as advised by manufacturer.
- Check that the external water circuits are full and that the fluid circulates freely with no signs of leakage or air bubbles. If ethylene glycol antifreeze is used, check that the percentage concentration is correct.
- Check that the pump direction of rotation is correct, and allow fluid to circulate for at least 24 hours (12 hours for each pump). Then clean the basket filters on the pump suction.

- Adjust the water system so that the flow rates are as specified.
- Check that the water quality is as specified.
- Check that the oil heaters, have been energised for at least 12 hours.

5.2 Refrigerant Charging YCRM Units

Units are supplied with a nitrogen holding charge. This should be relieved carefully via the suction service connections and the liquid line service connections.

The unit should be evacuated with a suitable vacuum pump/recovery unit as appropriate to below 100 microns.

Do not liquid charge with static water in any of the heat exchangers. Care must also be taken to liquid charge slowly to avoid excessive thermal stress at the charging point. Once the vacuum is broken, charge the unit with the full operating charge as given in the Physical Data section of this manual. Check the unit data plate and/or unit labels for the type of refrigerant to be used with the unit.

5.3 Starting

The starting sequence is as follows.

- Turn on the master isolating switch (12 hours before).
- Check that the compressor oil is sufficiently warm (minimum temperature at the oil pan exterior must be approximately 40°C) and that the auxiliary control circuit is energised.
- Check that all external equipment is in running order and that the associated control equipment is correctly calibrated.
- Start the liquid pump and check that the water flow rate is as required.
- Set the desired fluid inlet temperature on the control panel (refer to Section 6).
- Start the unit (refer to Section 6).

- After around 15 minutes of operation, check that no air bubbles are visible through the sight glass on the fluid line.



If air bubbles are visible, the unit has lost part of its charge through one or more leaks. The leaks must be eliminated refer to Section 7.

- Repeat the starting procedure after eliminating the leaks.
- Where the compressor is provided with a sight glass, check that the oil level is correct.

5.4 Performance Check

Check the following:

- Evaporator inlet water temperature.
- Evaporator outlet water temperature.
- Evaporator outlet water flow rate.
- Compressor current at startup and stable operating conditions.

Check the saturated evaporation and condensation temperatures during operation at high and low pressure by connecting gauges to the schrader valves on the high and low pressure refrigerant circuits.

High pressure side	Approximately 10 to 12°C above condenser water inlet temperature.
Low pressure side	Approximately 5 to 7°C below chilled water outlet temperature.

5.5 Customer Handover

- Familiarise the user with the machine operating instructions in section 6.

6 OPERATION

YCWM/YCRM series chillers are equipped with an electronic control and monitoring system as standard. The system provides control, monitoring and alarm functions.

The system consists of an electronic circuit board and a control panel with display and touch keys.

Control functions:

- Unit capacity control
- Compressor startup delay
- Anti-freezing protection

Alarm management and display

- High pressure alarm.

When the alarm is activated, the control system locks out the associated refrigerating circuit and opens the compressor control chain (fail-safe mode). The alarm is reset from the pressure switch and manually from the panel.

- Low pressure alarm.

When the alarm is activated, the control system locks out the associated refrigerating circuit. Alarm operation is delayed approximately 30 seconds after starting. Alarm is reset manually from the panel.


- Anti-freezing alarm.

This alarm is activated when water temperature at evaporator outlet drops below 3 °C. The control system locks out the associated refrigerating circuit. Alarm is reset manually from the panel.














- External interlock alarm.

When the alarm is activated, the control system locks out the unit. Reset is automatic.

Control Panel



6.1 Control Panel

Item	Function
	Displays operating and fault parameters.
	SET POINT + key (increases temperature SET POINT).
	SET POINT - key (reduces temperature SET POINT).
	SET POINT display key.
	Circuit 1 or 2 power key and LED (Select circuit 1 or 2).
	Circuit 1 or 2 compressor ON LED.
	Circuit 1 or 2 high pressure alarm LED. Indicates that high pressure switch for circuit 1 or 2 has been activated.
	Circuit 1 or 2 low pressure alarm LED. Indicates that low pressure switch for circuit 1 or 2 has been activated.
	Voltage indicator LED. Indicates that unit is connected to power supply.
	Circuit 1 or 2 anti-freezing alarm LED. Indicates that water temperature at evaporator outlet is below safe limit.
	External interlock alarm LED.
	Warm weather mode start key and LED. Starts the unit in the cooling mode. Led lights up to indicate operating in cooling mode.
	Cold weather mode start key and LED. Starts the unit in the heating mode. Led lights up to indicate operating in heating mode.


6.2 Unit Starting


To start the unit proceed as follows:

- Set the master switch to the on (I) position to energise the control panel.




Check that  LED (voltage indicator) goes on.

Check that there are no active alarm signals.



- Activate the two circuits for operation by pressing the  key for each circuit.

The unit is now in stand-by, the display will come on and the  LED's for the associated circuits will flash for approximately 15 seconds before coming on.


If necessary, set the water temperature as follows:

- Press the set point display key  to display the unit set point on the display.
- Change the unit set point using the  key to increase or the  key to decrease the temperature.


The unit set point is factory set to 12°C for warm weather operation and 45 °C for cold weather operation.


- Press the  key to start the unit in the cooling mode or the  key to start unit in the heating mode.

The  LED or the  LED will go on.

Compressor operation will be indicated by  LED's for each circuit.

6.3 Water Temperature Display

To display the evaporator inlet water temperature press the  key.

To display the evaporator outlet water temperature press the  key.



6.4 Alarm Display and Reset

Alarms are indicated by the associated panel LED's and by messages on the display. Details of the alarm codes are given below.

E01	SENSOR FAILURE INLET WATER TEMPERATURE SENSOR (EVAPORATOR)
E02	SENSOR FAILURE OUTLET WATER TEMPERATURE SENSOR (EVAPORATOR CIRCUIT 1)
E03	SENSOR FAILURE TEMPERATURE SENSOR (CONDENSER INLET)
E 04	SENSOR FAILURE OUTLET WATER TEMPERATURE SENSOR (EVAPORATOR CIRCUIT 2)
E 05	SENSOR FAILURE OUTLET WATER TEMPERATURE SENSOR (CONDENSER CIRCUIT 1)
E06	CIRCUIT1 ANTI FREEZING
E07	CIRCUIT 2 ANTI FREEZING
E08	SENSOR FAILURE OUTLET WATER TEMPERATURE SENSOR (CONDENSER CIRCUIT 2)
E09	HIGH PRESSURE CIRCUIT 1
E10	HIGH PRESSURE CIRCUIT 2
E 13	EXTERNAL INTERLOCK
E 14	LOW PRESSURE CIRCUIT 1
E 15	LOW PRESSURE CIRCUIT 2

6.5 Unit Shutdown

To shutdown the unit proceed as follows:

- Press the  to return the unit to stand-by.
- De-activate the two circuits by pressing the  key for each circuit.
- Turn master isolating switch to OFF position to de-energise the unit.

Page left intentionally blank

7 MAINTENANCE



Never release refrigerant to the atmosphere when emptying the refrigerating circuit. Suitable retrieval equipment must be used. If reclaimed refrigerant cannot be re-used. It must be returned to the manufacturer.



Never discard used compressor oil, as it contains refrigerant in solution. Return used oil to the oil manufacturer.

The Safety Section of this manual should be read carefully before attempting any maintenance operation on the unit.

Unless otherwise indicated, the maintenance operations described below can be performed by any properly trained maintenance technician.

7.1 General Requirements

The York YCWM/YCRM range has been designed to work continuously provided they are regularly maintained and operated within the limitations given in this manual. Each unit should be maintained in accordance with the schedule by the operator/customer, backed up by regular service and maintenance visits by an authorised York Service Centre.

It is the responsibility of the owner to provide for these regular maintenance requirements and/or enter into a maintenance agreement with a York Service Centre to protect the operation of the unit.

If damage or a system failure occurs due to improper maintenance during the warranty period, York shall not be liable for costs incurred to return the unit to satisfactory condition.

This maintenance section applies only to the basic YCWM/YCRM unit and may, on individual contracts, be supplemented by additional requirements to cover any modifications or ancillary equipment as applicable.

7.2 Daily Maintenance

The maintenance checks should be carried out in accordance with the maintenance schedule detailed below by a competent person. Please note, however, that YCWM/YCRM units are not generally user serviceable and no attempt should be made to rectify faults or problems found during daily checks. If in any doubt, contact your local York service agent.

Scheduled Maintenance

Operation	Daily	Weekly	Monthly	Start of Season	End of Season
Check evaporator entering / leaving liquid temperature	●				
Check evaporator pressure drop		●			
Check condenser pressure drop		●			
Check electrical power consumption		●			
Check suction pressure and temperature		●			
Check discharge pressure and temperature		●			
Check compressor oil level		●			
Check for gas bubbles in refrigerant		●			
Check low pressure switch				●	
Check high pressure switch				●	
Check evaporator insulation				●	
Check tightness of wiring terminal screws				●	
Clean outside surface of the unit with soapy water				●	
Check specific gravity of brine (Glycol) if applicable				●	●
Drain and clean the evaporators and condensers					●

7.3 Refrigerant Charge



Never introduce liquid refrigerant in the low pressure side of circuit. Extreme care must be taken to ensure that circuit is correctly charged.

An insufficient charge will lead to poor machine performance. In extreme cases, the low pressure switch will cut in and lock the circuit.

Excessive charge will raise the condensation pressure (which in extreme cases will cause the high pressure switch to cut in and lock the circuit) with a consequent increase in power consumption.



Under no circumstances must the compressor be used as a vacuum pump to purge circuit.

The refrigerant circuit must be charged whenever it is emptied for maintenance purposes (leak repair, compressor replacement, etc.). Charge quantities are given in Section 9.

Before charging, the circuit must be vacuum-purged and dried, reaching a minimum absolute pressure of 50 Pa.

The refrigerant gas must be introduced to eliminate vacuum and to charge the circuit to 90% of the total required gas in liquid form through the appropriate charging valve on liquid line at condenser outlet.

A refrigerant container should then be connected to the charging valve on suction line, the container should be held so that only gaseous phase refrigerant is released (R22).

The compressor should be started and gas allowed to flow from the refrigerant container until liquid in the sight glass runs clear and gas temperature at evaporator outlet has stabilised at around 5°C.

R407C units must be charged when the refrigerant is in the liquid phase. A service valve is provided for charging the unit at low pressure.

7.4 Compressor(s)

Compressors are supplied with the correct quantity of lubricant required for operation. Under normal operating conditions, lubricant will last the life of the unit. Fluid top-up is not required as long as refrigerating circuit operates correctly and no repair operations have been carried out.

Compressor replacement (as a result of failure), should be carried out by an Authorised York Service Centre.

7.5 Filter Drier

Refrigerating circuits are provided with filter/driers.

The filter/driers are non-inspectable strainer type. Filter/drier clogging will be indicated by bubbles in the sight glass, or by a difference in temperature upstream and downstream of filter/drier.

If bubbles persist after the changing cartridge, the machine has lost part of its refrigerant charge through one or more leaks which must be identified and repaired.

7.6 Sight Glass

The sight glass is used to observe refrigerant flow and moisture content. Bubbles in the flow indicate that the filter/drier is clogged, or that refrigerant charge is low.

A colour indicator is located inside the sight glass. Compare the colour of the indicator with the scale on the sight glass lock ring to determine the moisture content of refrigerant. If moisture content is too high, proceed as follows:

- Discharge the circuit without releasing refrigerant to the atmosphere. Vacuum-purge the circuit and replenish the charge.

7.7 Thermostatic Expansion Valve

YCWM/YCRM refrigerating circuits are provided with a thermostatic expansion valve with an external equaliser. Valves are calibrated at the factory for a 5°C temperature rise.

To check the temperature rise:

Read the suction pressure using a pressure gauge connected to the charging valve on suction side.

Using the pressure gauge temperature scale, determine the saturated suction temperature T_{sa} corresponding to this pressure.

Determine the effective suction temperature T_{se} using a contact thermometer applied to the evaporator gas outlet fitting.

Temperature rise S is given by:

$$S = T_{se} - T_{sa}$$

The temperature rise can be corrected using the adjuster screw on the thermostatic expansion valve. Turn the adjuster screw clockwise to increase the temperature rise and counterclockwise to reduce the temperature.

Turn the adjuster screw through a single revolution and operate the unit for five minutes. Then check the temperature rise again and correct as necessary.

If the thermostatic expansion valve does not react to temperature rise calibration, it is probably malfunctioning and must be replaced. Valve replacement must be performed by an authorised York Service Centre.

7.8 Evaporator(s)

Check the heat exchanger water side for cleanliness at regular intervals. This may be accomplished by checking water side pressure drop (refer to Section 9) or simply by checking the fluid temperatures at heat exchanger inlet and outlet and comparing them with evaporation temperatures.

For effective heat exchange, the water outlet temperature and the saturated evaporation temperature should differ by 5 to 7 °C. A larger difference indicates that the heat exchanger is operating inefficiently, and is thus soiled.

If soiled, the heat exchanger must be chemically cleaned by authorised York service personnel.

For other types of service (special maintenance, heat exchanger replacement, etc.), contact an authorised York Service Centre.

7.9 Condensers

Check the condenser water side for cleanliness at regular intervals. This may be accomplished by checking water side pressure drop (refer to Section 9).

Soiling of the condenser results in increased condensing pressure, which reduces efficiency and increases current consumption and may cause the high pressure switch to activate.

It is advisable to supply the condensers with anti-algae and anti-lime treated water.

If soiled, the heat exchanger must be chemically cleaned by authorised York service personnel.

For other types of service (special maintenance, heat exchanger replacement, etc.), contact an authorised York Service Centre.

Page left intentionally blank

8 TROUBLE SHOOTING

The following table details possible unit faults, their probable cause and suggested remedies. For any other problems not immediately recognisable and/or for technical assistance, call an Authorised York Service Centre.


Fault	Probable Cause	Remedy
Differential oil pressure switch cuts on, break circuit.	Defective differential pressure switch operation.	Check switch operation, replacing if necessary.
	Low oil level as a result of circuit leakage.	Determine location of leak and repair.
	Start up with cold oil.	Check oil heater operation.
	Compressor lube circuit malfunction.	Call an Authorised York Service Centre.
Unit operates continuously, but without cooling.	Low refrigerant charge.	Top up charge.
	Drier/filter clogged.	Replace drier/filter.
	Loss of efficiency in one or both circuits.	Check compressors and replace if necessary
Suction line freezes.	Temperature rise of thermostatic valve out of calibration.	Increase setting.
		Check charge
Excessive noise.	Vibrating pipework.	Secure pipework.
		Check pipework retainers.
	Thermostatic expansion valve hiss.	Top up charge.
		Check filter/drier, replacing if necessary.
	Noisy compressor.	Check condition of valves.
		Bearings have seized; replace compressor.
Check that compressor retaining nuts are tight.		
Low compressor oil level.	One or more gas or oil leaks in circuit.	Identify and eliminate all leaks.
	Mechanical damage to compressor.	Call an Authorised York Service Centre.
	Faulty crankcase oil heater.	Check electrical circuit and crankcase heater element operation, replacing any defective components.

Fault	Probable Cause	Remedy
One or both compressors not working.	Power circuit interrupted.	Check power circuit for earth leakage and shorts. Check fuses.
	High pressure switch activation.	Reset pressure switch from panel and re-start unit. Identify and eliminate causes of pressure switch activation.
	Control circuit fuse blown.	Check control circuit for earth leakage and shorts. Change fuses.
	Loose terminal clamps.	Check clamp tightness.
	Power circuit thermal overload cut-out activation.	Check operation of control and safety devices. Identify and eliminate cause of activation.
	Incorrect wiring.	Check control and safety device wiring.
	Line voltage too low.	Check line voltage. If problem due to system, eliminate it. If problem is due to distribution network, inform the electricity supply company.
	Compressor motor short-circuited.	Check motor winding continuity
	Compressor seizure.	Replace compressor.
Low pressure switch cuts in, braking circuit.	Gas leakage.	Identify and eliminate leakage.
	Insufficient charge.	Top up charge.
	Pressure switch failure.	Replace pressure switch.
High pressure switch cuts in, braking circuit.	High pressure switch malfunction.	Check switch operation, replacing if necessary.
	Delivery valve partially closed.	Open valve, replacing if necessary.
	Non-condensables in circuit.	Purge circuit.
	Condenser water circuit dirty.	Clean and descale if necessary.
Liquid line too hot.	Insufficient charge.	Identify and eliminate causes of charge loss and top up charge.
	Condenser water circuit dirty.	Clean and descale if necessary.
Liquid line freezes.	Liquid line valve partially closed.	Check that all valves are open.
	Receiver/drier clogged.	Replace cartridge.

9 TECHNICAL DATA


9.1 Pressure Drop Graphs

YCWM-B and YCRM-B Models 60 to 150 - Evaporators




Note: Total unit flow rate is shown.

YCWM and YCRM Models 60 to 150 - Evaporators




Note: Total unit flow rate is shown.

YCWM-B, YCRM-B, YCWM and YCRM Models 170 to 280 - Evaporator




Note: Total unit flow rate is shown.

YCWM-B and YCWM Models 60 to 150 - Condensers



Note: Total unit flow rate is shown.

YCWM-B and YCWM Models 170 to 280 - Condensers



Note: Total unit flow rate is shown.

9.2 Safety Switch Settings

YCWM/YCRM		60	75	90	120	150	170	200	240	280	
Low Pressure Switch	bar	0,5									
High Pressure Switch	bar	22				28					
TüV High Pressure Switch	bar	25									
Oil Pressure Switch	bar	0,8									
Anti Freezing Thermostat	°C	5									
Safety Valve	bar	24									
Evaporator Water Differential Pressure Switch		50% of Nominal Capacity									

9.3 Operational Limits

YCWM/YCRM				60		75		90		120		150		
				Min.	Max.	Min.	Max.	Min.	Max.	Min.	Max.	Min.	Max.	
Chilled Liquid	Evaporator	Water outlet	°C	5 to 15 (R22) 6 to 15 (R407C)										
	Water outlet	Brine outlet	°C	-10 to 15 (R22) -5 to 15 (R407C)										
	temperature	Temp. spread	°C	3 to 8										
	Flow rate (1)			m³/h	4,3	20,3	5,0	24,0	6,9	32,7	8,6	42,1	10,4	50,4
	Pressure drop (1)			kPa	7,8	149,5	10,4	205,6	9,6	191,6	5,9	125,6	6,7	130,6
			kPa	6,3	112,9	6,7	125,1	6,1	113,8	4,7	93,0	5,3	103,4	
Max. working pressure			bar	10										
Cooling Liquid (2)	Liquid outlet	Water outlet	°C	25 to 50 (R22) 30 to 50 (R407C)										
	temperature	Temp. spread	K	3 to 8										
	Flow rate (1)			m³/h	6,1	24,4	7,2	29,5	8,3	39,2	12,6	50,7	15,2	61,2
	Pressure drop (1)			kPa	15,2	212,2	15,7	230,7	13,8	271,4	18,2	265,0	17,7	258,2
Max. working pressure			bar	10										
Power supply voltage 400 V, 3 Ø, 50 Hz (nominal)			V	360 to 440										
Recommended system water volume (3)			l	730		860		1050		1550		1750		

(1) Total unit flow rate and pressure drop are given

(2) YCWM-B & YCWM only

(3) Table shows minimum water / brine volume of system

YCWM/YCRM				170		200		240		280		
				Min.	Max.	Min.	Max.	Min.	Max.	Min.	Max.	
Chilled Liquid	Evaporator	Water outlet	°C	5 to 15 (R22) 6 to 15 (R407C)								
	Water outlet	Brine outlet	°C	-10 to 15 (R22) -5 to 15 (R407C)								
	temperature	Temp. spread	°C	3,5 to 8								
	Flow rate (1)			m³/h	13,7	31,0	23,0	51,1	23,4	52,6	27,4	61,6
	Pressure drop (1)			kPa	8,1	39,4	10,1	46,9	10,8	51,3	12,4	60,4
Max. working pressure			bar	10								
Cooling Liquid (2)	Liquid outlet	Water outlet	°C	25 to 50 (R22) 30 to 50 (R407C)								
	temperature	Temp. spread	K	3 to 8								
	Flow rate (1)			m³/h	21,6	50,4	27,4	62,0	31,6	67,8	36,0	82,0
	Pressure drop (1)			kPa	15,0	77,7	16,9	80,2	17,7	74,6	18,6	89,6
Max. working pressure			bar	10								
Power supply voltage 400 V, 3 Ø, 50 Hz (nominal)			V	360 to 440								
Recommended system water volume (3)			l	960		1160		1280		1536		

(1) Total unit flow rate and pressure drop are given

(2) YCWM-B & YCWM only

(3) Table shows minimum water / brine volume of system

9.4 Physical Data

YCWM/YCRM			60	75	90	120	150
Refrigerant Circuits			2	2	2	2	2
Refrigerant charge per circuit	R 22	kg	2	2,2	3	4	4,5
	R407C	kg	2,3	2,6	4	4,2	4,7
Compressor Note: x=2 R22 x=7 R407C	Type		H(x)BG124	H(x)5G144	H(x)NG184	H(x)NG244	H(x)NG294
	Theoretical displacement	m ³ /h	39,8	44,2	58,2	76,4	88,3
	Number		2	2	2	2	2
	No. of cylinders		3	3	6	6	6
	Revs per minute	rpm	2900	2900	2900	2900	2900
	Oil charge per compressor	l	2,9	3,1	6,6	6,6	6,6
	No. of loading stages	%	100-50	100-50	100-50	100-50	100-50
Evaporator	Number		2	2	2	2	2
	Type (Direct Expansion) R407C		V25/60	V25/70	B45/40	V45/60	V45/70
	Type (Direct Expansion) R22		B25/50	V25/50	B45/30	B45/50	B45/60
	Water volume per evaporator	l	2,85	3,32	3,76	5,64	6,58
Water cooled	Number		2	2	2	2	2
	Type (R407C & R22)		B25/50	B25/60	B45/30	B45/40	B45/50
Condenser (1)	Water volume per condenser	l	2,37	2,85	2,82	3,76	4,7
YCWM Weight	Operating R407C (R22)	kg	440 (435)	450 (440)	587 (577)	600 (587)	621 (607)
	Shipping R407C (R22)	kg	430 (425)	440 (430)	577 (567)	590 (577)	611 (597)
YCRM Weight	Operating R407C (R22)	kg	412(407)	422 (412)	559 (549)	572(559)	593(579)
	Shipping R407C (R22)	kg	402 (397)	412 (402)	549 (539)	562(549)	583(569)
Dimensions	Length	mm	1210	1210	1210	1210	1210
	Width	mm	758	758	758	758	758
	Height	mm	1060	1060	1060	1060	1060

(1) YCWM-B & YCWM only

YCWM/YCRM			170	200	240	280
Refrigerant Circuits			2	2	2	2
Refrigerant charge per circuit	R 22	kg	9,1	9,5	10,0	13,8
	R407C	kg	8,5	8,6	9,9	11,5
Compressor Note: x=2 R22 x=7 R407C	Type		H(x)NG184	H(x)NG204	H(x)NG244	H(x)NG294
	Theoretical displacement	m ³ /h	58.25	66.35	76.4	88.3
	Number		4	4	4	4
	No. of cylinders		6	6	6	6
	Revs per minute	rpm	2900	2900	2900	2900
	Oil charge per compressor	l	7	7	7	7
	No. of loading stages	%	100-75	100-75	100-75	100-75
Evaporator (R407C & R22)	Number		1	1	1	1
	Type (Direct expansion)		EHD156R	EHD205R	EHD235R	EHD275R
	Water volume	l	41,8	62,7	58,1	53,2
Water cooled	Number		2	2	2	2
	Type (R407C & R22)		CPS120	CPS145	CPS160	CPS180
Condenser (1)	Water volume per condenser	l	6,1	7,2	8	9,4
YCWM Weight	Operating	kg	1117	1215	1251	1322
	Shipping	kg	1062	1136	1177	1250
YCRM Weight	Operating	kg	974	1061	1091	1140
	Shipping	kg	931	996	1033	1049
Dimensions	Length	mm	2200	2200	2200	2200
	Width	mm	800	800	800	800
	Height	mm	1600	1600	1600	1600

(1) YCWM-B & YCWM only

9.5 Unit Electrical Data

Model		YCWM/YCRM				
		60	75	90	120	150
Current Input (A)	Nom. Cond.	30	35	45	64	76
	Max. Cond.	34	43	52	73	88
Power Input (KW)	Nom. Cond.	16	19	23	33	41
	Max. Cond.	20	23	29	41	51

Nominal conditions at 7°C chilled water outlet temperature, 35°C condenser outlet temperature (YCWM)

Maximum conditions at 12°C chilled water outlet temperature, 50°C condenser outlet temperature (YCWM)

Nominal conditions at 7°C chilled water outlet temperature, 40°C condensing temperature (YCRM)

Maximum conditions at 12°C chilled water outlet temperature, 55°C condensing temperature (YCRM)

Model		YCWM/YCRM			
		170	200	240	280
Current Input (A)	Nom. Cond.	92	104	128	152
	Max. Cond.	108	124	152	184
	Max. start.	206	243	304	353
Power Input (KW)	Nom. Cond.	49	58	66	81
	Max. Cond.	63	75	85	105

Nominal conditions at 7°C chilled water outlet temperature, 35°C condenser outlet temperature (YCWM)

Maximum conditions at 12°C chilled water outlet temperature, 50°C condenser outlet temperature (YCWM)

Nominal conditions at 7°C chilled water outlet temperature, 40°C condensing temperature (YCRM)

Maximum conditions at 12°C chilled water outlet temperature, 55°C condensing temperature (YCRM)

9.6 Compressor Electrical Data

Model YCWM/ YCRM	System	Compressor	Voltage (V)	Power Input at Nom. Cond. per Comp. (kW)	Power Input at Max. Cond. per Comp. (kW)	Current at Nom Cond. per Comp. (A)	Max. Current per Comp. (A)	DOL Starting Current (A) LRA	Max. Fuse Size (A)
60	1+2	H7BG124	400	8	10	15	17	93	20
75	1+2	H75G144	400	9	12	18	22	110	25
90	1+2	H7NG184	400	12	14	23	26	125	25
120	1+2	H7NG244	400	16	20	32	37	190	40
150	1+2	H7NG294	400	20	25	38	44	215	50

Nominal conditions at 7°C chilled water outlet temperature, 35°C condenser outlet temperature (YCWM)

Maximum conditions at 12°C chilled water outlet temperature, 50°C condenser outlet temperature (YCWM)

Nominal conditions at 7°C chilled water outlet temperature, 40°C condensing temperature (YCRM)

Maximum conditions at 12°C chilled water outlet temperature, 55°C condensing temperature (YCRM)

Model YCWM YCRM	System	Compressor	Voltage (V)	Power Input at Nom. Cond. per Comp. (kW)	Power Input at Max. Cond. per Comp. (kW)	Current at Nom Cond. per Comp. (A)	Max. Current per Comp. (A)	DOL Starting Current (A) LRA	Max. Fuse Size (A)
170	1+2+3+4	H2NG184	400	12	15	23	27	125	120
200	1+2+3+4	H2NG204	400	14	18	26	31	150	160
240	1+2+3+4	H2NG244	400	17	21	32	38	190	200
280	1+2+3+4	H2NG294	400	21	27	38	46	215	250

Nominal conditions at 7°C chilled water outlet temperature, 35°C condenser outlet temperature (YCWM)

Maximum conditions at 12°C chilled water outlet temperature, 50°C condenser outlet temperature (YCWM)

Nominal conditions at 7°C chilled water outlet temperature, 40°C condensing temperature (YCRM)

Maximum conditions at 12°C chilled water outlet temperature, 55°C condensing temperature (YCRM)


9.7 Sound Power Levels

YCWM/ YCRM Model	Standard Units		Units with Acoustic Kit	
	R22	R407C	R22	R407C
	Sound Power (dB(A))	Sound Power (dB(A))	Sound Power (dB(A))	Sound Power (dB(A))
60	67	70	-	-
75	68	71	-	-
90	68	71	-	-
120	69	72	-	-
150	70	73	-	-
170	90	97	74	81
200	90	97	74	81
240	91	98	75	82
280	92	99	76	83

Tolerance ± 2 dB(A)

Acoustic Kit supplied as standard on Models 60 to 150





9.8 Space Requirements



Model YCWM/YCRM	Distance (mm)				
	A	B	C	D	E
60 to 150	600	600	600	600	1000
170 to 280	2200	800	1000	1000	1500

9.9 Dimensions

YCWM-B, YCRM-B, YCWM and YCRM Models 60 to 150




Note:
 EV = Evaporator
 CD = Condenser

YCWM															Evaporator	Condenser		
Model	A	B	C	D	E	F	G	H	I	J	K	L	M	N	O	Pipe Connections	Pipe Connections	
60	1060	1210	758	20	500	278	479	500	500	500	-	410	479	100	150	ISO-G 1"	ISO-G 1"	
75	1060	1210	758	20	500	278	479	500	500	500	-	410	479	100	150	ISO-G 1"	ISO-G 1"	
90	1060	1210	758	26	555	286	456	510	538	555	-	420	456	100	150	ISO-G 1 1/2"	ISO-G 1 1/2"	
120	1060	1210	758	26	555	286	456	510	538	555	-	420	456	100	150	ISO-G 1 1/2"	ISO-G 1 1/2"	
150	1060	1210	758	26	555	286	456	510	538	555	-	420	456	100	150	ISO-G 1 1/2"	ISO-G 1 1/2"	
YCRM															Evaporator	Refrigerant	Refrigerant	
Model	A	B	C	D	E	F	G	H	I	J	K	L	M	N	O	Pipe Connections	Inlet Connections	Outlet Connections
60	1060	1210	758	20	500	278	479	500	295	430	70	390	-	100	150	ISO-G 1"	5/8"	7/8"
75	1060	1210	758	20	500	278	479	500	295	430	70	390	-	100	150	ISO-G 1"	5/8"	7/8"
90	1060	1210	758	26	555	286	456	510	225	485	70	390	-	100	150	ISO-G 1 1/2"	7/8"	1 1/8"
120	1060	1210	758	26	555	286	456	510	225	485	70	390	-	100	150	ISO-G 1 1/2"	7/8"	1 1/8"
150	1060	1210	758	26	555	286	456	510	225	485	70	390	-	100	150	ISO-G 1 1/2"	7/8"	1 1/8"


Dimensions in mm unless stated

YCWM-B and YCWM Models 170 to 280




YCRM																			
Model	A	B	C	D	E	F	G	H	I	J	K	L	M	N	O	P	R	S	T
170	2200	1600	800	398	1500	618	368	1570	50	60	1237	147	157	500	114	760	3"	1 1/8"	7/8"
200	2200	1600	800	398	1500	618	368	1570	50	60	1237	147	157	500	114	760	4"	1 1/8"	7/8"
240	2200	1600	800	398	1500	618	368	1570	50	60	1237	147	157	500	114	760	4"	1 3/8"	7/8"
280	2200	1600	800	398	1500	618	368	1570	50	70	1237	147	157	500	114	760	4"	1 3/8"	7/8"

Dimensions in mm unless stated




YCRM-B and YCRM Models 170 to 280



YCRM																			
Model	A	B	C	D	E	F	G	H	I	J	K	L	M	N	O	P	R	S	T
170	2200	1600	800	398	1500	618	368	1570	50	60	1237	147	157	500	141	760	3"	1 1/8"	7/8"
200	2200	1600	800	398	1500	618	368	1570	50	60	1237	147	157	500	114	760	4"	1 1/8"	7/8"
240	2200	1600	800	398	1500	618	368	1570	50	60	1237	147	157	500	114	760	4"	1 3/8"	7/8"
280	2200	1600	800	398	1500	618	368	1570	50	70	1237	147	157	500	114	760	4"	1 3/8"	7/8"


Dimensions in mm unless stated



9.10 Process and Instrumentation Diagrams

YCWM, YCRM, YCWM-B and YCRM-B Models 60 to 150

YCWM Only



Code letters for Measure-, Switch- and Control			
Value [Pos. 1]	Add to Position 1	Function [Pos. 2]	
Pressure	P	Difference	D
Temperature	T	Proportion	P
Level	L	Relation	R
Flow Rate	F		
Density	D		
Humidity	M		
Elect. Conductivity	S		
Velocity	V		
Viscosity	W		
Weight	K		
Concentration	Y		
Safety Valve			
	n. DIN 19227		
		Indicator	I
		Recorder	R
		Counter	Q
		Controller	C
		Alarm	A
		Signal	S
		Interlock	B
		Maximum	+
		Minimum	-
		Max.Min.	O
		Test Point	X
		or Unit	
		Emergency	Z

Local	Display Remotely	Display in Panel	Display on Microprocessor Remotely

Components


- 1** Compressor
- 2** Condenser
- 3** Filter Drier
- 4** Sight Glass
- 5** Expansion Valve
- 6** Evaporator

Notes

- Shut Off Valves
- Schrader Valve
- Flow Switch supplied as Kit

YCWM, YCRM, YCWM-B and YCRM-B Models 170 to 280

YCWM Only



Code letters for Measure-, Switch- and Control		
Value (Pos. 1)	Add to Position 1	Function (Pos. 2)
Pressure	P	Indicator
Temperature	T	Recorder
Level	L	Counter
Flow Rate	F	Controller
Density	D	Alarm
Humidity	M	Signal
Elect. Conductivity	S	Interlock
Velocity	C	Maximum
Viscosity	V	Minimum
Weight	W	Max.Min.
Concentration	K	Test Point
Safety Valve	Y	or Unit
	n. DIN 19227	Emergency
		Z

Local	Display Remotely	Display in Panel	Display on Microprocessor Remotely

Components

- 1** Compressor
- 2** Condenser
- 3** Filter Drier
- 4** Sight Glass
- 5** Expansion Valve
- 6** Evaporator

Notes

- Shut Off Valves
- Schrader Valve
- Flow Switch supplied as Kit
- Common Manifold

10 SPARE PARTS

10.1 Recommended Spares

The table below lists the recommended spares for one unit for 2 years.

Component	Qty.
HP Switch	1
LP Switch	1
Differential Oil Pressure Switch	1
Gas Filter	2
Thermostatic Valve	1
Auxiliary Relays	2
Compressor Fuses	6
Auxiliary Fuses	6
Compressor Contactor	1
Power Contactor	1

10.2 Recommended Compressor Oils

The table below lists the recommended oil type for each unit.

Model	R22		R407C	
	Oil Type	Brand	Oil Type	Brand
YCWM/YCRM 60	1501	Shrieve Zerol	300SZ	CAN 300
YCWM/YCRM 75	1501	Shrieve Zerol	300SZ	CAN 300
YCWM/YCRM 90	1501	Shrieve Zerol	300SZ	CAN 300
YCWM/YCRM 120	1501	Shrieve Zerol	300SZ	CAN 300
YCWM/YCRM 150	1501	Shrieve Zerol	300SZ	CAN 300
YCWM/YCRM 170	1501	Shrieve Zerol	300SZ	CAN 300
YCWM/YCRM 200	1501	Shrieve Zerol	300SZ	CAN 300
YCWM/YCRM 240	1501	Shrieve Zerol	300SZ	CAN 300
YCWM/YCRM 280	1501	Shrieve Zerol	300SZ	CAN 300

10.3 Associated Diagrams

The tables below lists the wiring diagrams for each unit.

Model	Wiring Diagram	Model	Wiring Diagram
YCWM 60	035B60400-000	YCRM 60	035B60450-000
YCWM 75	035B60400-000	YCRM 75	035B60450-000
YCWM 90	035B60402-000	YCRM 90	035B60452-000
YCWM 120	035B60403-000	YCRM 120	035B60453-000
YCWM 150	035B60403-000	YCRM 150	035B60453-000
YCWM 170	035B60406-000	YCRM 170	035B60455-000
YCWM 200	035B60406-000	YCRM 200	035B60455-000
YCWM 240	035B60406-000	YCRM 240	035B60455-000
YCWM 280	035B60406-000	YCRM 280	035B60455-000

This page left intentionally blank

11 DE-COMMISSIONING , DISMANTLING AND DISPOSAL



Never release refrigerant to the atmosphere when emptying the refrigerating circuits. Suitable retrieval equipment must be used. If reclaimed refrigerant cannot be re-used. It must be returned to the manufacturer.



Never discard used compressor oil, as it contains refrigerant in solution. Return used oil to the oil manufacturer.

Unless otherwise indicated, the operations described below can be performed by any properly trained maintenance technician.

11.1 General

Isolate all sources of electrical supply to the unit including any control system supplies switched by the unit. Ensure that all points of isolation are secured in the 'OFF' position. The supply cables may then be disconnected and removed. For connection points refer to Section 4.

Remove all refrigerant from each system of the unit into a suitable container using a refrigerant reclaim or recovery unit. This refrigerant may then be re-used, if appropriate, or returned to the manufacturer for disposal. Under NO circumstances should refrigerant be vented to atmosphere. Drain the refrigerant oil from each system into a suitable container and dispose of according to local laws and regulations governing the disposal of oily wastes. Any spilt oil should be mopped up and similarly disposed of.

Isolate the unit heat exchanger(s) from all external water systems and drain the heat exchanger section(s) of the system. If no isolation valves are installed it may be necessary to drain the complete system(s).



If glycol or similar solutions have been used in the water system(s), or chemical additives are contained, the solution **MUST** be disposed of in a suitable and safe manner. Under **NO** circumstances should any system containing glycol or similar solutions be drained directly into domestic waste or natural water systems.

After draining, the water pipework can be disconnected and removed.

Packaged units can generally be removed in one piece after disconnection as above. Any fixing down bolts should be removed and then the unit should be lifted from position using the points provided and equipment of adequate lifting capacity.

Reference should be made to Section 4 for unit installation instructions, Section 9 for unit weights and Section 3 for handling.

Units which cannot be removed in one piece after disconnection as above, must be dismantled in position. Special care should be taken regarding the weight and the handling of each component. Where possible units should be dismantled in the reverse order of installation.



Residual refrigerant oil and glycol or similar solutions may remain in some parts of the system. These should be mopped up and disposed of as described above.

It is important to ensure that whilst components are being removed the remaining parts are supported in a safe manner.



Only use lifting equipment of adequate capacity.

After removal from position the unit parts may be disposed of according to local laws and regulations

This page left intentionally blank



YORK INTERNATIONAL

Part No. 035B40022-000 (04/99)

Subject to change without notice
ALL RIGHTS RESERVED