

SCREW COMPRESSOR S51 - 26
Refrigerating capacity and power consumption
Volume ratio 2.6

Capacity and power consumption

The capacity curves refer to a process with no subcooling of the liquid and no superheating of the suction gas. Corrections for subcooling and superheating are to be made according to manual sheet 430 - E - 1. For operating conditions outside shaded area select higher built-in volume ratio for best efficiency.

The capacity data are based on measurements with series-produced machines.

⊕ 50Hz
2950 r/m

Condenser performance

For condenser performance see manual sheet 4840 - E - 1.



Limitations

There are certain limitations in the operation range of the compressor.

For combination of condensing and evaporating temperatures outside the curves, ask for further information.

Refrigerant: NH₃

60Hz
3540 r/m



Dieses Blatt darf ohne unsere Erlaubnis weder kopiert, ändern überlassen oder in sonst unzulässiger Weise verwendet werden. Das Recht zu Änderungen behalten wir uns vor. STAL

This document must not be copied without our consent, nor must its contents be made known to others or otherwise unauthorizedly used. All data subject to change without notice. STAL

Denna handling får ej kopieras utan vårt medgivande och ej heller delges åt annan eller eljest obehörigen användas. Rätt till ändring-er och meddelande förbehålles. STAL

