



Selection: Semi-hermetic Reciprocating Compressors

Input Values

Compressor model Mode	(44G-60.2Y) Refrigeration and Air conditioning	Suction gas temperature Operating mode	20,00 °C Auto
Refrigerant	R404A	Power supply	400V-3-50Hz
Reference temperature	Dew point temp.	Capacity control	100%
Liq. subc. (in condenser)	0 K	Useful superheat	100%


Result

Q [W]	Cooling capacity	COP [-]	COP/EER
Qu* [W]	Evaporator capacity	m [kg/h]	Mass flow
P [kW]	Power input	Op.	Operating mode
I [A]	Current	th [°C]	Discharge gas temp. w/o cooling
Qc [W]	Condenser Capacity (w. HX)		

tc	to	5°C	0°C	-5°C	-10°C	-15°C	-20°C	-25°C	-30°C
30°C	Q [W]	190536	159790	133081	109897	89820	72494	57607	44884
	Qu* [W]	190536	159790	133081	109897	89820	72494	57607	44884
	P [kW]	38,1	37,1	35,6	33,7	31,4	28,8	26,0	23,1
	I [A]	69,0	67,5	65,4	62,7	59,6	56,2	52,7	49,2
	Qc [W]	226761	195064	166925	141902	119648	99877	82352	66865
	COP [-]	5,00	4,30	3,74	3,26	2,86	2,51	2,21	1,94
	m [kg/h]	4912	4062	3343	2734	2216	1776	1403	1087
	Op.	Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard
	th [°C]	58,0	64,3	70,8	77,6	84,8	92,6	101,1	110,8
	40°C	Q [W]	163554	137110	114042	93948	76492	61386	48374
Qu* [W]		163554	137110	114042	93948	76492	61386	48374	37224
P [kW]		45,8	43,5	40,8	37,8	34,5	31,1	27,6	24,1
I [A]		80,2	76,8	72,8	68,4	63,8	59,2	54,6	50,4
Qc [W]		207022	178393	152771	129824	109289	90948	74616	60134
COP [-]		3,57	3,16	2,80	2,49	2,22	1,97	1,75	1,54
m [kg/h]		4767	3933	3228	2630	2121	1689	1322	1012
Op.		Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard
th [°C]		69,0	75,2	81,6	88,3	95,5	103,3	112,0	122,1
50°C		Q [W]	136319	114179	94768	77797	63015	50200	39152
	Qu* [W]	136319	114179	94768	77797	63015	50200	39152	29685
	P [kW]	52,4	48,9	45,2	41,2	37,1	33,0	28,9	24,9
	I [A]	90,3	85,0	79,3	73,4	67,5	61,7	56,3	51,3
	Qc [W]	186101	160651	137671	116942	98285	81550	66607	53343
	COP [-]	2,60	2,33	2,10	1,89	1,70	1,52	1,35	1,19
	m [kg/h]	4625	3803	3108	2519	2018	1593	1233	929
	Op.	Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard
	th [°C]	80,0	86,1	92,5	99,2	106,5	114,5	123,7	134,9

-- No calculation possible (see message in single point selection)
 *According to EN12900 (20°C suction gas temp., 0K liquid subcooling)


Application Limits 100% 44G-60.2





Technical Data: (44G-60.2Y)

Dimensions and Connections



Technical Data

Technical Data

Displacement (1450 RPM 50Hz)	169,0 m ³ /h
Displacement (1750 RPM 60Hz)	204,0 m ³ /h
No. of cylinder x bore x stroke	4+4 x 75 mm x 55 mm
Weight	484 kg
Max. pressure (LP/HP)	19 / 28 bar
Connection suction line	76 mm - 3 1/8"
Connection discharge line	2x28 mm - 1 1/8"
Connection cooling water	R 3/4"
Oil type R134a/R407C/R404A/R507A/R407A/R407F	tc<55°C: BSE32 tc>55°C: BSE55 (Option)
Oil type R22 (R12/R502)	B5.2 (Standard)

Motor data

Motor voltage (more on request)	380-420V PW-3-50Hz
Max operating current	2x53.0 A
Winding ratio	50/50
Starting current (Rotor locked)	2x135.0 A Y / 2x220.0 A YY
Max. Power input	2 x 30,1 kW

Extent of delivery (Standard)

Motor protection	SE-B2
Enclosure class	IP54 (Standard), IP66 (Option)
Vibration dampers	Standard
Oil charge	9,00 dm ³

Available Options

Discharge gas temperature sensor	Option
Start unloading	Option
Capacity control	100-75-50-25% (Option)
Additional fan	Option
Water-cooled cylinder heads	Option
Oil service valve	Option
Crankcase heater	2 x 140 W (Option)
Oil pressure monitoring	MP54 (Option), Delta-PII (Option)

Sound measurement

Sound power level (+5°C / 50°C)	84,5 dB(A) @ 50Hz
Sound power level (-10°C / 45°C)	84,0 dB(A) @ 50Hz
Sound power level (-35°C / 40°C)	(89,5) dB(A) @ 50Hz
Sound pressure level @ 1m (+5°C / 50°C)	76,5 dB(A) @ 50Hz
Sound pressure level @ 1m (-10°C / 45°C)	76,0 dB(A) @ 50Hz
Sound pressure level @ 1m (-35°C / 40°C)	(81,5) dB(A) @ 50Hz



Semi-hermetic Reciprocating Compressors

Motor 1 = e.g. 4TES-12 with 12 "HP", primary for air-conditioning (e.g. R22,R407C) and air-conditioning with R134a at high ambient temperatures.

Motor 2 = e.g. 4TES-9 with 8 "HP", universal Motor for medium and low temperature application (e.g. R404A, R507A, R407A, R407F) and air-conditioning with R134a

Motor 3 = e.g. 4TES-8, for medium temperature applications and R134a

For more information concerning the application range use the "Limits" button.

Operation modes 4VES-7 to 6FE-44 and 44JE-30 to 66FE-88 with R407F/R407A/R22

CIC = liquid injection with low temperature application, suction gas cooled motor.

ASERCOM certified performance data

The Association of European Refrigeration Component Manufacturers has implemented a procedure of certifying performance data. The high standard of these certifications is assured by:

- * plausibility tests of the data performed by experts.
- * regular measurements at independent institutes.

These high efforts result in the fact that only a limited number of compressors can be submitted. Due to this not all BITZER compressors are certified until now. Performance data of compressors which fulfil the strict requirements may carry the label "ASERCOM certified". In this software you will find the label at the respective compressors on the right side below the field "result" or in the print out of the performance data. All certified compressors and further information are listed on the homepage of ASERCOM.

Condensing capacity

The condensing capacity can be calculated with or without heat rejection. This option can be set in the menu Program Options. The heat rejection is constantly 5 % of the power consumption. The condensing capacity is to be found in the line Condensing cap. (with HR) resp. Condensing capacity.

Data for sound emission

Data based on 50 HZ application (IP-units 60 Hz) and R404A if not declared.

Sound pressure level: values based on free field area conditions with hemispherical sound emission in 1 meter distance.

General remarks regarding sound data

Listed sound data were measured under testing conditions in our laboratory. For this purpose the free-standing test sample is mounted on a solid foundation plate and the pipework is connected vibration-free to the largest extent possible. Suction and discharge lines are fixed in a flexible configuration, such that a transmission of vibrations to the environment can be largely excluded. In real installations considerable differences might be observed, compared to the measurements in the laboratory. The airborne sound emitted by the compressor can be reflected from surfaces of the system and this may increase the airborne sound level measured close to the compressor. Vibrations caused by the compressor are also transferred to the system by the compressor feet and piping depending on the damping ratio of the fixings. Thus, the vibrations can induce other components to such an extent that these components contribute to an increase in airborne sound emission. If required, the transfer of vibrations to the system can be minimized by suitable fixing and damping elements.

Legend of connection positions according to "Dimensions":

- 1 High pressure connection (HP)
- 2 Connection for discharge gas temperature sensor (HP) (for 4VE(S)-6Y .. 4NE(S)-20(Y) connection for CIC sensor as alternative)
- 3 Low pressure connection (LP)
- 4 CIC system: injection nozzle (LP)
- 4b Connection for CIC sensor
- 4c Connection for CIC sensor (MP / operation with liquid subcooler)
- 5 Oil fill plug
- 6 Oil drain
- 7 Oil filter (magnetic screw)
- 8 Oil return (oil separator)
- 8* Oil return with NH3 and insoluble oil
- 9 Connection for oil and gas equalization (parallel operation)
- 9a Connection for gas equalization (parallel operation)
- 9b Connection for oil equalization (parallel operation)
- 10 Oil heater connection
- 11 Oil pressure connection +
- 12 Oil pressure connection –
- 13 Cooling water connection
- 14 Intermediate pressure connection (MP)
- 15 Liquid injection (operation without liquid subcooler and with thermostatic expansion valve)
- 16 Connection for oil monitoring (opto-electrical oil monitoring "OLC-K1" or differential oil pressure switch "Delta-PII")



4G-30 2Y

BITZER Software v6.10.2 rev2250

30.09.2019 / All data subject to change.

4 / 4

- 17 Refrigerant inlet at liquid subcooler
 - 18 Refrigerant outlet at liquid subcooler
 - 19 Clamp space
 - 20 Terminal plate
 - 21 Maintenance connection for oil valve
 - 22 Pressure relief valve to the atmosphere (discharge side)
 - 23 Pressure relief valve to the atmosphere (suction side)
 - 24 IQ MODULE
 - SL Suction gas line
 - DL Discharge gas line
- Dimensions can show tolerances according to EN ISO 13920-B.