

DWM D2DL3-75X-AWM/D (x2) / D22DL3-150X-AWM/D

Specifications

Hersteller	DWM
Typ	D2DL3-75X-AWM/D (x2) / D22DL3-150X-AWM/D
Kältemittel	Freon
kW at 0°C/+40°C	39,0
kW at -5°C/+40°C	31,6
kW at -10°C/+40°C	25,2
kW at -20°C/+40°C	15,2
kW at -30°C/+40°C	8,3
Druckschalter	✓
Druckmanometer	✓
Flüssigkeitssammler	✓
Ölabscheider	✓
Schauglass	✓
m ³ / h	47,4
Bemerkungen	Y.o.b. 2001
Package / Rack	✓
Größe	2000x700x800 mm (LxWxH)
Stock	1



Description

Used DWM D2DL3-75X-AWM/D (x2) / D22DL3-150X-AWM/D

Gebrauchter DWM D2DL3-75X-AWM/D (x2) / D22DL3-150X-AWM/D halbhermetischer Tandem-Kolbenkompressor auf Freon. Komplett mit Flüssigkeitssammler, AC&R S-5188 Ölabscheider und Druck- und Sicherheitsschaltern/-manometern. Der Tandemkompressor hat eine Gesamtverdrängung von 47,4 m³/h.



