

Bock F5 (x3) condensing unit

Specifications

Hersteller	Bock
Typ	F5 (x3) condensing unit
Kältemittel	Freon
kW at +10°C/+40°C	249.99
kW at 0°C/+40°C	178.20
kW at -5°C/+40°C	147.45
kW at -10°C/+40°C	120.03
kW at -20°C/+40°C	74.82
kW at -30°C/+40°C	41.94
kW at -40°C/+40°C	20.94
kW at -45°C/+40°C	14.16
E-Motor Specs	11 kW (x3)at 1445 RPM
Anlaufentlastung	✓
Leistungsregelung	✓
Druckschalter	✓
Druckmanometer	✓
Flüssigkeitssammler	✓
Flüssigkeitssammler	115
Inhalt ltr.	
Ölabscheider	✓
Bemerkungen	Electromotor: 11 kW at 1445 RPM // Pully EM: 180 mm / Pully compr.: 200 mm
Bemerkungen	R404a - R22 or other freon types
Condensing Unit	✓



Größe	3800x1800x2000 mm (LxWxH)
-------	------------------------------

Stock	1
-------	---

Description

Used Bock F5 (x3) condensing unit



R404A/R507		Performance data											1.450 rpm	
Type	Cond. temp. °C	Cooling capacity \dot{Q}_c [W]											Power P [kW]	
		Evaporating temperature °C												
		10	5	0	-5	-10	-15	-20	-25	-30	-35	-40	-45	
FX2	30 Q	13423	11418	9621	8020	6606	5366	4290	3366	2584	1933	1402	979	
	P	2.21	2.19	2.13	2.05	1.94	1.80	1.65	1.48	1.31	1.12	0.94	0.75	
FX3	40 Q	11561	9785	8201	6797	5562	4485	3555	2761	2092	1537	1085	724	
	P	2.65	2.56	2.44	2.30	2.13	1.95	1.76	1.55	1.34	1.12	0.91	0.70	
FX4	30 Q	9652	8113	6749	5548	4500	3593	2816	2159	1609	1157	791		
	P	3.03	2.88	2.71	2.51	2.30	2.07	1.83	1.59	1.34	1.10	0.86		
FX5	40 Q	28402	24165	20377	17071	14041	11442	9187	7231	5658	4231	3096	2175	
	P	3.92	3.97	3.94	3.83	3.66	3.44	3.17	2.88	2.56	2.23	1.90	1.57	
FX14/1166	30 Q	24498	20763	17437	14495	11911	9657	7710	6042	4628	3442	2458	1650	
	P	4.97	4.85	4.66	4.41	4.11	3.77	3.40	3.01	2.61	2.21	1.83	1.46	
FX14/1366	40 Q	20584	17356	14498	11985	9791	7889	6254	4860	3660	2690	1862		
	P	5.90	5.62	5.31	4.89	4.47	4.02	3.56	3.08	2.61	2.15	1.72		