

Helpman LEX-24-E

Specifications

Hersteller	Helpman
Typ	LEX-24-E
Kälteleistung kW	17,8
Kältemittel	Freon
Anzahl der Ventilatoren	2
Ventilator Durchmesser	7
in mm	
Abtauung	Electric
Luftdurchsatz in m ³ /h	11600
Größe	2030x800x780 mm
Bemerkungen	Diameter fan 50 cm
Remarks	Surface 69,8 m ²
Volume	28,2 dm ³
Gewicht	128 kg
Stock	1



Description

Used Helpman LEX-24-E

Used blow-through Helpman LEX-24-E evaporator with electric defrosting. Two antriebstechnik fans, 0,22 kW and 1330 RPM, diameter 50 cm. *All components of this used evaporator will be tested on good working, leak free condition (electro engines), coils, bearings) Choosing HOSBV means buying with warranty. We perform a industrial cleaning and rust spots will be covered. Also, we can arrange your shipment.



HELPMAN DUJJC
C3-86

Blow Through Unit Coolers 1.5 - 40 kW **LEX**

Nominal Capacities (kW)

Cooler type	R 22		R 134a		R 404A		For reference only	
	frosted DT _i	dry conditions DT _i	frosted DT _i	dry conditions DT _i	frosted DT _i	dry conditions DT _i	R 22	R 134a R 404A
Fin spacing 4 mm								
LEX 2-4	1.5	1.3	1.5	1.5	1.3	1.1	1.3	
LEX 4-4	1.9	1.5	1.8	1.7	1.3	1.6		
LEX 6-4	2.9	2.4	2.8	2.4	2.1	2.5		
LEX 8-4	4.7	4.1	4.7	4.1	3.5	4.1		
LEX 10-4	5.7	4.4	4.8	4.1	3.8	4.5		
LEX 12-4	5.9	5.6	6.2	5.1	4.9	5.4		
LEX 14-4	8.5	6.4	7.1	5.7	5.6	6.2		
LEX 16-4	8.7	6.4	9.3	7.5	7.3	8.1		
LEX 18-4	9.7	8.7	9.8	8.5	7.6	8.8		
LEX 20-4	12.8	10.8	12.7	11.8	9.4	11.0		
LEX 22-4	16.1	13.0	15.4	14.0	11.3	13.4		
LEX 24-4	20.0	16.1	19.2	17.4	14.0	16.7		
LEX 26-4	26.0	23.0	26.0	22.6	20.0	22.8		
LEX 28-4	32.8	29.0	33.2	29.5	25.2	29.9		
LEX 30-4	40.3	32.5	39.5	35.0	29.3	33.4		
Fin spacing 7 mm								
LEX 2-7	1.3	1.2	1.3	1.1	1.0	1.2		
LEX 4-7	1.7	1.4	1.7	1.5	1.2	1.4		
LEX 6-7	2.5	2.2	2.5	2.2	1.9	2.2		
LEX 8-7	4.1	3.7	4.3	3.8	3.3	3.7		
LEX 10-7	3.7	3.6	4.0	3.2	3.2	3.5		
LEX 12-7	5.0	4.9	5.3	4.4	4.3	4.6		
LEX 14-7	5.5	5.5	6.0	4.9	4.8	5.2		
LEX 16-7	7.4	7.3	8.0	6.4	6.3	7.0		
LEX 18-7	8.5	7.8	8.8	7.4	7.0	7.9		
LEX 20-7	11.4	10.0	11.4	9.9	8.7	9.9		
LEX 22-7	14.5	12.4	14.4	12.6	10.7	12.4		
LEX 24-7	18.1	15.6	17.8	15.7	13.5	15.5		
LEX 26-7	22.8	21.2	23.4	19.8	18.4	20.4		
LEX 28-7	28.5	26.5	28.5	24.8	23.0	25.5		
LEX 30-7	36.5	31.0	35.9	31.7	27.0	31.2		

Capacities
 -Lightly frosted coil
 -Relative Humidity 95 %
 -Suction gas superheating 22 % of the temperature difference (DT_i) with a minimum of 3.5 K