

York YLCA - 60 - G1TP 380T

Specifications

Brand	York
Type	YLCA - 60 - G1TP 380T
Product type	Air Cooled Chiller
Capacity kW	60,1
Capacity Tons	17,1
Refrigerant	Freon
Refrigerant Type	R410
Weight in kg.	611
Sizes	2450x1020x1720 mm (LxWxH)
Display	Carel uC2 SE
Number of fans	2
Fan specifications	50 Hz - 0,60 kW - 660 RPM
Remarks	Y.o.b. 2015



Description

Used York YLCA - 60 - G1TP 380T

Used York YLCA - 60 - G1TP 380T air cooled chiller build in 2015. Complete with 2 scroll compressors, Condenser with 2 EBM-papst fans - 50 Hz - 0,60 kW - 660 RPM, Plate heat exchanger as evaporator and a Carel uC2 SE control panel.

*All components of this used chiller will be tested on adequate performance, leak free condition (condensing blocks), compressors, fans, control panel, and so forth). Choosing HOSBV means buying with warranty. We perform an industrial cleaning. *If requested we are happy to arrange your shipment.



CONTROL		CE JOHNSON CONTROLS MANUFACTURING, TURKEY	
S/N.		80011E53733981	
CONTROL		CE Johnson Controls Klima ve Soğutma Servis San. ve Tic. A.Ş. Manisa Subesi. Muradiye San Bölgesi, Dr. 0099 Orhan Aksoy Cad, No:14 Muradiye, Manisa Türkiye	
MOD.	YLCA-60-G1TP 380T	SAP CODE	S668526182
INDOOR HEAT EXCHANGE		n° 1	
<input type="checkbox"/> 60.5 kW COOLING	<input checked="" type="checkbox"/> kW HEATING		
MAXIMUM TEMPERATURE (TS)		<input checked="" type="checkbox"/> °C	MAXIMUM PRESSURE (PS) <input type="checkbox"/> 4,1 MPa
AIR FLOW	<input checked="" type="checkbox"/> dm ³ /s	<input checked="" type="checkbox"/> m ³ /s LIQUID	<input type="checkbox"/> 2,9 dm ³ /s <input type="checkbox"/> 0,6 MPa
OUTDOOR HEAT EXCHANGER n°		2 MAXIMUM PRESSURE (PS) <input type="checkbox"/> 4,1 MPa	
MAXIMUM TEMPERATURE (TS)		<input type="checkbox"/> 46 °C	LIQUID <input type="checkbox"/> 2,9 dm ³ /s <input checked="" type="checkbox"/> MPa
AIR FLOW	<input checked="" type="checkbox"/> dm ³ /s	<input type="checkbox"/> 5,17 m ³ /s	
HEAT RECOVERY		MAXIMUM PRESSURE (PS) <input checked="" type="checkbox"/> MPa n° <input checked="" type="checkbox"/>	
<input checked="" type="checkbox"/> kW HEATING	LIQUID	<input checked="" type="checkbox"/> dm ³ /s	<input checked="" type="checkbox"/> MPa
COMPRESSOR n°	2		CIRCUIT n° 1
GAZ	<input type="checkbox"/> R410 <input type="checkbox"/> 16	KG.Cire. OPERATING WEIGHT	<input type="checkbox"/> 611 Kg. <input checked="" type="checkbox"/> dBA
3 PHASES	<input type="checkbox"/> 400 V. <input type="checkbox"/> 50 Hz.	<input type="checkbox"/> 26,3 kW	<input type="checkbox"/> 44 IP.
COOLING CEE	<input checked="" type="checkbox"/> W/W	<input type="checkbox"/> 42 (FL)AMPS.	<input type="checkbox"/> 118 (LR)AMPS
HEATING CEE	<input checked="" type="checkbox"/> W/W	<input checked="" type="checkbox"/> (FL)AMPS.	<input checked="" type="checkbox"/> (LR)AMPS









