

Carrier 30 RB 302

Specifications

Brand	Carrier
Туре	30 RB 302
Product type	Air Cooled Chiller
Capacity kW	293,0
Capacity Tons	83,3
Refrigerant	Freon
Refrigerant Type	R410A
Weight in kg.	2519
Sizes	3590x2250x2400 mm
	(LxWxH)
Compressor(s) type &	3x Performer
model	SH240A4ACE &
	Performer SH300B4ACC
Display	Carrier Pro-Dialog+
Number of fans	5
Remarks	Y.o.b. 2015
Remarks	Around 2.000 operating
	hours



Description

Used Carrier 30 RB 302

Used Carrier 30 RB 302 air cooled chiller on R410A and build in 2015. Complete with 3x Performer SH240A4ACE & 2x SH300B4ACC hermetic scroll compressors, condenser with grooved copper tubes and aluminium fins and 5 fans with a total airflow of 22,569 l/s. shell and tube functioning as evaporator with a volume of 110 liter, liquid line filter driers. Carrier Pro-Dialog+ and Danfoss VLT HVAC drives. The water chiller has around 2000 operating hours. *All components of this used chiller will be tested on good working, leak free condition (condensing blocks), compressors, fans, control panel, etcetera). Choosing HOSBV means buying with warranty. We perform a industrial cleaning and rust spots will



be covered. Also, we can arrange your shipment.







-REVETENENT DES ECHANGEURS A AIR AIR HEAT EXCHANGER COATING LUET-WARMETAUSCHER BESCHICHTUNG ENVIRO SHIELD
(FR) NUMERO DE SERIE SERIAL NUMER SERIENNUMER M2015003197
MUDELLNUMMER 30RB03021012-PE-
3 - VARIANTE VARIANT 30RB
VARIANTE STANICA ET ANTE DESAI - MARE E FARICIATIONE A DI ESTAN MENTELINGUERMI MO MATIM MENTELINGUERMI MO MATIM
25 - Flutte Pendant le Transport Medium During: He Transport Flutstoet where Des transportes R410a 31.5 kg
s - FLUIDE - GROUPE -
7 - CHARGES CIRCUIT A/B/C MEDIAN CHARGE A/B/C KREISLAW A/B/C 18.50 / 13.00 / * kg
9 - FLUIDE O'INERTAGE INERTING KEDIUM MEUTRALISEMMA-HEDIUM
21 - HAUTE PRESSION 22 - BASSE PRESSION HIGH PRESSURE LOW PRESSINE
10 - PRESSION ADMISSIBLE MIN/MAX ALLAMBLE PRESSIGN FINI/MAX ZULASSIE MIN/MAX. BULKASE MIN/MAX DULASSIE MIN/MAX. BULKASE (PS) -1.0 / 44.20 bar -1.0 / 29.00 bar
11 - ТЕМРЕРАТИЛЕ АЛИТІЗСІВLЕ ИТИМИХ ДОЛАЗСІЕ ТЕМРЕРАТИЛЕ ПІХИМАХ ДОЛАЗСІЕ ТЕМРЕРАТИЛЕ ТИКИКАХ - ТЕМРЕРАТИЛЕ (Т5) -20.0 / 68.0 °C -20.0 / 48.0 °C
12 - PRESSION DE DECLENCHEMENT DES PRESSOSTATS MIRICIS SETTING MIRICIS SETTING MIRICIS SETTING MIRICIS DE DECLENCIS 44.2 bar * bar
13 - PRESSION DE DECLENCHEMENT DES SOUPARES SAFETY RELLES VALVE SETTING KONCHEMENTER VALVE SETTING
14 - PRESSION D'ESSAL D'ETANCHEITE DE L'UNITE
15 - TENSION + -
SPANNING 400 V 10% 10% 16-PHASES 3
19 - PUISSANCE ARSORRES MAY
Ne prese treat the term of ter
Mitmain Z519 kg 24- metosa w accusament no utorat or nortune meter and and arguint and utorat or nortune
Bar * bar bar * bar constructions of another set and the set and



































