

Frascold Q7-36.1Y (x2)

Specifications

Brand	Frascold
Type	Q7-36.1Y (x2)
Refrigerant	Freon
kW at -5°C/+40°C	49,3
kW at -10°C/+40°C	40,7
kW at -20°C/+40°C	26,5
kW at -30°C/+40°C	16,1
kW at -40°C/+40°C	8,7
kW at -45°C/+40°C	5,8
Capacity Control	✓
On steel base frame	✓
Pressure safety switches	✓
Hp/Lp/Op	
Liquid receiver	✓
Liquid receiver ltr.	50
Oil separator	✓
Sight Glass	✓
m3 / h	67,2
Package / Rack	✓
Sizes	1200x1010x1810 mm (LxWxH)



Description

Used Frascold Q7-36.1Y (x2)

Used Frascold TWINQ7-36.1Y compressor unit on Freon. Complete with 2x Frascold Q7-36.1Y semi-hermetic piston compressors, GVN HLR-8A-F/F-50x1 liquid receiver with a volume of 50 liters, pressure and safety switches, Carel NXL003152H variable frequency converter, Soler & Palau REB-5 speed controller, Televis Compact 600 monitor, Eliwell EWCM 6100 display and a control box.

*Why choose for HOSBV? We're not only the largest used refrigeration specialist in Europe, but also, we deliver all equipment including an extensive test, warranty and an industrial cleaning.

*Optionally we can also perform a new paint job and arrange the logistics.



frascold® Type **TWINQ7-36.1Y**
Nr. **0M001002**

Hz	Displ. m ³ /h	RPM	Max. Operating Disch. Pressure	bar 80
50	35,86	1450	Max. Static Suct. Pressure	bar 20,5
60	43,04	1740		

Oil type: POE32 3~ **CE**

Volt		Hz	MRA		LRA	
Δ	Y		Δ	Y	Δ	Y
220-240	380-420	50	33,6	19,4	152	87,3
265-290	440-480	60	33,6	19,4	152	87,3

Frascold S.p.A. **TQ7361 0AM001002** FRASCALDINA ITALY







