

Carrier 30 RA 080

Specifications

Brand	Carrier
Type	30 RA 080
Product type	Air Cooled Chiller
Capacity kW	79,0
Capacity Tons	22,5
Refrigerant	Freon
Refrigerant Type	R407C
Weight in kg.	631
Sizes	2100x1100x1350 mm (LxWxH)
Compressor(s) type & model	1x Performer SZ185S4CC & 1x Performer SZ185S4RC
Display	Carrier Pro-Dialog Plus
Number of fans	1
Fan specifications	50 Hz - 1,8/0,25 kW - 945/465 RPM
Remarks	Y.o.b. 2003



Description

Used Carrier 30 RA 080

Used Carrier 30 RA 080 air cooled chiller on R407C. Complete with 1 Performer SZ185S4CC & 1 Performer SZ185S4RC scroll compressor, condenser with 1 fan - 50 Hz - 1,8/0,25 kW - 945/465 RPM, plate heat exchanger functioning as evaporator with a volume of 7,6 dm³, water pump and a Carrier Pro-Dialog Plus display. *All components of this used chiller will be tested on adequate performance, leak free condition (condensing blocks), compressors, fans, control panel, and so forth). Choosing HOSBV means buying with warranty. We perform a industrial cleaning. if requested we can arrange your shipment.



1 - NUMERO DE SÉRIE SERIAL NUMBER	12V312723	
2 - MODÈLE - MODEL	30RA-080-A0325-PEE--	
3 - VARIANTE - VARIANT	30RA	
4 - ANNÉE DE FABRICATION ET DATE D'ESSAI YEAR OF MANUFACTURING AND TEST DATE	2003/09/03	
5 - FLUIDE - MEDIUM R	407C	CE0062
6 - GROUPE - GROUP	2	
7 - CHARGES CIRCUIT A	18,0 kg	8 - CHARGES CIRCUIT B 0,0 kg
9 - FLUIDE DE CONFINEMENT CONFINEMENT MEDIUM	23 - --AZOTE--NITROGENE--	
10 - PRESSION ADMISSIBLE MIN/MAX ALLOWABLE PRESSURE MIN/MAX (PS)	21 - HAUTE PRESSION HIGH PRESSURE 0,9 32,0 bar	22 - BASSE PRESSION LOW PRESSURE 0,9 25,0 bar
11 - TEMPERATURES ADMISSIBLE MIN/MAX ALLOWABLE TEMPERATURE MIN/MAX (TS)	- 20 72 °C	- 20 62 °C
12 - PRESSION DE DÉCLENCHEMENT DES PRESSOSTATS PRESSURE SWITCH SETTING	29,0 bar	
13 - PRESSION DE DÉCLENCHEMENT DES SOUPAPES SAFETY RELIEF VALVE SETTING	0,0 bar	25,0 bar
14 - PRESSION D'ESSAI D'ÉTANCHÉITÉ DE L'UNITÉ UNIT LEAK TEST PRESSURE	15,0 bar	
15 - TENSION VOLTAGE	400 V	10 10 % 16 - PHASES 3
17 - FRÉQUENCE FREQUENCY	50 Hz	18 - I MAXIMALE MAXIMUM AMPS 67,2 0,0 A
19 - PUISSANCE ABSORBÉE MAX MAX POWER INPUT	40,0 0,0 kW	
20 - POIDS NET NET WEIGHT	631 kg	

MANUFACTURING IN FRANCE BY
CARRIER s.a.
01120 - MONTLUEL - FRANCE
A SUBSIDIARY OF CARRIER CORPORATION
SYRACUSE NEW YORK
UNITED STATES OF AMERICA










