

Bitzer 6G.2Y (x2) & 4N.2Y (x1)

Specifications

| | |
|------------------------------|------------------------------|
| Brand | Bitzer |
| Type | 6G.2Y (x2) & 4N.2Y (x1) |
| Refrigerant | Freon |
| kW at -5°C/+40°C | 206,1 |
| kW at -10°C/+40°C | 169,9 |
| kW at -20°C/+40°C | 111,5 |
| kW at -30°C/+40°C | 68,2 |
| kW at -40°C/+40°C | 37,0 |
| kW at -45°C/+40°C | 25,0 |
| Unloaded Start | ✓ |
| On steel base frame | ✓ |
| Pressure safety switches | ✓ |
| Hp/Lp/Op | |
| Pressure gauges | ✓ |
| Hp/Lp/Op | |
| Condensing pressure switches | ✓ |
| Oil separator | ✓ |
| Oil level system AC&R | ✓ |
| Solenoid Valve | ✓ |
| m3 / h | 373,7 |
| Remarks | SN: 1672714195 - Y.o.b. 2007 |
| Remarks | SN: 1666105748 - Y.o.b. 2004 |
| Remarks | SN: 1677105759 - Y.o.b. 2009 |



| | |
|----------------|------------------------------|
| Package / Rack | ✓ |
| Sizes | 2900x1650x2000 mm (LxWxH) |

Description

Used Bitzer 6G.2Y (x2) & 4N.2Y (x1)

Used Bitzer semi-hermetic reciprocating rack on Freon. Complete with a Bitzer 4N.2Y that has a Rotor KF180L25 electric motor - 50 Hz - 7,5/11 kW - 980/1470 RPM, Bitzer 6G.2Y (x2) both with a Rotor electric motor - 50 Hz - 30 kW - 1465 RPM, oil separator, oil reservoir, oil level regulator and pressure and safety switches/gauges. The compressor rack has a total displacement of 373,7 m³/h.
*Why choose for HOSBV? Were not only the largest used refrigeration specialist in Europe, but also, we deliver all equipment including an extensive test, warranty and industrial cleaning.
*Optional we can also perform a new paint job and arrange the logistics.





