

Carrier 30 HXC 130

Specifications

Brand	Carrier
Type	30 HXC 130
Product type	Water Cooled Chiller
Capacity kW	450,0
Capacity Tons	128,0
Refrigerant	Freon
Refrigerant Type	R134A
Weight in kg.	2.474
Sizes	3600x1000x2000 mm (LxWxH)
Compressor(s) type & model	1 Carrier 06NW2250S7NC & 1 Carrier 06NW2209S7NC
Display	Carrier Pro-Dialog Plus
Remarks	Y.o.b. 2008



Description

Used Carrier 30 HXC 130

Used Carrier 30 HXC 130 water cooled chiller on R134A. Complete with 1 Carrier 06NW2250S7NC & 1 Carrier 06NW2209S7NC screw compressor, shell and tube as evaporator with a water volume of 65 liter, Carrier 09RX2100FA-216-PEE-- shell and tube as condenser with a water volume of 78 liter and a Carrier Pro-Dialog Plus. *All components of this used chiller will be tested on adequate performance, leak free condition (condensing blocks), compressors, fans, control panel, and so forth). Choosing HOSBV means buying with warranty. We perform an industrial cleaning. *If requested we are happy to arrange your shipment.



1 - (FR) NUMERO DE SERIE (EN) SERIAL NUMBER (DE) SERIENNUMMER	12Y819624	
2 - MODELE - MODEL MODELLNUMMER	30HCX130-A0430-PEE - -	
3 - VARIANTE VARIANT VARIANTE	30HCX	
4 - ANNEE DE FABRICATION ET DATE D'ESSAI YEAR OF MANUFACTURING AND TEST DATE HERSTELLUNGSJAHR UND DATUM	25/11/2008	
5 - FLUIDE - REFRIGERANT KÄLTEMITTEL	R 134 a	
6 - GROUPE - GROUP GRUPPE	2	
7 - CHARGES CIRCUIT A/B REFIG. CHARGE A/B KREISLAUF A/B	51.00 Kg /	47.00 Kg
9 - FLUIDE D'INERTAGE INERTING MEDIUM NEUTRALISIERUNG-MEDIUM	23 - -AZOTE--NITROGEN--STICKSTOFF	
10 - PRESSION ADMISSIBLE MIN/MAX ALLOWABLE PRESSURE MIN/MAX ZULASSIGE MIN/MAX -DRUCKE	(PS) -1.0 / 21.00 bar	-1.0 / 21.00 bar
11 - TEMPERATURE ADMISSIBLE MIN/MAX ALLOWABLE TEMPERATURE MIN/MAX ZULASSIGE MIN/MAX -TEMPERATUREN	(TS) -20 / 72 °C	-20 / 72 °C
12 - PRESSION DE DECLENCHEMENT DES PRESSOSTATS PRESSURE SWITCH SETTING DRUCKSCHALTER-SOLLDRUCK	16.0 bar	* bar
13 - PRESSION DE DECLENCHEMENT DES SOUPAPES SAFETY RELIEF VALVE SETTING SICHERHEITSENTWÄHLER-SOLLDRUCK	23.0 bar	23.0 bar
14 - PRESSION D'ESSAI D'ETANCHEITE DE L'UNITE UNIT LEAK TEST PRESSURE LECKTEST-DRUCK DES GERÄTS		15.0 bar
15 - TENSION VOLTAGE SPANNUNG	400 V	10% 10% 16 - PHASES PHASES PHASEN 3
17 - FREQUENCE FREQUENCY FREQÜENZ	~ 50 Hz	18 - I MAXIMALE MAXIMUM AMPERE MAXIMALER STROM 236.00 / * A
19 - PUISSANCE ABSORBÉE MAX MAX POWER INPUT LEISTUNGSAUFNAHME	144.00 / * kW	
20 - POIDS NET NET WEIGHT NETTOGEWICHT	2474 Kg	
24 - PRESSION DE DECLENCHEMENT DES DISQUES DE RUPTURE RUPTURE DISCS SETTING EINSTELLDRUCK DER BRUCHScheiben	* bar	* bar

CE 0062

Carrier

MANUFACTURED IN FRANCE BY
CARRIER SCS - 01120 MONTLUEL - FRANCE
A SUBSIDIARY OF CARRIER CORPORATION
SYRACUSE NEW YORK UNITED STATES OF AMERICA







