

Carrier 30XWHP0862

Specifications

Brand	Carrier
Type	30XWHP0862
Product type	Heat pump
Capacity kW	982,0
Capacity Tons	279,2
Refrigerant	Freon
Refrigerant Type	R134A
Weight in kg.	3965
Sizes	3900x1200x1950 mm (LxWxH)
Compressor(s) type & model	1x Carrier 06TW819SW1C
Display	Carrier Touch Pilot 33CNTPILOT-01-R



Description

Used Carrier 30XWHP0862

Used Carrier 30XWHP0862 water-sourced screw heat pump on R134A. Complete with 1 Carrier 06TUW819SW1C screw compressor, shell and tube evaporator with a volume of 154 liter, shell and tube condensor with a volume of 148 liter, SWEP V120THx66/1P-NC-S braced heat exchanger and a control cabinet with a Carrier Touch Pilot 33CNTPILOT-01-R controller. The condensor has a maximum leaving temperature of 50°C. *All components of this used chiller will be tested on adequate performance, leak free condition (condensing blocks), compressors, fans, control panel, and so forth). Choosing HOSBV means buying with warranty. We perform a industrial cleaning. if requested we can



Your partner for used commercial and
industrial refrigeration equipment

arrange your shipment.



1 - (FR) NUMERO DE SERIE (EN) SERIAL NUMBER (DE) SERIENNUMMER	12Z914186
2 - MODELE - MODEL MODELLNUMMER	30XWHP0862-0001PEE--
3 - VARIANTE VARIANT VARIANTE	30XW
4 - ANNEE DE FABRICATION ET DATE D'ESSAI YEAR OF MANUFACTURING AND TEST DATE HERSTELLUNGSDATUM UND DATUM	11/01/2010
5 - FLUIDE - MEDIUM KÄLTERMITTEL	R 134 a
6 - GROUPE - GROUP GRUPPE	2
7 - CHARGES CIRCUIT A/B MEDIUM CHARGE A/B KREISLAUF A/B	170.00 Kg / * Kg
9 - FLUIDE D'INERTAGE INERTING MEDIUM NEUTRALISIERUNG-MEDIUM	23 --AZOTE--NITROGEN--
10 - PRESSION ADMISSIBLE MIN/MAX ALLOWABLE PRESSURE MIN/MAX ZULASSIGE MIN/MAX - DRUCKE	(PS) -1.0 / 21.00 bar
11 - TEMPERATURE ADMISSIBLE MIN/MAX ALLOWABLE TEMPERATURE MIN/MAX ZULASSIGE MIN/MAX - TEMPERATUREN	(TS) -20 / 72 °C
12 - PRESSION DE DECLENCHEMENT DES PRESSOSTATS PRESSURE SWITCH SETTING DRUCKSCHALTER-SOLLDRUCK	15.0 bar
13 - PRESSION DE DECLENCHEMENT DES SOUPAPES SAFETY RELIEF VALVE SETTING SICHERHEITSVENTIL - SOLLDRUCK	23.0 bar
14 - PRESSION D'ESSAI D'ETANCHEITE DE L'UNITE UNIT LEAK TEST PRESSURE LECKTEST-DRUCK DES GERÄTS	15.0 bar
15 - TENSION VOLTAGE SPANNUNG	400 V 10% 10%
17 - FREQUENCE FREQUENCY FREQUENZ	~ 50 Hz
19 - PUISSANCE ABSORBEE MAX MAX POWER INPUT LEISTUNGSAUFNAHME	223.00 / * kW
20 - POIDS NET NET WEIGHT NETTOGEWICHT	3646 Kg
24 - PRESSION DE DECLENCHEMENT DES DISQUES DE RUPTURE RUPTURE DISC SETTING EINSTELLDRUCK DER RÜFTSCHREIBEN	* bar





