

### Bitzer HSN 7471-75 (x2) & HSN 7451-60 (x1)

### **Specifications**

Brand	Bitzer
Туре	HSN 7471-75 (x2) & HSN
	7451-60 (x1)
Refrigerant	Freon
kW at -20ºC/+40ºC	259,7
kW at -30ºC/+40ºC	161,6
kW at -40ºC/+40ºC	94,3
kW at -45ºC/+40ºC	69,7
Unloaded Start	1
Capacity Control	✓
On steel base frame	✓
Pressure safety switches	1
Hp/Lp/Op	
Pressure gauges	✓
Hp/Lp/Op	
Oil separator	✓
Liquid line filter drier	✓
Solenoid Valve	✓
Control panel	✓
m3 / h	692





Reckardes / Rack

Sizes

evaporators.

Please note we will only				
4990x11320x180001etre				
uasvidezing solution				
with capacity matching				
condensor and				

#### Description

### Used Bitzer HSN 7471-75 (x2) & HSN 7451-60 (x1)

Used Bitzer HSN 7471-75 (x2) & HSN 7451-60 (x1) screw compressor rack on Freon. Complete with a Bitzer OA 9011 oil separator, braced heat exchanger as oil cooler, liquid line filter drier and pressure and safety switches/gauges. The compressors have a total displacement of 692 m<sup>3</sup>/h.

Please note we will only offer this as complete blastfreezing solution with capacity matching condensor and evaporators

\*Why choose for HOSBV? Were not only the largest used refrigeration specialist in Europe, but also, we deliver all equipment including an extensive test, warranty and industrial cleaning. \*Optional we can also perform a new paint job and arrange the logistics.



## Your partner for used commercial and industrial refrigeration equipment















# Your partner for used commercial and industrial refrigeration equipment



				yp HSI	N 7471-7	75
BITZER KÜHLM Mi Nennspannung	ade in l	E.C.	GMBH 1	S.Nr. 157	<b>10201</b>	I]Drehzahl
V 3Ph~	Hz	A (max.)	A $(\Delta)$	Α (ΔΔ)	m³/h	min-1
400	50	144	350	585	250	2900
IP 54 ND/HD 378 028-21	max.	19/25 ba	r •			(€
and the second			<u>S66</u> .	01		1

<	Bitz	er		yp HSN .Nr. 1582	7451-8		
BITZER KÜHL	MASC Made in		J GMBH				
Nennspannung	Frequ.	the second s	Anlaufstron	The second s	Fördervol.	Drehz	
V 3Ph~ 400	Hz	A (max.)	Α (Δ)	A $(\Delta \Delta)$	m³/h	min -1	-
	50	98	267	449	192	2900	
460	60	98	267	449	230	3500	
IP 54 ND/HD max. 19 / 28 bar							
				14 11 11 11 11 11 11 11 11 11 11 11 11 1			
				11230			

	Bitze		S	yp HSN .Nr. 1611	1 7471-7 10644	5
BITZER KÜHLM	ASCH ade in E	INENBAU.	GMBH	16	110644	I
Nennspannung V 3Ph~	Frequ. Hz			m Α (ΔΔ)	Fördervol m <sup>3</sup> /h	Drehzahl min <sup>-1</sup>
400	50	144	350	585	250	2900
460	60	144	350	585	300	3500
IP 54 ND/HD max. 19 / 28 bar C €   378 028-21 C €						
			S-0	30		



## Your partner for used commercial and industrial refrigeration equipment











