

# Bitzer 4CC-9.2Y-40S Condensing unit

## Specifications

Brand	Bitzer
Type	4CC-9.2Y-40S Condensing unit
Refrigerant	Freon
kW at 0°C/+40°C	25,3
kW at -5°C/+40°C	21,1
kW at -10°C/+40°C	17,4
kW at -20°C/+40°C	11,4
kW at -30°C/+40°C	7,0
kW at -40°C/+40°C	3,8
Capacity Control	✓
On steel base frame	✓
Pressure safety switches	✓
Hp/Lp/Op	
Liquid receiver	✓
Liquid receiver ltr.	20
Oil separator	✓
Liquid line filter drier	✓
Sight Glass	✓
Solenoid Valve	✓
Control panel	✓
m3 / h	32,5 - 39,2
Remarks	Y.o.b. 2008
Condensing Unit	✓
Sizes	1450x1000x1300 mm (LxWxH)



## Description

### Used Bitzer 4CC-9.2Y-40S Condensing unit

Used Semi-hermetic Reciprocating Condensing unit on Freon. Complete with a Bitzer 4CC-9.2Y -40S semi-hermetic reciprocating compressor, Gökceler AC -RDG 200 A liquid receiver with a volume of 20 liter, condenser with 4 Ziehl-Abegg FE040 -4EK.2F.V7 fans 50 Hz - 0,31 kW - 1320 RPM - diameter 400 mm and pressure and safety switches. The compressor has a displacement of 32,5 m<sup>3</sup>/h at 1450 RPM and 39,2 m<sup>3</sup>/h at 1750 RPM.

\*Why choose for HOSBV? We are not only the largest used refrigeration specialist in Europe, but also, we deliver all equipment including an extensive test, warranty and an industrial cleaning. \*Optionally we can



also perform a new paint job and arrange the logistics.









