

Bitzer 4CC-9.2Y-40S Condensing unit

Specifications

| | |
|--------------------------|---------------------------------|
| Brand | Bitzer |
| Type | 4CC-9.2Y-40S Condensing unit |
| Refrigerant | Freon |
| kW at 0°C/+40°C | 25,3 |
| kW at -5°C/+40°C | 21,1 |
| kW at -10°C/+40°C | 17,4 |
| kW at -20°C/+40°C | 11,4 |
| kW at -30°C/+40°C | 7,0 |
| kW at -40°C/+40°C | 3,8 |
| Capacity Control | ✓ |
| On steel base frame | ✓ |
| Pressure safety switches | ✓ |
| Hp/Lp/Op | |
| Liquid receiver | ✓ |
| Liquid receiver ltr. | 20 |
| Oil separator | ✓ |
| Liquid line filter drier | ✓ |
| Sight Glass | ✓ |
| Solenoid Valve | ✓ |
| Control panel | ✓ |
| m ³ / h | 32,5 - 39,2 |
| Remarks | Y.o.b. 2008 |
| Condensing Unit | ✓ |
| Sizes | 1450x1000x1300 mm (LxWxH) |



Description

Used Bitzer 4CC-9.2Y-40S Condensing unit

Used Semi-hermetic Reciprocating Condensing unit on Freon. Complete with a Bitzer 4CC-9.2Y -40S semi-hermetic reciprocating compressor, Gökceler AC -RDG 200 A liquid receiver with a volume of 20 liter, condenser with 4 Ziehl-Abegg FE040 -4EK.2F.V7 fans 50 Hz - 0,31 kW - 1320 RPM - diameter 400 mm and pressure and safety switches. The compressor has a displacement of 32,5 m³/h at 1450 RPM and 39,2 m³/h at 1750 RPM.

*Why choose for HOSBV? We are not only the largest used refrigeration specialist in Europe, but also, we deliver all equipment including an extensive test, warranty and an industrial cleaning. *Optionally we can



also perform a new paint job and arrange the logistics.





