

Trane BCXB 020

Specifications

| | |
|----------------------------|--|
| Brand | Trane |
| Type | BCXB 020 |
| Product type | Heat pump |
| Capacity kW | 20,1 |
| Capacity Tons | 5,7 |
| Refrigerant | Freon |
| Refrigerant Type | R410A |
| Weight in kg. | 331 kg |
| Sizes | 1810x1000x1680 mm (LxWxH) |
| Compressor(s) type & model | 2x Copeland ZP42K5E-TFD-422 |
| Display | Lumity iPro display |
| Number of fans | 1 |
| Fan specifications | 50/60 Hz - 0,39 kW - 900 RPM - diameter 630 mm |
| Remarks | Y.o.b. 2022 |



Description

Used Trane BCXB 020

Used Trane BCXB 020 heat pump on R410A build in 2022. Complete with 2 Copeland ZP42K5E-TFD-422 scroll compressors, condenser with 1 EBM-Papst A3G630-BM07-H1 fan - 50/60 Hz - 0,39 kW - 900 RPM - diameter 630 mm and a total airflow of 6.000 m³/h, braced heat exchanger as evaporator, Frigo-Mec RV-180X490 receiver, Frigo-Mec 10/S-SP-31-ODS 22 receiver and a control cabinet with a Lumity iPro display.



*All components of this used chiller will be tested on adequate performance, leak free condition (condensing blocks), compressors, fans, control panel, and so forth). Choosing HOSBV means buying with warranty. We perform an industrial cleaning. *If requested we



Your partner for used commercial and industrial refrigeration equipment

are happy to arrange your shipment.



|   | |
|---|-------------------------------------|
| Modelo - Type | BCXB 020XXXX11X1111X11DXX1XX1XXCNAT |
| Matrícula unita - Serial number | PR-5228-G0 |
| Anno costruzione - Manufact year | 2022 |
| Peso in funzionamento (Kg) - Operation weight (Kg) | 331 |
| <small>Contiene gas fluorati ad effetto serra disciplinati dal Protocollo di Kyoto Contains fluorinated greenhouse gases covered by the Kyoto Protocol</small> | |
| Gas refrigerante - Refrigerant/ GWP (ton) | R410a / 2088 |
| Carica refrigerante (Kg) - Refrigerant charge (Kg) | 13 |
| CO2 equivalent (ton) - CO2 equivalents (Ton) | 27,144 |
| Tipo di olio - Oil type | Emkarate RL32 3MMAF |
| Alimentazione elettrica - Power supply | |
| Tensione - Voltage V / Ph / Hz | 400/3/50 |
| F.L.I. MAX (KW) | 9,4 |
| F.L.A. MAX (A) | 16,6 |
| <small>Massima pressione ammissibile (PS) - Max allowable pressure (PS)</small> | |
| Circuito gas - Gas circuit | LP 24,5 bar - HP 43 bar |
| <small>Circuito acqua - Water circuit</small> | |
| Massima temperatura di stoccaggio e trasporto: 55°C Maximum transport and storage temperature: 55°C | |



