

HK Refrigeration H6 23 12/16P

Specifications

| | |
|-------------------------------|--|
| Brand | HK Refrigeration |
| Type | H6 23 12/16P |
| Product type | Drycooler |
| kW | 38,2* |
| Number of Fans | 2 |
| RPM of the Fans | 390/270 |
| Refrigerant | Glycol |
| Air Flow in m ³ /h | 5.800 |
| diameter fans Ø | 630 mm |
| Surface (m ²) | 66,7 |
| Tube volume | 11,1 dm ³ |
| Sizes | 3470x110x600 mm (LxWxH) |
| Remarks | *Capacity is based on a medium inlet temperature of 60°C and an outlet temperature of 40°C |



Description

Used HK Refrigeration H6 23 12/16P

New HK Refrigeration H6 23 12/16P drycooler. Complete with 2 Ziehl-Abegg FB063-NDK.4I.6S - 50 Hz - 0,19/0,09 kW - 390/270 RPM - diameter 630 mm and a total airflow of 5.800 m³/h. The current condenser will be converted into a drycooler and the appropriate flanges will be installed. The drycooler has a capacity of 38,2kW with a medium inlet temperature of 60°C and an outlet temperature of 40°C.

*All components of this used condensor will be tested on adequate functionality, leak free condition (electro engines), condensing block, bearings. Choosing HOSBV means buying with warranty. We perform an industrial cleaning. on demand, we can



Your partner for used commercial and industrial refrigeration equipment

arrange your shipment.



