

DWM DLSGP-40X-EWL & DKSJB-100/EWL/000 Condensing unit

Specifications

| | |
|--------------------------|---|
| Brand | DWM |
| Type | DLSGP-40X-EWL & DKSJB-100/EWL/000 Condensing unit |
| Refrigerant | Freon |
| kW at -5°C/+40°C | 3,9* |
| kW at -10°C/+40°C | 3,2* |
| kW at -20°C/+40°C | 2,0*/7,7** |
| kW at -30°C/+40°C | 1,1*/4,5** |
| kW at -40°C/+40°C | 0,5*/2,1** |
| kW at -45°C/+40°C | 0,3*/1,2** |
| Pressure safety switches | ✓ |
| Hp/Lp/Op | |
| Pressure gauges | ✓ |
| Hp/Lp/Op | |
| Suction accumulator | ✓ |
| Oil separator | ✓ |
| Sight Glass | ✓ |
| Control panel | ✓ |
| m3 / h | DLGSP-40X-EWL - 22,5 m ³ /h & DWM DKSJB-100/EWL/000 - 6,3 m ³ /h |



| | |
|---------|---|
| Remarks | **Capacity of the DWM DLSGP-40X-EWL |
| | *Capacity of the DWM DKSJB-100/EWL/000 |

Description

Used DWM DLSGP-40X-EWL & DKSJB-100/EWL/000 Condensing unit

Used DWM DKSJB-100/EWL/000 water cooled condensing unit. Complete with a DWM Copeland WP2 shell and tube condenser and pressure and safety switches/gauges. The compressor has a displacement of 6,3 m³/h.

Used DWM DLSGP-40X-EWL water cooled condensing unit on Freon. Complete with a DWM WR4 shell and tube condenser, oil separator, suction accumulator and pressure and safety switches/gauges. The compressor has a displacement of 22,5 m³/h.

Further the two condensing units comes with a shared control cabinet.

*Why choose for HOSBV? Were not only the largest used refrigeration specialist in Europe, but also, we deliver all equipment including an extensive test, warranty and industrial cleaning.

*Optional we can also perform a new paint job and arrange the logistics.





