

# Bock HG6/1240-4 S (x2) cool package

## Specifications

Brand	Bock
Type	HG6/1240-4 S (x2) cool package
Refrigerant	Freon
Refrigerant type	r404a / r507a
kW at 0°C/+40°C	174,4
kW at -5°C/+40°C	144,2
kW at -10°C/+40°C	117,8
kW at -20°C/+40°C	75,6
kW at -30°C/+40°C	45,2
On steel base frame	✓
Pressure safety switches	✓
Hp/Lp/Op	
Pressure gauges	✓
Hp/Lp/Op	
Liquid receiver	✓
Oil level system AC&R	✓
Liquid line filter drier	✓
Package / Rack	✓



## Description

### Used Bock HG6/1240-4 S (x2) cool package

Used cool package with a Bock HG6/1240-4 S (x2) semi hermetic reciprocating compressor. \*Why choose for HOSBV? Were not only the largest used refrigeration specialist in Europe, but also, we deliver all equipment including an extensive test, warranty and industrial cleaning. Optional we can arrange shipment and export documents.



**Performance data table**

Application: Refrigeration & AC  
 Reference temperature: Dew point  
 Supply frequency: 50 Hz  
 Voltage: 400 V  
 Suction gas temperature: 20 °C  
 Subcooling (outside cond.): 0 K

tc [°C]		to [°C]								
		10.0	5.0	0.0	-5.0	-10.0	-15.0	-20.0	-25.0	-30.0
30.0	Q [W]		123000	103000	85300	70000	56800	45300	35600	27400
	P [kW]		27.20	26.00	24.50	22.80	20.90	18.90	16.80	14.80
	I [A]		53.00	51.40	49.50	47.40	45.20	42.90	40.80	38.70
35.0	Q [W]		114000	95000	78700	64500	52100	41600	32600	25000
	P [kW]		29.90	28.20	26.30	24.20	22.00	19.70	17.30	15.00
	I [A]		56.00	54.30	51.70	49.10	46.40	43.80	41.30	39.00
40.0	Q [W]		105000	87200	72100	58900	47600	37800	29600	22800
	P [kW]		32.30	30.20	27.90	25.40	22.90	20.30	17.70	15.20
	I [A]		60.10	57.10	53.90	50.70	47.50	44.50	41.70	39.20
45.0	Q [W]		95300	79500	65600	53500	43100	34200	26700	20400
	P [kW]		34.60	32.10	29.40	26.60	23.70	20.90	18.10	15.40
	I [A]		63.50	59.70	55.90	52.10	48.50	45.10	42.00	39.30
50.0	Q [W]		86300	71800	59100	48100	38700	30600	23800	18100
	P [kW]		36.90	33.90	30.70	27.90	24.50	21.40	18.40	15.50
	I [A]		66.70	62.30	57.80	53.50	49.50	45.70	42.40	39.40
55.0	Q [W]		77400	64200	52700	42800	34300	27100	21000	15900
	P [kW]		38.80	35.40	32.00	28.60	25.20	21.80	18.60	15.60
	I [A]		69.80	64.70	59.60	54.80	50.30	46.20	42.60	39.50