

Carrier 30 RB 262-0273-PEE

Specifications

Brand	Carrier
Туре	30 RB 262-0273-PEE
Product type	Air Cooled Chiller
Capacity kW	270
Capacity Tons	76,8
Refrigerant	Freon
Refrigerant Type	R 410a
Hydronic Module	✓
Weight in kg.	2292
Sizes	2400x2250x2350 mm
Compressor(s) type &	Performer SH300A4ACA
model	
Display	Carrier pro-dialog plus
Remarks	y.o.b. 2007
Remarks	See pictures with
	running hours



Description

Used Carrier 30 RB 262-0273-PEE

Used Carrier 30 RB 262-0273-PEE air cooled chiller. Complete with 4 Performer scroll compressors SH300A4ACA. Shell & tube evaporator/exchanger 110 ltr. 4 Axial fans with a total airflow of 18.056 l/s and Pro-dialog plus controling. Hydromodule with dubbel pump Tee 50 Hz - 4 kW - 2915 RPM and expansion vessel 50 ltr.

*All components of this used chiller will be tested on good working, leak free condition (condensing blocks), compressors, fans, control panel, etcetera). Choosing HOSBV means buying with warranty. We perform a industrial cleaning and rust spots will be covered. Also, we can arrange your shipment.



Your partner for used commercial and industrial refrigeration equipment







WURERO DE SERVICE SERVICE MUBER DELENTALMER	
1 - (FR) NUMERO DE SERIE (EN) SERIA NUMBER (DE) SERIENNUMER 2 - MODELL NUMBER NODELLNUMER 30RB02620273-PEE	
3 -VARIANTE VARIANT 30RB	
4 - ANKE DE FARRICATION ET DATE D'ESSAI YEAN OF MANYATURING AND ISES DATE HERSTELLUNKSLAM UND DATUN	
S- FUTURE - KEDIUM R 410 a	
7 - CHARGE CHART A BIC 29.0 Kg / 29.0 Kg / * Kg	
9 - FUIDE O'INERTAGE THENTEN KEDINI NEUTRALISTERNING-KEDINI 23 AZOTE - NITROGEN - STICKSTOFF	
21 - HAUTE PRESSION 22 - BASSE PRESSION HIGH PRESSURE 22 - BASSE PRESSION 10 -PRESSIELE RIW/WAY HOCHORUKSETE LOW PRESSURE	
ALCUMABLE PRESSURE NIN/MAX ZULASSIGE NIN/MAX - DRUCKE (PS) -0.9 / 44.2 han	
ALLOWABLE TEMPERATURE NIN MAX ZULASSIGE NIN/NAX TEMPERATUREN (TS) -20.0 / 68.0 °C	
PRESSURE SWITCH SETTING DRUCKSCHALTER-SOLDRICK	
SAFETY RELIEF VALVE SETTING DAT	
UNTITIER TERMENT OF L'UNITE 30.0 bar	
15 - TRAESON WIDTAGE 400 V 100 - 17.0 bar	
PROUBLY ~ 50 Hz 18 t Home PHASES 3	
**	
ARTIER SCS. CHILDREN CHILLE CHILDREN CHILDREN CHILDREN CHILDREN CHILDREN CHILDREN CHILDREN CHILLE CHILDREN CHILDREN CHILLE CHILDREN CHILLE CHILDREN CHILDREN CHILDREN CHILDREN CHILDREN CHILDREN CHILDREN	
STATES OF AMERICA	



Your partner for used commercial and industrial refrigeration equipment



MODEL: SH300A4	DMPRESSOR AACA 41218		
THERMALLY PROTECTED SYSTEM	SYSTEME DE PROTECTION 1	THERMIQUE	
460 V 3 ~ 60 Hz 65 A Max	880-400 V 3 ~ 50 Hz LR 260 A	c PL us	
P.E.D. Ps = 30.2 bar Marking Ts max = 51°C L.P. side Ts min = -35 °C			
LUBRICANT: POE OIL	160SZ		
CAUTION Use of hydrocarbon ATTENTION L'utilisation d'hydrocarbon le fabricant	s is not approved by the mai procarbures n'est pas autoris	nufacturer sée par	
REFRIGERANT: R410	A		



hy save Liquid Pressure Amplification				
	Refrigeration "Floating Head Pressure Techn World Head Quarters - Hysave United Kingdom w.hysave.com T:+44 (0) 1761 416 123 - F: +44 (0) 1761 417			
CAT. NO.	SEC-DO-DND			
SPEC.	JAN JE CX DECKEL			
НР	.25	S. A		
VOLTS	2200 360-440	R UC		
AMPS	14.04.3	LRE A.A.A.		
R.P.M.	2050	REL		
FRAME	ABOYZ HZ SO PH J	UFA DOR T SN		
SER. F:	CODE DES CLASS	MAN FOR		
NEMA N	OM. EFF. % P.F. %	*		
RATING	ALS-SONT	CE		
CC	USABLE AT 208V A			
BEARING	a tota allo serve allo serve allo	SP®		
ENCL	HERE SN COVERTER	75		
	-NP1762			
		all and a		
a.	· · · · · · · · · · · · · · · · · · ·			



Your partner for used commercial and industrial refrigeration equipment







