

Carrier 30 RBS 140

Specifications

Brand	Carrier
Tipo	30 RBS 140
Product type	Air Cooled Chiller
Capacidad kW	139,6
Capacity Tons	39,7
Refrigerante	Freon
Tipo de Refrigerante	R410a
Pump	✓
Sizes	2060x2270x1360 mm (LxWxH)
Compressor(s) type & model	4x Copeland ZP154KQE-TFD-604
Display	Carrier pro-dialog plus
Number of fans	2
Fan specifications	50 Hz - 0,54/0,18 kW - 720/500 RPM
Remarks	y.o.b. 2013
Stock	1



Description

Used Carrier 30 RBS 140

Used Carrier 30 RBS 140 air cooled chiller with 4x Copeland ZP154KQE-TFD-604 scroll compressors. Condensor with 2 fans with max air flow of 10.600 m³/h. Pump Grundfos max waterflow 30 m³/h. This chiller has a Carrier Prodialog plus controller.

*All components of this used chiller will be tested on good working, leak free condition (condensing blocks), compressors, fans, control panel, etcetera). Choosing HOSBV means buying with warranty. We perform an industrial cleaning and rust spots will be covered. Also, we can arrange your shipment.



1 - (FR) NUMERO DE SERIE (EN) SERIAL NUMBER (DE) SERIENNUMMER	M2013016467		
2 - MODELE - MODEL MODELLNUMMER	30RBS-140-0565-PE -		
3 - VARIANTE VARIANT VARIANTE	NGAC		
4 - ANNEE DE FABRICATION ET DATE D'ESSAI YEAR OF MANUFACTURING AND TEST DATE HERSTELLUNGSJAHR UND DATUM	28/05/2013	CE 0062	
25 - FLUIDE PENDANT LE TRANSPORT MEDIUM DURING THE TRANSPORT FLUSSIGKEIT WAHREND DES TRANSPORTES	R410a	25.0	Kg
5 - FLUIDE - MEDIUM KALTENITTEL	R 410 a	6 - GROUPE - GROUP GRUPPE	2
7 - CHARGES CIRCUIT A/B MEDIUM CHARGE A/B KREISLAUF A/B	12.50	Kg /	12.50 Kg
9 - FLUIDE D'INERTAGE INERTING MEDIUM NEUTRALISIERUNG-MEDIUM	23 AZOTE - NITROGEN - STICKSTOFF		
10 - PRESSION ADMISSIBLE MIN/MAX ALLOWABLE PRESSURE MIN/MAX ZULASSIGE MIN/MAX - DRUCKE	(PS) -1.0 / 44.20 bar	22 - BASSE PRESSION LOW PRESSURE NIEDERDRUCKSEITE	-1.0 / 28.00 bar
11 - TEMPERATURE ADMISSIBLE MIN/MAX ALLOWABLE TEMPERATURE MIN/MAX ZULASSIGE MIN/MAX - TEMPERATUREN	(TS) -20.0 / 68.0 °C		-20.0 / 48.0 °C
12 - PRESSION DE DECLENCHEMENT DES PRESSOSTATS PRESSURE SWITCH SETTING DRUCKSCHALTER-SOLLDRUCK	44.2 bar		* bar
13 - PRESSION DE DECLENCHEMENT DES SOUPAPES SAFETY RELIEF VALVE SETTING SICHERHEITSENTWENTIL - SOLLDRUCK	* bar		* bar
14 - PRESSION D'ESSAI D'ETANCHEITE DE L'UNITE LEAKTEST - DRUCK DES GERATS			17.0 bar
15 - TENSION VOLTAGE SPANNUNG	400 V	+ 10% - 10%	16 - PHASES PHASES PHASEN
17 - FREQUENCE FREQUENCY FREQUENZ	~ 50 Hz	18 - I MAXIMALE MAXIMUM AMPS MAXIMAL STROM	139.70 / * A
19 - PUISSANCE ABSORBEE MAX MAX POWER INPUT LEISTUNGSAUFNAHME	65.40 / *		KW
20 - POIDS NET NET WEIGHT NETTOGEWICHT	881		Kg
24 - PRESSION DE DECLENCHEMENT DES DISQUES DE RUPTURE RUPTURE DISK SETTING EINSTELLDRUCK DER RISSSCHREIBEN	* bar		* bar

Carrier MANUFACTURED IN FRANCE BY
CARRIER SCS - 01120 MONTLUEL - FRANCE
AN AFFILIATED COMPANY OF CARRIER CORPORATION
FARMINGTON CT, USA





