

# Carrier 30 RA 240

## Specifications

Brand	Carrier
Tipo	30 RA 240
Product type	Air Cooled Chiller
Capacidad kW	245,0
Capacity Tons	69,7
Refrigerante	Freon
Tipo de Refrigerante	R407C
Pump	✓
Peso kg.	2395
Sizes	3310x2270x1670 mm (LxWxH)
Compressor(s) type & model	6x Performer SZ185W4PC
Display	Pro-dialog Plus
Number of fans	4
Remarks	Y.o.b. 2005
Stock	1



## Description

### Used Carrier 30 RA 240

Used Carrier 30 RA 240 air cooled chiller. Complete with 6 Performer SZ185W4PC scroll compressors and a condenser using 4 fans with a total airflow of 20.908 m<sup>3</sup>/h, pumps, plate heat exchanger and a pro dialog plus panel.

\*All components of this used chiller will be tested on adequate performance, leak free condition (condensing blocks), compressors, fans, control panel, and so forth). Choosing HOSBV means buying with warranty. We perform an industrial cleaning. If requested we can arrange your shipment.



99PS - 525 - - - 172 - - EE - A

1 - (FR) NUMERO DE SERIE (EN) SERIAL NUMBER (DE) SERIENNUMMER  
**12W512709**

2 - MODELE - MODEL MODELNUMMER  
**30RA-240-B0520-PEE--**

3 - VARIANTE - VARIANT VARIANTE  
**30RA**

4 - ANNEE DE FABRICATION ET DATE D'ESSAI YEAR OF MANUFACTURING AND TEST DATE HERSTELLUNGSJAHR UND DATUM  
**2005/09/19**

5 - FLUIDE - MEDIUM KALTEMITTEL  
**R 407C**

6 - GROUPE - GROUP GRUPPE  
**2**

7 - CHARGES CIRCUIT A KALTEMITTELFULLUNG KREISLAUF 1  
**29,0 kg**

8 - CHARGES CIRCUIT B KALTEMITTELFULLUNG KREISLAUF 2  
**29,0 kg**

9 - FLUIDE DE CONFINEMENT CONFINEMENT MEDIUM SICHERHEITTSFILLUNGS-MEDIUM  
**23 --AZOTE--NITROGENE--**

10 - PRESSION ADMISSIBLE MIN/MAX ALLOWABLE PRESSURE MIN/MAX ZULASSIGE MIN/MAX - DRUCKE  
**(PS) - 0,9 32,0 bar - 0,9 25,0 bar**

11 - TEMPERATURES ADMISSIBLE MIN/MAX ALLOWABLE TEMPERATURE MIN/MAX ZULASSIGE MIN/MAX - TEMPERATUREN  
**(TS) - 20 72 °C - 20 62 °C**

12 - PRESSION DE DECLENCHEMENT DES PRESSOSTATS PRESSURE SWITCH SETTING DRUCKSCHALTER-SOLLDRUCK  
**29,0 bar / bar**

13 - PRESSION DE DECLENCHEMENT DES SOUPAPES SAFETY RELIEF VALVE SETTING SICHERHEITSVENTIL - SOLLDRUCK  
**/ bar 25,0 bar**

14 - PRESSION D'ESSAI D'ETANCHEITE DE L'UNITE UNIT LEAK TEST PRESSURE LECKTEST - DRUCK DES GERATS  
**+ 15,0 bar**

15 - TENSION SPANNUNG  
**400 V**

16 - PHASES PHASEN  
**3**

17 - FREQUENCE FREQUENCY FREQUENZ  
**50 Hz**

18 - I MAXIMALE MAXIMUM AMPS MAXIMALSTROM  
**205,9 / A**

19 - PUISSANCE ABSORBEE MAX MAX POWER INPUT LEISTUNGSANNAHME  
**119,6 / kW**

20 - POIDS NET NET WEIGHT NETTOWICHT  
**2395 kg**

24 - PRESSION DE DECLENCHEMENT DES DISQUES DE RUPTURE RUPTURE DISKS SETTING EINSTELLDRUCK DER BERSTSCHEIBEN  
**/ bar / bar**

**Carrier**

MANUFACTURED IN FRANCE BY  
**CARRIER s.a.s - 01120 - MONTLUEL - FRANCE**  
 A SUBSIDIARY OF CARRIER CORPORATION  
 SYRACUSE NEW YORK UNITED STATES OF AMERICA





