

DWM DLSGP-40X-EWL (x2) & D4DA5-200X-AWM/D (x2) & D3DS5-150X-AWM/D (x1)

Specifications

Marca	DWM
Tipo	DLSGP-40X-EWL (x2) & D4DA5-200X-AWM/D (x2) & D3DS5-150X-AWM/D (x1)
Refrigerante	Freon
kW at -30°C/+40°C	78,1*
kW at -40°C/+40°C	46,9*
Control de capacidad	✓
Sober Bancada	✓
Presostatos	✓
Acumulador de succión	✓
Separador de aceite	✓
Sistema de nivel de aceite	✓
La línea de líquido filtro secador	✓
Mirilla	✓
Comentarios	Y.o.b. 2012
Comentarios	*Capacity based on all the compressors together.
Package / Rack	✓



	(LxWxH)
Standaard	2820x1260x2250 mm

Description

Used DWM DLSP-40X-EWL (x2) & D4DA5-200X-AWM/D (x2) & D3DS5-150X-AWM/D (x1)

Used DWM Copeland rack for low and medium temperature application. Complete with 5 DWM Copeland compressoren: DLSP-40X-EWL (x2), D4DA5-200X-AWM/D (x2), D3DS5-150X-AWM/D (x1). Furthermore the unit contains a suction accumulator, liquid line filter dryer, oil separator, AC&R oil level regulator for every compressor, AC&R S-9109-CE oil reservoir, Danfoss ADAP KOOL frequency converter and a Danfoss ADAP-KOOL Gateway AKA 245. Capacity based on all the compressors together.

*Why choose for HOSBV? We are not only the largest used refrigeration specialist in Europe, but also, we solely deliver our orders after performing an extensive test and an industrial cleaning. If requested we are happy to arrange your logistics.















