

# DWM D2DB3-50X-AWM/D Condensing unit

## Specifications

|                                       |                                    |
|---------------------------------------|------------------------------------|
| Marca                                 | DWM                                |
| Tipo                                  | D2DB3-50X-AWM/D<br>Condensing unit |
| Refrigerante                          | Freon                              |
| kW at -5°C/+40°C                      | 18,5                               |
| kW at -10°C/+40°C                     | 15,0                               |
| kW at -20°C/+40°C                     | 9,4                                |
| kW at -30°C/+40°C                     | 5,3                                |
| kW at -40°C/+40°C                     | 2,6                                |
| kW at -45°C/+40°C                     | 1,7                                |
| Sober Bancada                         | ✓                                  |
| Presostatos                           | ✓                                  |
| Recipiente de líquido                 | ✓                                  |
| Separador de aceite                   | ✓                                  |
| La línea de líquido filtro<br>secador | ✓                                  |
| Mirilla                               | ✓                                  |
| m3 / h                                | 28,0                               |
| Comentarios                           | Y.o.b. 2005                        |
| Condensing Unit                       | ✓                                  |
| Tamaños                               | 760x990x660 mm<br>(LxWxH)          |
| Stock                                 | 1                                  |



## Description

### Used DWM D2DB3-50X-AWM/D Condensing unit

Used DWM D2DB3-50X-AWM/D semi-hermetic reciprocating condensing unit on Freon. Complete with a condenser with 2 Hidria 121 0311-4-0132 fans - 50/60 Hz - 0,11/0,15 kW - 1360/1490 RPM - diameter 350 mm, Copeland liquid receiver with a volume of 11,5 liter, Henry S-5587-CE oil separator and a liquid line filter drier. The compressor has a displacement of 28 m<sup>3</sup>/h.

\*Why choose for HOSBV? We are not only the largest used refrigeration specialist in Europe, but also, we deliver all equipment including an extensive test, warranty, and industrial cleaning. \*Optional we can also perform a new paint job and arrange



the logistics.





