

# Bitzer 4N-20.2

## Specifications

|                            |                            |
|----------------------------|----------------------------|
| Marca                      | Bitzer                     |
| Tipo                       | 4N-20.2                    |
| Refrigerante               | Freon                      |
| kW at 0°C/+40°C            | 45,8                       |
| kW at -5°C/+40°C           | 38,1                       |
| kW at -10°C/+40°C          | 31,3                       |
| kW at -20°C/+40°C          | 20,4                       |
| kW at -30°C/+40°C          | 12,4                       |
| kW at -40°C/+40°C          | 6,7                        |
| Presostatos                | ✓                          |
| Recipiente de líquido      | ✓                          |
| Recipiente de líquido ltr. | 54                         |
| Separador de aceite        | ✓                          |
| La línea de líquido filtro | ✓                          |
| secador                    |                            |
| Mirilla                    | ✓                          |
| m <sup>3</sup> / h         | 56,1                       |
| Comentarios                | Y.o.b. 1997                |
| Tamaños                    | 1750x550x940 mm<br>(LxWxH) |
| Stock                      | 1                          |



## Description

### Used Bitzer 4N-20.2

Used Bitzer 4N-20.2 semi-hermetic reciprocating compressor on Freon. Complete with a Bitzer F 550 T liquid receiver with a volume of 54 liters, oil separator, liquid line filter drier, sight glass and pressure and safety switches. The compressor has a displacement of 56,1 m<sup>3</sup>/h.

\*Why choose for HOSBV? Were not only the largest used refrigeration specialist in Europe, but also, we deliver all equipment including an extensive test, warranty and industrial cleaning.

\*Optional we can also perform a new paint job and arrange the logistics.



