

Copeland ZR12M3E-TWD-551 (x2) Condensing unit

Specifications

| | |
|---------------------------------------|--|
| Marca | Copeland |
| Tipo | ZR12M3E-TWD-551 (x2) Condensing unit |
| Refrigerante | Freon |
| kW at +10°C/+40°C | 71,4 |
| kW at 0°C/+40°C | 49,1 |
| kW at -5°C/+40°C | 40,2 |
| kW at -10°C/+40°C | 32,5 |
| kW at -20°C/+40°C | 20,5 |
| Sober Bancada | ✓ |
| Presostatos | ✓ |
| Recipiente de líquido | ✓ |
| Recipiente de líquido ltr. | 35 |
| La línea de líquido filtro secador | ✓ |
| Mirilla | ✓ |
| Panel de control | ✓ |
| m ³ / h | 50 Hz - 57,6 m ³ /h / 60 Hz - 69,4 m ³ /h |
| Condensing Unit | ✓ |
| Stock | 1 |



Description

Used Copeland ZR12M3E-TWD-551 (x2) Condensing unit

Used condensing unit on Freon. Complete with 2 Copeland ZR12M3E-TWD-551 scroll compressors, condenser with 6 EBM-Papst S4E400-AP02-83 fans - 50/60 Hz - 0,16/0,24 kW - 1430/1700 RPM - diameter 400 mm, liquid receiver with a volume of 35 liter, pressure and safety switches, liquid line filter drier and a control cabinet. The compressors have a total displacement of 57,6 m³/h at 50 Hz & 69,4 m³/h at 60 Hz.

*Why choose for HOSBV? Were not only the largest used refrigeration specialist in Europe, but also, we deliver all equipment including an extensive test, warranty and industrial cleaning.



*Optional we can also perform a new paint job and arrange the logistics.





