

Güntner GGDC CP

080.1/14-32-3949306M

Specifications

Marca	Güntner
Tipo	GGDC CP 080.1/14-32-3949306M
Tipo de producto	Air Cooled Gas Cooler
Capacidad kW	209,2*
Número de aficionados	4
RPM de los ventiladores	490
Refrigerante	CO2
Flujo de aire in m³/h	36.300
ventiladores de diámetro	800 mm
Ø	
Superficie (m2)	1237,1
Volumen del tubo	74,7 dm³
Tamaños	5300x1500x1640 mm (LxWxH)
Comentarios	Y.o.b. 2020
Remarks	*Capacity is based on a transcritical system with a CO2 inlet temperature of 120°C and an outlet temperature of 34°C
Stock	1



Description

Used Güntner GGDC CP 080.1/14-32-3949306M

Used Güntner GGDC CP 080.1/14-32-3949306M air-cooled gas cooler. Complete with 4 Ebm-papst S3G800-CA77-49 fans - 50/60 Hz - 0,24 kW - 490 RPM - diameter 800 mm and a total airflow of 36.300 m³/h.

This gas cooler worked with the following compressor set 17561

*All components of this used condenser will be tested on adequate functionality, leak-free condition (electro engines), condensing block and



bearings. Choosing HOS BV means buying with warranty. We perform an industrial cleaning. on demand, we can arrange your shipment.



EAC		
Projektnummer - Project number Druckgerätebezeichnung - Pressure equipment type UI Nummer - UI number Seriennummer - Serial number Herstellungsjahr - Year of manufacture Ventilator/Drehzahl/Stromaufn. - Fan/ID/Speed/Current Umgebungstemperatur - Ambient air temperature Volumen - Volume (V) Max. zulässiger Druck (PS) Zulässige min./max. Temperatur (TS) Permissible min./max. temperature (TS) Prüfdruck (PT) / Prüfmedium Test pressure (PT) / Test medium Prüfdatum - Test date Fluidgruppe / Zustand - Group of fluid / State Total el. power consumption: 0.53 kW		
101141687	GGDC CP 080.1/14-32-3949306M	
3949306	50416115946.00085	
2020	VT03062U.1 / 2497 / 415 min -1 / 0.7 A	
-30 °C / +50 °C	74.7 l	
120 / 0 bar	0 / -1 bar	
-50 °C / +150 °C	-50 °C / +40 °C	
171.6 bar / Druckluft - Compressed air		
2020-11-10		
2 / gasförmig - gaseous		





