


Mycom N200VLDD-MS

Specifications

Marca	Mycom
Tipo	N200VLDD-MS
Refrigerante	NH 3 (ammonia)
kW at +10°C/+40°C	1654,4
kW at 0°C/+40°C	1157,0
kW at -5°C/+40°C	954,7
kW at -10°C/+40°C	779,8
kW at -20°C/+40°C	502,0
kW at -30°C/+40°C	303,9
kW at -40°C/+40°C	167,6
kW at -45°C/+40°C	117,7
Piston Descargador	✓
Control de capacidad	✓
Sober Bancada	✓
Recipiente de líquido ltr.	60 Hz - 355 kW - 3565 RPM
Separador de aceite	✓
Panel de control	✓
Comentarios	Y.o.b. 2008
Tamaños	3600x1200x1900 mm (LxWxH)
Stock	4



Description

Used Mycom N200VLDD-MS

Used Mycom N200VLDD-MS screw compressor skid on NH3 (Ammonia). Complete with a Teco ASJC-PA electric motor - 60 Hz - 355 kW - 3565 RPM, Mayekawa T-A1906 oil separator, Mycom M50P-M oil pump and a Mycom MYPRO-CP3 controller.

*Why choose for HOSBV? Were not only the largest used refrigeration specialist in Europe, but also, we deliver all equipment including an extensive test, warranty and industrial cleaning.

*Optional we can also perform a new paint job and arrange the logistics.

