

Helpman LEX 10-N

Specifications

Marca	Helpman
Tipo	LEX 10-N
Capacidad kW	3,7
Refrigerante	Freon
Número de aficionados	2
Fan del Espacio in mm	7
Descongelación	None
m ³ /h	3130
Tamaños	1100x450x430 mm
Comentarios	Surface 13,5 m2
Volume	6,0 dm ³
Peso	45,5 kg
Stock	1



Description

Used Helpman LEX 10-N

Used Helpman LEX 10-N with 2 fans, 0,03kW 1665 RPM. *All components of this used evaporator will be tested on good working, leak free condition (electro engines), coils, bearings) Choosing HOSBV means buying with warranty. We perform a industrial cleaning and rust spots will be covered. Also, we can arrange your shipment.



Blow Through Unit Coolers 1.5 - 40 kW LEX

Nominal Capacities (kW)

Cooler type	R 22		R 134a		R 404A		For reference only	
	frosted DT ₁	frosted DT ₂	frosted DT ₁	frosted DT ₂	frosted DT ₁	frosted DT ₂	dry conditions DT ₁	dry conditions DT ₂
Fin spacing 4 mm								
LEX 2-4	1.5	1.3	1.5	1.3	1.1	1.1	1.3	1.6
LEX 4-4	1.9	1.5	1.9	1.5	1.7	1.3	1.6	1.6
LEX 6-4	2.8	2.4	2.8	2.4	2.4	2.1	2.5	2.5
LEX 8-4	4.2	4.1	4.2	4.1	4.1	3.8	4.1	4.1
LEX 10-4	4.7	4.4	4.9	4.5	4.1	3.8	4.2	4.2
LEX 12-4	5.9	5.6	6.2	5.8	5.1	4.9	5.4	5.4
LEX 14-4	6.5	6.4	7.1	6.7	5.7	5.6	6.2	6.2
LEX 16-4	8.7	8.4	9.3	8.9	7.5	7.3	8.1	8.1
LEX 18-4	9.7	9.7	9.8	9.8	8.5	7.9	8.8	8.8
LEX 20-4	12.8	10.8	12.7	11.2	9.4	11.0	11.0	11.0
LEX 22-4	16.1	13.0	16.4	14.0	11.3	13.4	13.4	13.4
LEX 24-4	20.0	16.1	19.2	17.4	14.0	16.7	16.7	16.7
LEX 26-4	26.0	23.0	26.0	22.6	20.0	22.6	22.6	22.6
LEX 28-4	32.8	29.0	33.2	28.5	25.2	28.9	28.9	28.9
LEX 30-4	40.3	32.5	38.5	35.0	29.3	33.4	33.4	33.4
Fin spacing 7 mm								
LEX 2-7	1.3	1.2	1.3	1.1	1.0	1.2	1.2	1.2
LEX 4-7	1.7	1.4	1.7	1.5	1.2	1.4	1.4	1.4
LEX 6-7	2.5	2.2	2.5	2.2	1.9	2.2	2.2	2.2
LEX 8-7	4.1	3.7	4.3	3.6	3.3	3.7	3.7	3.7
LEX 10-7	3.7	3.6	4.0	3.2	3.2	3.5	3.5	3.5
LEX 12-7	5.0	4.9	5.3	4.4	4.4	4.6	4.6	4.6
LEX 14-7	5.5	5.5	6.0	4.8	4.8	5.2	5.2	5.2
LEX 16-7	7.4	7.3	8.0	6.4	6.3	7.0	7.0	7.0
LEX 18-7	8.5	7.8	8.8	7.4	6.8	7.6	7.6	7.6
LEX 20-7	11.4	10.0	11.4	9.9	9.7	9.9	9.9	9.9
LEX 22-7	14.5	12.4	14.3	12.6	10.7	12.4	12.4	12.4
LEX 24-7	18.1	15.6	17.8	15.7	13.5	15.6	15.6	15.6
LEX 26-7	22.5	21.2	23.4	19.8	16.4	20.4	20.4	20.4
LEX 28-7	28.5	26.5	29.3	24.8	23.0	25.5	25.5	25.5
LEX 30-7	36.5	31.9	35.9	31.7	27.0	31.2	31.2	31.2

Capacities
 -Lightly frosted coil
 -Relative humidity 65 %
 -Suction gas superheating 62 % of the temperature difference (DT₁)
 with a minimum of 3.5 K