

Bluebox/Western Tetris DC 33.4 ST 1PS

Specifications

Brand	Bluebox/Western
Type	Tetris DC 33.4 ST 1PS
Product type	Air Cooled Chiller
Capacité kW	324,0
Capacity Tons	92,2
Réfrigérant	Freon
Refrigerant Type	R410A
Liquid buffer tank	✓
Pump	✓
module hydraulique	✓
Weight	2275
Sizes	3720x2300x2400 mm (LxWxH)
Compressor(s) type & model	Bitzer GSD80385VAB4 (x4)
Number of fans	5
Fan specifications	diameter 800 mm
Remarks	Y.o.b. 2013
Stock	1



Description

Used Bluebox/Western Tetris DC 33.4 ST 1PS

Used Bluebox Tetris DC 33.4 ST 1PS air cooled chiller. Complete with 4 Bitzer scroll compressors, condenser with 5 fans, plate heat exchangers, liquid receivers, liquid line filter driers, Lowara PLM112B14S2/355 E3 water pump, liquid expansion tank, Carel pCO5 programmable controllers and Carel EVD4 drivers for electronic expansion valves. The unit runs on R410A and has two refrigeration circuits. The total airflow is 105.000 m³/h.


*All components of this used chiller will be tested on adequate performance, leak free condition (condensing blocks), compressors, fans, control panel, and so forth). Choosing HOSBV means buying with warranty. We perform a



Your partner for used commercial and industrial refrigeration equipment

industrial cleaning. if requested we can arrange your shipment.



BLUE BOX AIR WITH CARE <small>A COMPANY IN THE SWEGON GROUP</small>		Via Valletta, 5 30010 Cantarana di Cona (VE) ITALY Tel: (+39) 0426921111	 1370
Modello/Model Model/Modèle Tetriss DC 33.4 ST 1PS			
Tipo refrigerante Refrigerant type Kältemitteltyp Type réfrigérant	IP quadro elettrico IP electrical panel IP Schaltschrank IP tableau électrique	Metricola Serial number Seriennummer Matricule	
.R410A	X4	BBOX084535	
Corrente massima assorbita Max. absorbed current Max. Stromaufnahme Courant maxi absorbée	Corrente massima di spunto Max. starting current Max. Anlaufstrom Courant maxi de démarrage		
.302,4 A	.498,4 A		
Tensione-Fasi-Frequenza Voltage-Phases-Frequency Spannung-Phasen-Frequenz Tension-Phases-Fréquence	Tensione circuiti ausiliari Auxiliary circuit voltage Steuerspannung Tension circuit auxiliaires		
.400V 3 ~ 50Hz	.230-24V ~ 50Hz		
Numero circuiti refrigerante Refrigerant circuit number Anzahl der Kältekreise Nombre circuits réfrigérant	Press. max refriger. alta/bassa Max. Refrig. pressure high/low Max. N/n Kältemittelbetriebsdruck Pression maxi réfrig. haute/basse		
	4.500 kPa 2.600 kPa 45 bar 26 bar		
Press. massima circuito idraulico Max. hydraulic circuit pressure Max. zulässiger Druck im Wassersystem Press. Maxi circuit hydraulique	Data di produzione Date of manufacture Herstellungsdatum Date de production		
.600 kPa 6bar	.07.03.2013		
Carica refrigerante per circuito(kg) / Charge réfrigérant par circuit(kg) Kältemittel-Füllmenge je Kältekreis(kg) / Füllmenge réfrigérant par circuit(kg)			
C1 34,6	C2 16,4	C3	C4
Manufactured by Blue Box Group S.r.l.			





