

## Bitzer 6G-40.2Y (x2) / 66G-80.2Y

### Specifications

Marque	Bitzer
Le type	6G-40.2Y (x2) / 66G-80.2Y
Réfrigérant	Freon
kW at 0°C/+40°C	205,0
kW at -5°C/+40°C	170,7
kW at -10°C/+40°C	140,6
kW at -20°C/+40°C	92,0
kW at -30°C/+40°C	55,9
kW at -40°C/+40°C	29,9
Démarrage à vide	✓
Contrôle de capacité	✓
Sur le châssis en acier	✓
Réservoir de liquide	✓
Réservoir de liquide ltr.	105
Séparateur d'huile	✓
Liquid déshydrateur	✓
ligne	
Voyant	✓
Electrovanne	✓
m3 / h	50 Hz - 253,6 m <sup>3</sup> /h / 60 Hz - 305,8 m <sup>3</sup> /h
Package / Rack	✓
Tailles	2110x810x1400 mm (LxWxH)
Stock	3



### Description

#### Used Bitzer 6G-40.2Y (x2) / 66G-80.2Y

Used Bitzer 6G-40.2Y (x2) & 66G-80.2Y semi-hermetic reciprocating compressor on Freon. Complete with a Bitzer F1052T liquid receiver, ESK Schultze OS 67FH oil separator and a liquid line filter drier. The compressor has a displacement of 253,6 m<sup>3</sup>/h at 50 Hz & 305,8 m<sup>3</sup>/h at 60 Hz.

\*Why choose for HOSBV? We are not only the largest used refrigeration specialist in Europe, but also, we deliver all equipment solely if it has passed our extensive test. Warranty and industrial cleaning are included in your purchase. \*If requested we are happy to arrange your shipment.





